

## 3M™ Dual Conductor Metal Wrist Strap for Monitors

The Dual Conductor Metal Wrist Straps are durable premium performance metal wrist bands that create a reliable electrical contact to the user's wrist. The wrist band provides 360-degree protection and three size options allow for conformance to most user's wrists. Meets the resistance requirements of ANSI/ESD S20.20-2014, EIA 625.



### **WARNING:**

All 3M Wrist Straps should not be used in areas where the individual may come in contact with electrical circuitry exceeding 250 volts.

### Specifications - Band

Specifications - Band	Typical Value
Metal	Stainless Steel
Contact	360 degrees around wrist
Color	Black
Plug Size	3.4 mm
Cord Removal Force	< 5 lbs.

### Specifications - Cord

Specifications - Cord	Typical Value
Length	5, 10 or 20 feet
Resistance	1 megohm
Flex life	≥ 16,000 flexes
Color	Gray
Plug Size	3.4 mm

### Part Numbers

2381	3M™ Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1.5 m) cord (Small)
2382	3M™ Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1.5 m) cord (Medium)
2383	3M™ Dual Conductor Metal Wrist Strap . Includes band and 5 ft. (1.5 m) cord (Large)
2384	3M™ Dual Conductor Metal Wrist Strap (Small)
2385	3M™ Dual Conductor Metal Wrist Strap (Medium)
2386	3M™ Dual Conductor Metal Wrist Strap (Large)

### Related Products

3M™ Workstation Monitor Model 724
3M™ Wrist Strap Monitor Model 725
3M™ Wrist Strap and Ground Monitor Model 773
3M™ Iron Man Plus Workstation Monitor CTC331
3M™ Ground Man Plus Ground Monitor CTC334

\*Meets the requirements of ANSI/ESD S20.20-2014, EIA 625



# 3M™ Dual Conductor Metal Wrist Strap for Monitors

3M is a trademark of 3M Company.

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



### Electronics Materials Solutions Division Static Control Products

926 JR Industrial Drive  
Sanford, NC 27332-9733  
Toll-Free: 866-722-3736  
International: 919-718-0000  
Email: [3mstaticinfo@mmm.com](mailto:3mstaticinfo@mmm.com)  
[www.3Mstatic.com](http://www.3Mstatic.com)

Please recycle. Printed in USA.  
© 3M 2014. All rights reserved.  
78-9102-1850-8 JHA

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)