

# DATA SHEET

## **74ALVCH16821**

20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

Product specification

1998 May 29

IC24 Data Handbook

## 20-bit bus-interface D-type flip-flop; positive-edge trigger (3-State)

# 74ALVCH16821

### FEATURES

- Wide supply voltage range of 1.2V to 3.6V
- Complies with JEDEC standard no. 8-1A
- Current drive  $\pm 24$  mA at 3.0 V
- CMOS low power consumption
- Direct interface with TTL levels
- MULTIBYTE™ flow-through standard pin-out architecture
- Low inductance multiple  $V_{CC}$  and ground pins for minimum noise and ground bounce
- All data inputs have bus hold
- Output drive capability 50Ω transmission lines @ 85°C

### DESCRIPTION

The 74ALVCH16821 has two 10-bit, edge triggered registers, with each register coupled to a 3-State output buffer. The two sections of each register are controlled independently by the clock (nCP) and Output Enable (nOE) control gates.

Each register is fully edge triggered. The state of each D input, one set-up time before the Low-to-High clock transition, is transferred to the corresponding flip-flop's Q output.

When  $\overline{nOE}$  is LOW, the data in the register appears at the outputs. When  $\overline{nOE}$  is HIGH, the outputs are in high impedance OFF state. Operation of the  $\overline{nOE}$  input does not affect the state of the flip-flops.

The 74ALVCH16821 has active bus hold circuitry which is provided to hold unused or floating data inputs at a valid logic level. This feature eliminates the need for external pull-up or pull-down resistors.

### QUICK REFERENCE DATA

GND = 0V;  $T_{amb} = 25^{\circ}\text{C}$ ;  $t_r = t_f \leq 2.5\text{ns}$

| SYMBOL            | PARAMETER                                   | CONDITIONS                                                                                   | TYPICAL                                         | UNIT |
|-------------------|---------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------|------|
| $t_{PHL}/t_{PLH}$ | Propagation delay<br>nCP to nQ <sub>n</sub> | $V_{CC} = 2.5\text{V}$ , $C_L = 30\text{pF}$<br>$V_{CC} = 3.3\text{V}$ , $C_L = 50\text{pF}$ | 2.6<br>2.5                                      | ns   |
| $C_I$             | Input capacitance                           |                                                                                              | 5.0                                             | pF   |
| $C_{PD}$          | Power dissipation capacitance per buffer    | $V_I = \text{GND to } V_{CC}^1$                                                              | Outputs enabled<br>33<br>Outputs disabled<br>17 | pF   |
| $F_{max}$         | Maximum clock frequency                     | $V_{CC} = 2.5\text{V}$ , $C_L = 30\text{pF}$<br>$V_{CC} = 3.3\text{V}$ , $C_L = 50\text{pF}$ | 250<br>350                                      | MHz  |

#### NOTE:

- $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ):  
 $P_D = C_{PD} \times V_{CC}^2 \times f_i + \Sigma (C_L \times V_{CC}^2 \times f_o)$  where:  
 $f_i$  = input frequency in MHz;  $C_L$  = output load capacitance in pF;  
 $f_o$  = output frequency in MHz;  $V_{CC}$  = supply voltage in V;  
 $\Sigma (C_L \times V_{CC}^2 \times f_o)$  = sum of outputs.

### ORDERING INFORMATION

| PACKAGES                     | TEMPERATURE RANGE                              | OUTSIDE NORTH AMERICA | NORTH AMERICA | DWG NUMBER |
|------------------------------|------------------------------------------------|-----------------------|---------------|------------|
| 56-Pin Plastic SSOP Type III | $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ | 74ALVCH16821 DL       | ACH16821 DL   | SOT371-1   |
| 56-Pin Plastic TSSOP Type II | $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ | 74ALVCH16821 DGG      | ACH16821 DGG  | SOT364-1   |


20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

74ALVCH16821

PIN DESCRIPTION

| PIN NUMBER                             | SYMBOL          | FUNCTION                                |
|----------------------------------------|-----------------|-----------------------------------------|
| 55, 54, 52, 51, 49, 48, 47, 45, 44, 43 | 1D0 - 1D9       | Data inputs                             |
| 42, 41, 40, 38, 37, 36, 34, 33, 31, 30 | 2D0 - 2D9       |                                         |
| 2, 3, 5, 6, 8, 9, 10, 12, 13, 14       | 1Q0 - 1Q9       | Data outputs                            |
| 15, 16, 17, 19, 20, 21, 23, 24, 26, 27 | 2Q0 - 2Q9       |                                         |
| 1, 28                                  | 1OE, 2OE        | Output enable inputs (active-Low)       |
| 56, 29                                 | 1CP, 2CP        | Clock pulse inputs (active rising edge) |
| 4, 11, 18, 25, 32, 39, 46, 53          | GND             | Ground (0V)                             |
| 7, 22, 35, 50                          | V <sub>CC</sub> | Positive supply voltage                 |

PIN CONFIGURATION




FUNCTION TABLE

| INPUTS |    |    | OUTPUT |
|--------|----|----|--------|
| nOE    | CP | Dx | Q      |
| L      | ↑  | L  | L      |
| L      | ↑  | H  | H      |
| L      | ‡  | X  | Q0     |
| H      | X  | X  | Z      |

H = HIGH voltage level  
L = LOW voltage level  
X = Don't care  
Z = High impedance OFF state  
↑ = LOW to HIGH clock transition  
‡ = Not a LOW-to-HIGH clock transition


LOGIC SYMBOL




20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

74ALVCH16821

LOGIC SYMBOL (IEEE/IEC)



LOGIC DIAGRAM



# 20-bit bus-interface D-type flip-flop; positive-edge trigger (3-State)

74ALVCH16821

## RECOMMENDED OPERATING CONDITIONS

| SYMBOL     | PARAMETER                                                                     | CONDITIONS                                             | LIMITS |          | UNIT |
|------------|-------------------------------------------------------------------------------|--------------------------------------------------------|--------|----------|------|
|            |                                                                               |                                                        | MIN    | MAX      |      |
| $V_{CC}$   | DC supply voltage 2.5V range (for max. speed performance @ 30 pF output load) |                                                        | 2.3    | 2.7      | V    |
|            | DC supply voltage 3.3V range (for max. speed performance @ 50 pF output load) |                                                        | 3.0    | 3.6      |      |
| $V_I$      | DC Input voltage range                                                        |                                                        | 0      | $V_{CC}$ | V    |
| $V_O$      | DC output voltage range                                                       |                                                        | 0      | $V_{CC}$ | V    |
| $T_{amb}$  | Operating free-air temperature range                                          |                                                        | -40    | +85      | °C   |
| $t_r, t_f$ | Input rise and fall times                                                     | $V_{CC} = 2.3$ to $3.0$ V<br>$V_{CC} = 3.0$ to $3.6$ V | 0<br>0 | 20<br>10 | ns/V |

## ABSOLUTE MAXIMUM RATINGS

In accordance with the Absolute Maximum Rating System (IEC 134)

Voltages are referenced to GND (ground = 0V)

| SYMBOL            | PARAMETER                                                                                             | CONDITIONS                                                                                                                     | RATING                 | UNIT |
|-------------------|-------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|------------------------|------|
| $V_{CC}$          | DC supply voltage                                                                                     |                                                                                                                                | -0.5 to +4.6           | V    |
| $I_{IK}$          | DC input diode current                                                                                | $V_I < 0$                                                                                                                      | -50                    | mA   |
| $V_I$             | DC input voltage                                                                                      | For control pins <sup>1</sup>                                                                                                  | -0.5 to +4.6           | V    |
|                   |                                                                                                       | For data inputs <sup>1</sup>                                                                                                   | -0.5 to $V_{CC} + 0.5$ |      |
| $I_{OK}$          | DC output diode current                                                                               | $V_O > V_{CC}$ or $V_O < 0$                                                                                                    | ± 50                   | mA   |
| $V_O$             | DC output voltage                                                                                     | Note 1                                                                                                                         | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_O$             | DC output source or sink current                                                                      | $V_O = 0$ to $V_{CC}$                                                                                                          | ± 50                   | mA   |
| $I_{GND}, I_{CC}$ | DC $V_{CC}$ or GND current                                                                            |                                                                                                                                | ± 100                  | mA   |
| $T_{stg}$         | Storage temperature range                                                                             |                                                                                                                                | -65 to +150            | °C   |
| $P_{TOT}$         | Power dissipation per package<br>-plastic medium-shrink (SSOP)<br>-plastic thin-medium-shrink (TSSOP) | For temperature range: -40 to +125 °C<br>above +55°C derate linearly with 11.3 mW/K<br>above +55°C derate linearly with 8 mW/K | 850<br>600             | mW   |

### NOTE:

1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

# 20-bit bus-interface D-type flip-flop; positive-edge trigger (3-State)

74ALVCH16821

## DC ELECTRICAL CHARACTERISTICS

Over recommended operating conditions. Voltage are referenced to GND (ground = 0 V).

| SYMBOL            | PARAMETER                           | TEST CONDITIONS                                                                                                                 | LIMITS                |                        |      | UNIT |
|-------------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------|------|------|
|                   |                                     |                                                                                                                                 | Temp = -40°C to +85°C |                        |      |      |
|                   |                                     |                                                                                                                                 | MIN                   | TYP <sup>1</sup>       | MAX  |      |
| V <sub>IH</sub>   | HIGH level Input voltage            | V <sub>CC</sub> = 2.3 to 2.7V                                                                                                   | 1.7                   | 1.2                    |      | V    |
|                   |                                     | V <sub>CC</sub> = 2.7 to 3.6V                                                                                                   | 2.0                   | 1.5                    |      |      |
| V <sub>IL</sub>   | LOW level Input voltage             | V <sub>CC</sub> = 2.3 to 2.7V                                                                                                   |                       | 1.2                    | 0.7  | V    |
|                   |                                     | V <sub>CC</sub> = 2.7 to 3.6V                                                                                                   |                       | 1.5                    | 0.8  |      |
| V <sub>OH</sub>   | HIGH level output voltage           | V <sub>CC</sub> = 2.3 to 3.6V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -100μA                    | V <sub>CC</sub> - 0.2 | V <sub>CC</sub>        |      | V    |
|                   |                                     | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -6mA                             | V <sub>CC</sub> - 0.3 | V <sub>CC</sub> - 0.08 |      |      |
|                   |                                     | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -12mA                            | V <sub>CC</sub> - 0.6 | V <sub>CC</sub> - 0.26 |      |      |
|                   |                                     | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -12mA                            | V <sub>CC</sub> - 0.5 | V <sub>CC</sub> - 0.14 |      |      |
|                   |                                     | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -12mA                            | V <sub>CC</sub> - 0.6 | V <sub>CC</sub> - 0.09 |      |      |
|                   |                                     | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -24mA                            | V <sub>CC</sub> - 1.0 | V <sub>CC</sub> - 0.28 |      |      |
| V <sub>OL</sub>   | LOW level output voltage            | V <sub>CC</sub> = 2.3 to 3.6V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100μA                     |                       | GND                    | 0.20 | V    |
|                   |                                     | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 6mA                              |                       | 0.07                   | 0.40 | V    |
|                   |                                     | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 12mA                             |                       | 0.15                   | 0.70 | V    |
|                   |                                     | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 12mA                             |                       | 0.14                   | 0.40 |      |
|                   |                                     | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 24mA                             |                       | 0.27                   | 0.55 |      |
| I <sub>I</sub>    | Input leakage current               | V <sub>CC</sub> = 2.3 to 3.6V;<br>V <sub>I</sub> = V <sub>CC</sub> or GND                                                       |                       | 0.1                    | 5    | μA   |
| I <sub>OZ</sub>   | 3-State output OFF-state current    | V <sub>CC</sub> = 2.7 to 3.6V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ;<br>V <sub>O</sub> = V <sub>CC</sub> or GND |                       | 0.1                    | 10   | μA   |
| I <sub>CC</sub>   | Quiescent supply current            | V <sub>CC</sub> = 2.3 to 3.6V; V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0                                      |                       | 0.2                    | 40   | μA   |
| ΔI <sub>CC</sub>  | Additional quiescent supply current | V <sub>CC</sub> = 2.3V to 3.6V; V <sub>I</sub> = V <sub>CC</sub> - 0.6V; I <sub>O</sub> = 0                                     |                       | 150                    | 750  | μA   |
| I <sub>BHL</sub>  | Bus hold LOW sustaining current     | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = 0.7V <sup>2</sup>                                                                      | 45                    | -                      |      | μA   |
|                   |                                     | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = 0.8V <sup>2</sup>                                                                      | 75                    | 150                    |      |      |
| I <sub>BHH</sub>  | Bus hold HIGH sustaining current    | V <sub>CC</sub> = 2.3V; V <sub>I</sub> = 1.7V <sup>2</sup>                                                                      | -45                   |                        |      | μA   |
|                   |                                     | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = 2.0V <sup>2</sup>                                                                      | -75                   | -175                   |      |      |
| I <sub>BHLO</sub> | Bus hold LOW overdrive current      | V <sub>CC</sub> = 3.6V <sup>2</sup>                                                                                             | 500                   |                        |      | μA   |
| I <sub>BHHO</sub> | Bus hold HIGH overdrive current     | V <sub>CC</sub> = 3.6V <sup>2</sup>                                                                                             | -500                  |                        |      | μA   |

### NOTES:

1. All typical values are at  $T_{amb} = 25^\circ C$ .
2. Valid for data inputs of bus hold parts.

# 20-bit bus-interface D-type flip-flop; positive-edge trigger (3-State)

74ALVCH16821

## AC CHARACTERISTICS FOR $V_{CC} = 2.3V$ TO $2.7V$ RANGE

GND = 0V;  $t_r = t_f \leq 2.0ns$ ;  $C_L = 30pF$ 

| SYMBOL                             | PARAMETER                                                          | WAVEFORM | LIMITS                        |                  |     | UNIT |
|------------------------------------|--------------------------------------------------------------------|----------|-------------------------------|------------------|-----|------|
|                                    |                                                                    |          | V <sub>CC</sub> = 2.5V ± 0.2V |                  |     |      |
|                                    |                                                                    |          | MIN                           | TYP <sup>1</sup> | MAX |      |
| t <sub>PLH</sub> /t <sub>PHL</sub> | Propagation delay<br>nCP to nQ <sub>n</sub>                        | 1, 4     | 1.0                           | 2.6              | 5.8 | ns   |
| t <sub>PZH</sub> /t <sub>PZL</sub> | 3-State output enable time<br>nOE <sub>n</sub> to nQ <sub>n</sub>  | 2, 4     | 1.0                           | 2.8              | 6.6 | ns   |
| t <sub>PHZ</sub> /t <sub>PLZ</sub> | 3-State output disable time<br>nOE <sub>n</sub> to nQ <sub>n</sub> | 2, 4     | 1.0                           | 2.2              | 5.7 | ns   |
| t <sub>W</sub>                     | nCP pulse width HIGH or LOW                                        | 3, 4     | 3.0                           | 1.8              |     | ns   |
| t <sub>SU</sub>                    | Set up time nD <sub>n</sub> to nCP                                 | 3, 4     | 1.4                           | 0.3              |     | ns   |
| t <sub>h</sub>                     | Hold time nD <sub>n</sub> to nCP                                   | 3, 4     | 0.4                           | 0.0              |     | ns   |
| F <sub>max</sub>                   | Maximum clock pulse frequency                                      | 1, 4     | 150                           | 250              |     | MHz  |

### NOTE:

1. All typical values are at  $V_{CC} = 2.5V$  and  $T_{amb} = 25^\circ C$ .

## AC CHARACTERISTICS FOR $V_{CC} = 3.0V$ TO $3.6V$ RANGE AND $V_{CC} = 2.7V$

GND = 0V;  $t_r = t_f \leq 2.5ns$ ;  $C_L = 50pF$ 

| SYMBOL                             | PARAMETER                                                          | WAVEFORM | LIMITS                       |                  |     |                        |                  |     | UNIT |
|------------------------------------|--------------------------------------------------------------------|----------|------------------------------|------------------|-----|------------------------|------------------|-----|------|
|                                    |                                                                    |          | V <sub>CC</sub> = 3.3 ± 0.3V |                  |     | V <sub>CC</sub> = 2.7V |                  |     |      |
|                                    |                                                                    |          | MIN                          | TYP <sup>1</sup> | MAX | MIN                    | TYP <sup>1</sup> | MAX |      |
| t <sub>PHL</sub> /t <sub>PLH</sub> | Propagation delay<br>nCP to nQ <sub>n</sub>                        | 1, 4     | 1.0                          | 2.5              | 4.5 | 1.0                    | 2.8              | 5.3 | ns   |
| t <sub>PZH</sub> /t <sub>PZL</sub> | 3-State output enable time<br>nOE <sub>n</sub> to nQ <sub>n</sub>  | 2, 4     | 1.0                          | 2.3              | 5.1 | 1.0                    | 3.2              | 6.2 | ns   |
| t <sub>PHZ</sub> /t <sub>PLZ</sub> | 3-State output disable time<br>nOE <sub>n</sub> to nQ <sub>n</sub> | 2, 4     | 1.0                          | 2.8              | 4.6 | 1.0                    | 3.1              | 5.0 | ns   |
| t <sub>W</sub>                     | nCP pulse width HIGH or<br>LOW                                     | 3, 4     | 3.3                          | 0.2              |     | 3.3                    | 1.7              |     | ns   |
| t <sub>SU</sub>                    | Set up time nD <sub>n</sub> to nCP                                 | 3, 4     | 1.0                          | 0.2              |     | 1.2                    | 0.3              |     | ns   |
| t <sub>h</sub>                     | Hold time nD <sub>n</sub> to nCP                                   | 3, 4     | 0.8                          | 0.4              |     | 0.6                    | −0.3             |     | ns   |
| F <sub>max</sub>                   | Maximum clock pulse<br>frequency                                   | 1, 4     | 150                          | 350              |     | 150                    | 300              |     | MHz  |

### NOTES:

1. All typical values are at  $T_{amb} = 25^\circ C$ .

20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

74ALVCH16821


AC WAVEFORMS

V<sub>CC</sub> = 2.3 TO 2.7 V RANGE


- 1. V<sub>M</sub> = 0.5 V
- 2. V<sub>X</sub> = V<sub>OL</sub> + 0.15V
- 3. V<sub>Y</sub> = V<sub>OH</sub> - 0.15V
- 4. V<sub>I</sub> = V<sub>CC</sub>
- 5. V<sub>OL</sub> and V<sub>OH</sub> are the typical output voltage drop that occur with the output load.

V<sub>CC</sub> = 3.0 TO 3.6 V RANGE AND V<sub>CC</sub> = 2.7 V


- 1. V<sub>M</sub> = 1.5 V
- 2. V<sub>X</sub> = V<sub>OL</sub> + 0.3V
- 3. V<sub>Y</sub> = V<sub>OH</sub> - 0.3V
- 4. V<sub>I</sub> = 2.7 V
- 5. V<sub>OL</sub> and V<sub>OH</sub> are the typical output voltage drop that occur with the output load.



Waveform 1. The input (nCP) to output propagation delays.




Waveform 2. The 3-State enable and disable times.



Waveform 3. Set up and hold times.

TEST CIRCUIT



Waveform 4. Load circuitry for switching times




20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

74ALVCH16821

SSOP56: plastic shrink small outline package; 56 leads; body width 7.5 mm

SOT371-1




20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

74ALVCH16821

TSSOP56: plastic thin shrink small outline package; 56 leads; body width 6.1mm

SOT364-1



---

20-bit bus-interface D-type flip-flop;  
positive-edge trigger (3-State)

---

74ALVCH16821

---

## NOTES

# 20-bit bus-interface D-type flip-flop; positive-edge trigger (3-State)

74ALVCH16821

## Data sheet status

| Data sheet status         | Product status | Definition [1]                                                                                                                                                                                                                                             |
|---------------------------|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Objective specification   | Development    | This data sheet contains the design target or goal specifications for product development. Specification may change in any manner without notice.                                                                                                          |
| Preliminary specification | Qualification  | This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. |
| Product specification     | Production     | This data sheet contains final specifications. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.                                                       |

[1] Please consult the most recently issued datasheet before initiating or completing a design.

## Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors  
811 East Arques Avenue  
P.O. Box 3409  
Sunnyvale, California 94088-3409  
Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1998  
All rights reserved. Printed in U.S.A.

print code

Date of release: 05-96

Document order number:

9397-750-04553

*Let's make things better.*

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email        amall@ameya360.com  
  
QQ            800077892  
  
Skype        ameyasales1 ameyasales2

➤ Customer Service :

Email        service@ameya360.com

➤ Partnership :

Tel            +86 (21) 64016692-8333  
  
Email        mkt@ameya360.com