

**HEYCO**




- Same design as Heyco Snap Bushings but **designed for metric sized mounting holes**.
- Convert raw-edged holes to smooth, neat insulated holes.
- Locking fingers snap into holes with fingertip pressure.
- Withstand a push back force of 35 pounds.
- Lock firmly into panel up to 2,5 mm (.098") thick.
- Multiple sizes for use in 16,0 mm (.630") to 32,0 mm (1.260") diameter holes. For other metric sizes, consult Heyco.
- For our complete range of Snap Bushings, see pages 5-1 thru 5-6.

## Heyco® Metric Snap Bushings




Multiple Locking Steps for Panel Thickness up to 2,5 mm (.098")  
Mounting Hole Diameter Range: 16,0 mm (.630") to 32,0 mm (1.260")

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
mm.	in.			A Inside Diameter		B Head Diameter		C Overall Height	
16,0	.630	<b>2142</b>	MSB 16-12	12,0	.472	18,5	.728	10,3	.406
20,0	.787	<b>2144</b>	MSB 20-16	16,0	.630	22,6	.890		
25,0	.984	<b>2146</b>	MSB 25-19	19,0	.748	27,8	1.094	11,5	.453
32,0	1.260	<b>2148</b>	MSB 32-26	26,0	1.023	34,9	1.375		

Standard color black. Consult Heyco for white and other colors.



Metric Snap Bushing



Rubber Grommets

## Heyco® UL Listed Thermoplastic Rubber Grommets

For Panel Thickness from .03" (0,8 mm) to .08" (2,0 mm)  
Mounting Hole Diameter Range: .500" (12,7 mm) to 1.250" (31,8 mm)

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
in.	mm.			A Inside Diameter		B Head Diameter		C Overall Height	
.500	12,7	<b>G1505</b>	TG 500	.41	10,4	.81	20,6	.28	7,1
.625	15,9	<b>G1506</b>	TG 625	.52	13,2	.93	23,6	.31	7,9
.750	19,1	<b>G1507</b>	TG 750	.65	16,5	1.06	26,9		
.875	22,2	<b>G1508</b>	TG 875	.77	19,6	1.19	30,2		
1.000	25,4	<b>G1509</b>	TG 1000	.89	22,6	1.32	33,5	.35	8,9
1.250	31,8	<b>G1510</b>	TG 1250	1.12	28,4	1.60	40,6		

Molded from Thermoplastic Rubber.

- **Convert raw-edged holes to smooth, neat, insulated holes.**
- Retaining bead snaps securely into place.
- Insulate and mechanically protect cable, tubing, hose, rope, rods, and shafts.
- UL approved for applications up to 122° F (50°C).
- Six diameters fit panel thickness from .03" (0,8 mm) to .08" (2,0 mm).

*Quick Specs*

<b>Material</b>	MSB	Nylon 6/6	<b>Material</b>	TG	Flex Temp (Thermoplastic Rubber)
<b>Certifications</b>		Recognized under the Component Program of Underwriters' Laboratories File E15331	<b>Certifications</b>		Listed under Underwriters' Laboratories File E15331
		Certified by the Canadian Standards Association File 8919			
<b>Flammability Rating</b>		94V-2	<b>Maximum Temperature Rating</b>		122°F (50°C)
<b>Material Temperature Index</b>	MSB	257°F (125°C)—Maximum temperature on part not to exceed 221°F (105°C)			

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
  
Email     amall@ameya360.com  
  
QQ        800077892  
  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
  
Email     mkt@ameya360.com