

# MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)

## High Voltage Power Transistors

### DPAK for Surface Mount Applications

Designed for line operated audio output amplifier, switchmode power supply drivers and other switching applications.

#### Features

- Lead Formed for Surface Mount Applications in Plastic Sleeves (No Suffix)
- Electrically Similar to Popular MJE340 and MJE350
- Epoxy Meets UL 94 V-0 @ 0.125 in
- NJV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

#### MAXIMUM RATINGS

| Rating  | Symbol         | Max           | Unit                     |
|---|----------------|---------------|--------------------------|
| Collector-Emitter Voltage   | $V_{CEO}$      | 300           | Vdc                      |
| Collector-Base Voltage  | $V_{CB}$       | 300           | Vdc                      |
| Emitter-Base Voltage  | $V_{EB}$       | 3             | Vdc                      |
| Collector Current – Continuous  | $I_C$          | 0.5           | Adc                      |
| Collector Current – Peak  | $I_{CM}$       | 0.75          | Adc                      |
| Total Power Dissipation<br>@ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$          | $P_D$          | 15<br>0.12    | W<br>W/ $^\circ\text{C}$ |
| Total Power Dissipation (Note 1)<br>@ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.56<br>0.012 | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range   | $T_J, T_{stg}$ | -65 to +150   | $^\circ\text{C}$         |
| ESD – Human Body Model  | HBM            | 3B            | V                        |
| ESD – Machine Model   | MM             | C             | V                        |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.



1. These ratings are applicable when surface mounted on the minimum pad sizes recommended.



ON Semiconductor®


<http://onsemi.com>

### SILICON POWER TRANSISTORS 0.5 AMPERE 300 VOLTS, 15 WATTS



**DPAK  
CASE 369C  
STYLE 1**

#### MARKING DIAGRAM



A = Assembly Location  
Y = Year  
WW = Work Week  
J3x0 = Device Code  
x = 4 or 5  
G = Pb-Free Package

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

# MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)

## THERMAL CHARACTERISTICS

| Characteristic                                   | Symbol          | Max  | Unit |
|--|-----------------|------|------|
| Thermal Resistance, Junction-to-Case             | $R_{\theta JC}$ | 8.33 | °C/W |
| Thermal Resistance, Junction-to-Ambient (Note 2) | $R_{\theta JA}$ | 80   | °C/W |
| Leading Temperature for Soldering Purpose        | $T_L$           | 260  | °C   |

2. These ratings are applicable when surface mounted on the minimum pad sizes recommended.

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

### OFF CHARACTERISTICS

|  |                |     |     |    |
|--|----------------|-----|-----|----|
| Collector-Emitter Sustaining Voltage (Note 3)<br>( $I_C = 1\text{ mA}$ , $I_B = 0$ ) | $V_{CEO(sus)}$ | 300 | –   | V  |
| Collector Cutoff Current<br>( $V_{CB} = 300\text{ V}$ , $I_E = 0$ )                  | $I_{CEO}$      | –   | 0.1 | mA |
| Emitter Cutoff Current<br>( $V_{BE} = 3\text{ V}$ , $I_C = 0$ )                      | $I_{EBO}$      | –   | 0.1 | mA |

### ON CHARACTERISTICS (Note 3)

|  |               |    |     |   |
|--|---------------|----|-----|---|
| DC Current Gain<br>( $I_C = 50\text{ mA}$ , $V_{CE} = 10\text{ V}$ )                     | $h_{FE}$      | 30 | 240 | – |
| Collector-Emitter Saturation Voltage<br>( $I_C = 100\text{ mA}$ , $I_B = 10\text{ mA}$ ) | $V_{CE(sat)}$ | –  | 1   | V |
| Base-Emitter On Voltage<br>( $I_C = 1\text{ A}$ , $V_{CE} = 10\text{ V}$ )               | $V_{BE(on)}$  | –  | 1.5 | V |

### DYNAMIC CHARACTERISTICS

|   |       |    |   |     |
|---|-------|----|---|-----|
| Current Gain – Bandwidth Product<br>( $I_C = 50\text{ mA}$ , $V_{CE} = 10\text{ V}$ , $f = 10\text{ MHz}$ ) | $f_T$ | 10 | – | MHz |
|---|-------|----|---|-----|

3. Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

# MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)

## TYPICAL CHARACTERISTICS

### MJD340




Figure 1. DC Current Gain

### MJD340




Figure 2. "On" Voltages

### MJD350




Figure 3. DC Current Gain

### MJD350




Figure 4. "On" Voltages

# MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)




Figure 5. Thermal Response




Figure 6. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 6 is based on  $T_{J(pk)} = 150^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided  $T_{J(pk)} \leq 150^\circ\text{C}$ .  $T_{J(pk)}$  may be calculated from the data in Figure 5. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 7. Power Derating

## MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)

### ORDERING INFORMATION


| Device       | Package           | Shipping†           |
|--------------|-------------------|---------------------|
| MJD340G      | DPAK<br>(Pb-Free) | 75 Units / Rail     |
| MJD340RLG    | DPAK<br>(Pb-Free) | 1,800 / Tape & Reel |
| MJD340T4G    | DPAK<br>(Pb-Free) | 2,500 / Tape & Reel |
| NJVMJD340T4G | DPAK<br>(Pb-Free) | 2,500 / Tape & Reel |
| MJD350G      | DPAK<br>(Pb-Free) | 75 Units / Rail     |
| MJD350T4G    | DPAK<br>(Pb-Free) | 2,500 / Tape & Reel |
| NJVMJD350T4G | DPAK<br>(Pb-Free) | 2,500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MJD340, NJVMJD340T4G (NPN), MJD350, NJVMJD350T4G (PNP)

## PACKAGE DIMENSIONS

### DPAK (SINGLE GAUGE) CASE 369C ISSUE D



#### NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.086     | 0.094 | 2.18        | 2.38  |
| A1  | 0.000     | 0.005 | 0.00        | 0.13  |
| b   | 0.025     | 0.035 | 0.63        | 0.89  |
| b2  | 0.030     | 0.045 | 0.76        | 1.14  |
| b3  | 0.180     | 0.215 | 4.57        | 5.46  |
| c   | 0.018     | 0.024 | 0.46        | 0.61  |
| c2  | 0.018     | 0.024 | 0.46        | 0.61  |
| D   | 0.235     | 0.245 | 5.97        | 6.22  |
| E   | 0.250     | 0.265 | 6.35        | 6.73  |
| e   | 0.090 BSC |       | 2.29 BSC    |       |
| H   | 0.370     | 0.410 | 9.40        | 10.41 |
| L   | 0.055     | 0.070 | 1.40        | 1.78  |
| L1  | 0.108 REF |       | 2.74 REF    |       |
| L2  | 0.020 BSC |       | 0.51 BSC    |       |
| L3  | 0.035     | 0.050 | 0.89        | 1.27  |
| L4  | ---       | 0.040 | ---         | 1.01  |
| Z   | 0.155     | ---   | 3.93        | ---   |


#### STYLE 1:

1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com