




OPERATING CHARACTERISTICS AT 25 °C AMBIENT																			
DIALIGHT P/N	LED COLOR	LED CHIP MATERIAL	EPOXY COLOR	I _F (mA)	FORWARD VOLTAGE (V)		LUMINOUS INTENSITY (mcd)			REVERSE CURRENT (μA) (@ V _R = 5 V)	PEAK WAVELENGTH (nm)	DOMINANT WAVELENGTH (nm)			VIEWING ANGLE (2 θ 1/2) (DEGREES)	REVISIONS			
					TYP.	MAX.	MIN.	TYP.	MAX.	MAX.		MIN.	TYP.	MAX.		REV.	ECN.	DRN.	DATE
597-3003-407	RED	AlInGaP	WHITE DIFFUSED	20	1.9	2.4	25.0	50.0	75.0	100	635	620	626	635	150	D	——	YIS	2-19-03
597-3212-407	ORANGE			20	1.9	2.4	25.0	65.0	105.0	100	609	600	605	612	150	D	——	YIS	2-19-03
597-3222-407	AMBER			20	1.9	2.4	25.0	65.0	105.0	100	592	583	590	597	150	D	——	YIS	2-19-03



SOLDER PAD LAYOUT



TAPE & REEL SPECIFICATION
NO SCALE

NOTES:

- PARTS PACKAGED ON 180 mm DIA. REEL, 8 mm TAPE, 4000/REEL (SEE SKETCH).
- TAPE AND REEL LEDS MAY REQUIRE RE-TAPING AFTER TWELVE MONTHS.
- DIALIGHT PART NUMBER: 597-3003-407, 597-3212-407, 597-3222-407.

ABSOLUTE MAXIMUM RATING AT 25°C AMBIENT	597-XXXX-407			UNITS
	3001 RED	3212 ORANGE	3222 AMBER	
POWER DISSIPATION	81			mW
CONTINUOUS FORWARD CURRENT	30			mA
PEAK FORWARD CURRENT (< 1/20 DUTY CYCLE T _w < 1 msec)	100			mA
DERATE LINEAR FROM 25 °C	.43			mA/°C
REVERSE VOLTAGE	5			V
OPERATING TEMPERATURE	-40 TO +85			°C
STORAGE TEMPERATURE	-40 TO +100			°C

REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
A	—	NEW RELEASE	MC		N.O.	7-14-97
B	—	ADDED P/N: 597-3222-407 AND WHITE DIFF. WAS CLEAR DIFF.	MC		D.C.	8-15-97
C	—	ADDED NOTES 2 AND 3.	TC	D.C.	N.O.	6-9-99
D	—	UPDATED LED SPEC.	YIS			

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.

SCALE 12:1 ALL DIM'S IN: INCHES (MM)		DRAWING NUMBER	REV
TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: ±1/64 DECIMALS (.XX): ±.02 DECIMALS (.XXX): ±.015 ANGLES: ±3° FINISH:		C-16248	D
FSCM 83330		TITLE SMT LED	MATERIAL
		Dialight	1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727
		SHEET OF	FAMILY TABLE:

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com