

Power Transistor (160V , 1.5A)

2SD2211 / 2SD1918 / 2SD1857A

●Features

- 1) High breakdown voltage.($V_{CE0} = 160V$)
- 2) Low collector output capacitance.
(Typ. 20pF at $V_{CB} = 10V$)
- 3) High transition frequency.($f_r = 80MHz$)
- 4) Complements the 2SB1275 / 2SB1236A.

●Absolute maximum ratings (Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CBO}	160	V
Collector-emitter voltage	V_{CEO}	160	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_c	1.5	A(DC)
		3	A(Pulse) *1
Collector power dissipation	P_c	1	W *2
		2	W
		10	W($T_c = 25^\circ C$)
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55 ~ +150	°C

- *1 Single pulse $P_w = 100ms$
- *2 Printed circuit board 1.7mm thick, collector plating 1cm² or larger.
- *3 When mounted on a 40 x 40 x 0.7mm ceramic board.

●Packaging specifications and hFE

Type	2SD2211	2SD1918	2SD1857A
Package	MPT3	CPT3	ATV
hFE	QR	Q	PQ
Marking	DQ*	-	-
Code	T100	TL	TV2
Basic ordering unit (pieces)	1000	2500	2500

* Denotes hFE

●External dimensions (Units : mm)

2SD2211

ROHM : MPT3
EIAJ : SC-62

(1) Base(Gate)
(2) Collector(Drain)
(3) Emitter(Source)

2SD1918

ROHM : CPT3
EIAJ : SC-63

(1) Base(Gate)
(2) Collector(Drain)
(3) Emitter(Source)

2SD1857A

ROHM : ATV

Taping specifications
(1) Emitter
(2) Collector
(3) Base

●Electrical characteristics (Ta = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	V_{CBO}	160	-	-	V	$I_c = 50\mu A$
Collector-emitter breakdown voltage	V_{CEO}	160	-	-	V	$I_c = 1mA$
Emitter-base breakdown voltage	V_{EBO}	5	-	-	V	$I_E = 50\mu A$
Collector cutoff current	I_{CBO}	-	-	1	μA	$V_{CB} = 120V$
Emitter cutoff current	I_{EBO}	-	-	1	μA	$V_{EB} = 4V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	-	-	2	V	$I_c/I_b = 1A/0.1A$ *
Base-emitter saturation voltage	$V_{BE(sat)}$	-	-	1.5	V	$I_c/I_b = 1A/0.1A$ *
DC current transfer ratio	hFE	120	-	390	-	$V_{CE}/I_c = 5V/0.1A$
		82	-	270	-	
Transition frequency	f_r	-	80	-	MHz	$V_{CE} = 5V, I_E = -0.1A, f = 30MHz$
Output capacitance	C_{ob}	-	20	-	pF	$V_{CB} = 10V, I_E = 0A, f = 1MHz$

* Measured using pulse current.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com