

Single-Phase Auto Transfer Switch / Switched PDU, 1.4kW 15A 120V, 1U Horizontal Rackmount, 8 NEMA 5-15R outlets, 2 NEMA 5-15P inputs

MODEL NUMBER: PDUMH15ATNET



Specifications

| OVERVIEW | |
|--|---|
| Style | Rackmount |
| PDU Type | Auto-Transfer Switch; Switched |
| OUTPUT | |
| Output Capacity Details | 1.4kW (120V input), 1.5kW (127V input), 1.2kW (100V input); 15A maximum (Agency de-rated to 12A continuous) |
| Frequency Compatibility | 60 Hz |
| Output Nominal Voltage | 100-127V nominal, single phase |
| Outlet Quantity / Type | 8 NEMA 5-15R |
| Number of Outlets | 8 |
| Outlet Type | NEMA 5-15R |
| Customized Load Management Receptacles | 8 individually controlled outlets |
| INPUT | |
| PDU Input Voltage | 100; 120; 127 |
| Maximum Input Amps | 15 |
| Maximum Input Amps Details | Agency de-rated to 12A continuous |
| PDU Plug Type | NEMA 5-15P |



| | |
|-------------------------------------|---|
| Input Cord Length (ft.) | 12 |
| Input Cord Length (m) | 3.66 |
| Input Phase | Single-Phase |
| LEDS ALARMS & SWITCHES | |
| Front Panel LEDs | 10 front panel LEDs display power on - off status for each outlet, plus 2 LEDs for power status on each input line cord. Digital Current Meter display shows total output power consumption in amps. |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 6.25 x 22.5 x 23.5 |
| Shipping Dimensions (hwd / cm) | 15.9 x 57.2 x 59.7 |
| Shipping Weight (lbs.) | 15.2 |
| Shipping Weight (kg) | 6.9 |
| Unit Dimensions (hwd / in.) | 1.75 x 17.5 x 14.5 |
| Unit Dimensions (hwd / cm) | 4.44 x 44.4 x 36.8 |
| Unit Weight (lbs.) | 11 |
| Unit Weight (kg) | 5 |
| Material of Construction | Steel |
| Form Factors Supported | 1U rackmount |
| PDU Form Factor | Horizontal (1U, 2U, etc) |
| ENVIRONMENTAL | |
| Relative Humidity | Up to 95% (non-condensing) |
| COMMUNICATIONS | |
| SNMP Compatibility | Yes, pre-installed SNMPWEBCARD provides remote monitoring via web, telnet, and SNMP management systems. Remote management gives user ability to turn connected loads on or off individually |
| CERTIFICATIONS | |
| TAA Compliant Option | TAA Compliant Version Available - Order Tripp Lite PDUMH15ATNETAA |
| Certifications | Tested to UL 60950-1 (USA, Canada), Class A (Emissions), NOM (Mexico), RoHS compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com