


Surface Mount 1900.00MHz SAW Filter

AFS14A40-1900.00-T3

Moisture Sensitivity Level (MSL) – This product is Hermetically Sealed and not Moisture Sensitive - MSL = N/A: Not Applicable



RoHS
Compliant



1.4 x 1.1 x 0.7 mm

FEATURES:

- 1.4 x 1.1 x 0.7 mm low profile SMT package
- Low Insertion loss
- Excellent selectivity with high out-of-band rejection

APPLICATIONS:

- Wireless Communication
- Remote Control
- Cellular Phones

ELECTRICAL SPECIFICATIONS:


Maximum Ratings

Item	Value
Input Power Level	+13 dBm max.
DC Permissive Voltage	3.0V DC max.
Operating Temperature Range	-30°C to + 85°C
Storage Temperature Range	-40°C to + 85°C

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency (f_c)		1900.00		MHz	
Insertion Loss (IL)		2.0	2.7	dB	1880 ~ 1920MHz
Effective Bandwidth		40		MHz	
Amplitude Ripple		0.5	1.2	dB	1880 ~ 1920MHz
Worst-Case Input / Output Return Loss	9.5	11.7		dB	
Stop-band Attenuation (Referenced to 0.0 dB)	40	45		dB	D.C~1395 MHz
	40	48			1395~1435 MHz
	33	36			1435~1805 MHz
	25	33			1805~1840 MHz
	25	27			2000~2135 MHz
	31	34			2135~2175 MHz
	30	36			2175~3500 MHz
	22	29			3500~6000 MHz
Source Impedance (Z_s)		50		Ω	See note # 1
Load Impedance (Z_L)		50		Ω	See note # 1

Note #1: No matching network required for operation into 50 Ω 's

TEST CIRCUIT:



Bottom View




Surface Mount 1900.00MHz SAW Filter

AFS14A40-1900.00-T3




RoHS
Compliant




1.4 x 1.1 x 0.7 mm

OUTLINE DIMENSIONS:



C:	Input
A:	Output
B, D, E:	Ground

Recommended Land Pattern:



■ : Land Pattern
Unit : mm


*All Dimensions are in mm

Surface Mount 1900.00MHz SAW Filter

AFS14A40-1900.00-T3




RoHS
Compliant





1.4 x 1.1 x 0.7 mm

FREQUENCY CHARACTERISTICS:

Filter Frequency Response (Narrowband)




Filter Frequency Response (Wideband)




REFLECTION FUNCTIONS:


S11



S22



AFS14A40-1900.00-T3



RoHS
Compliant

Time (Sec)	Temp (°C)
0	20
20	20
40	145
60	145
80	155
100	155
120	165
140	175
160	190
180	215
200	250
220	260
240	250
260	170
280	145
300	145
320	135
340	115
360	105

Technical drawing of a wheel with the following dimensions and details:

- Main View (Top):**
 - Overall diameter: $\phi 100 \pm 0.3$
 - Inner diameter: $\phi 25.3$
 - Hub diameter: $\phi 17.0 \pm 0.13$
 - Hub thickness: 2.6 ± 0.13
 - Spoke diameter: $\phi 10.0 \pm 0.13$
 - Spoke thickness: 1.5 ± 0.2
 - Spoke width: 17.0 ± 0.13
 - Spoke angle: 120°
 - Spoke fillet: $R3.0$
 - Spoke fillet radius: 2.0
 - Spoke fillet angle: 60°
- Detail A:**
 - Top view of the hub with dimensions: 2.6 , 1.5 , and 120° .
- Detail B:**
 - Side view of the hub with dimensions: 2.6 ± 0.13 , 1.5 ± 0.2 , and 17.0 ± 0.13 .
- Other Dimensions:**
 - Overall width: 2.0
 - Hub width: 8.4 ± 0.3
 - Spoke width: 8.4 ± 0.3
 - Spoke angle: 60°
 - Spoke fillet radius: $R3.0$
 - Spoke fillet angle: 60°

Revised: 04.16.13

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com