




ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	23.0	± max
T:	9.5	± max
Lead Diameter	1.0	± nom
S:	7.8	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)	5.0	± max
B:	9.22	± nom
C:	3.82	± nom



Electrical Specifications

Resistance:	10.0 Ω	± 25 %
Max Steady State Current upto 65°C:	8.00	A
Max Rec. Energy Rating:	200	J
Actual Failure Instantaneous Energy:	450	J
Maximum Capacitance @ 120 VAC:	13,850	μ f
Maximum Capacitance @ 240 VAC:	3,473	μ f
Maximum Capacitance @ 440 VAC:	802	μ f
Maximum Capacitance @ 680 VAC:	400	μ f
Resistance @ 100% Max Current:	0.09	Ω
Resistance @ 50% Max Current:	0.18	Ω
Body Temperature at 100% Max Current:	194.00	°c
Dissipation Constant:	55.0	mw/°c
Thermal Time Constant:	112	Sec.
Material Type (for Beta and Curve):	G	

MS22 10008

Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com