




- One-piece solution with smooth internal surfaces provides for easier wire routing, protection, and installation around corner angles.
- Easy, permanent assembly: the installer twists the tubing over the connector ferrule.
- Snap-in Fittings are UL recognized for use with Heyco-Flex II tubing.
 See page 2-2.
- Unique locking fingers accommodate various panel thicknesses.
- All nylon construction is resistant to salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL certification and testing.)
- Suitable for a wide array of electrical applications:
 - Commercial and Industrial HVAC Systems
 - Motorized Equipment
 - Enclosed Power Sources
 - Garage Door Openers
 - Major Appliances
- Dry location only.
- Finishing collars available to neaten rough cut tubing ends. See page 2-7.
- Assembly Tool available for assembling Quick Twist Fittings into HF1 and HF2 Conduit and Tubing. See page 2-8.


Heyco-Flex™ Quick Twist Conduit Fittings

For use with Heyco-Flex™ II Tubing **90° Sweep. Snap-In Hubs**

	FITS TUBING TRADE SIZE	PART NO.		DESCRIPTION	PART DIMENSIONS A B C D E									
		Black	Gray		Mounting Hole Dia.		Max O.A. Height		Max O.A. Length		Hub Length		Flange Dia.	
					in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
	3/8	8500		HFC 3/8-S-90-Twist	.875	22.2	1.754	44.6	2.749	69.8	.39	9.9	1.23	31.2
	1/2	8505	8506	HFC 1/2-S-90-Twist	.0.0			,0		00,0		0,0	0	0.,2
	3/4	8510	8511	HFC 3/4-S-90-Twist	1.093	27,8	1.965	50,0	3.081	78,3	.39	9,9	1.50	38,1

Standard colors black and gray. Consult Heyco for other colors.







Quick Specs

Material Certifications

Flammability Rating Temperature Range Nylon 6/6

Recognized under the Component Program of Underwriters' Laboratories File E121095

94V-2

-22°F (-30°C) to 221°F (105°C)

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

> Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com