FAIRCHILD SEMICONDUCTOR™

October 2001
Revised March 2004

NC7SV125
TinyLogic® ULP-A Buffer with 3-STATE Output

General Description

The NC7SV125 is a single buffer with 3-STATE output from Fairchild's Ultra Low Power-A (ULP-A) Series of TinyLogic®. ULP-A is ideal for applications that require extreme high speed, high drive and low power. This product is designed for wide low voltage operating range (0.9V to 3.6V V_{CC}) and applications that require more drive and speed than the TinyLogic ULP series, but still offer best in class low power operation.

The NC7SV125 is uniquely designed for optimized power and speed, and is fabricated with an advanced CMOS technology to achieve high-speed operation while maintaining low CMOS power dissipation.

Features

- 0.9V to 3.6V V_{CC} supply operation
- 3.6V overvoltage tolerant I/O's at V_{CC} from 0.9V to 3.6V
- Extremely High Speed t_{PD}
  - 1.0 ns typ for 2.7V to 3.6V V_{CC}
  - 2.0 ns typ for 2.3V to 2.7V V_{CC}
  - 3.0 ns typ for 1.65V to 1.95V V_{CC}
  - 3.5 ns typ for 1.4V to 1.6V V_{CC}
  - 6.0 ns typ for 1.1V to 1.3V V_{CC}
  - 13 ns typ for 0.9V V_{CC}
- Power-Off high impedance inputs and outputs
- High Static Drive (I_{OH}/I_{OL})
  - ±24 mA @ 3.00V V_{CC}
  - ±18 mA @ 2.30V V_{CC}
  - ±6 mA @ 1.65V V_{CC}
  - ±4 mA @ 1.4V V_{CC}
  - ±2 mA @ 1.1V V_{CC}
  - ±0.1 mA @ 0.9V V_{CC}
- Uses patented Quiet Series™ noise/EMI reduction circuitry
- Ultra small MicroPak™ leadfree package
- Ultra low dynamic power

Ordering Code:

Order Number	Package Number	Product Code Top Mark	Package Description	Supplied As
NC7SV125P5X	MAA05A	V25	5-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3k Units on Tape and Reel
NC7SV125L6X	MAC06A	H6	6-Lead MicroPak, 1.0mm Wide	5k Units on Tape and Reel

Battery Life vs. V_{CC} Supply Voltage



TinyLogic ULP and ULP-A with up to 50% less power consumption can extend your battery life significantly.

Battery Life = $(V_{battery} * I_{battery} * .9)/(P_{device})/24$hrs/day

Where, $P_{device} = (I_{CC} * V_{CC}) + (C_{PD} + C_L) * V_{CC}^2 * f$

Assumes ideal 3.6V Lithium Ion battery with current rating of 900mAH and derated 90% and device frequency at 10MHz, with C_L = 15 pF load

TinyLogic® is a registered trademark of Fairchild Semiconductor Corporation.
MicroPak™, and Quiet Series™ are trademarks of Fairchild Semiconductor Corporation.

Logic Symbol

IEEE/IEC



Pin Descriptions

Pin Names	Description
A, $\overline{OE}$	Input
Y	Output
NC	No Connect

Function Table

Input		Output
$\overline{OE}$	In A	Out Y
L	L	L
L	H	H
H	X	Z

H = HIGH Logic Level
L = LOW Logic Level
X = HIGH or LOW Logic Level
Z = HIGH Impedance State

Connection Diagrams

Pin Assignments for SC70



(Top View)

Pad Assignments for MicroPak



(Top Thru View)

Absolute Maximum Ratings (Note 1)

Supply Voltage (V_{CC})	−0.5V to +4.6V
DC Input Voltage (V_{IN})	−0.5V to +4.6V
DC Output Voltage (V_{OUT})	
HIGH or LOW State (Note 2)	−0.5V to V_{CC} +0.5V
V_{CC} = 0V	−0.5V to +4.6V
DC Input Diode Current (I_{IK}) V_{IN} < 0V	±50 mA
DC Output Diode Current (I_{OK})	
V_{OUT} < 0V	−50 mA
V_{OUT} > V_{CC}	+50 mA
DC Output Source/Sink Current (I_{OH}/I_{OL})	± 50 mA
DC V_{CC} or Ground Current per	
Supply Pin (I_{CC} or Ground)	± 50 mA
Storage Temperature Range (T_{STG})	−65°C to +150°C

Recommended Operating Conditions (Note 3)

Supply Voltage	0.9V to 3.6V
Input Voltage (V_{IN})	0V to 3.6V
Output Voltage (V_{OUT})	
V_{CC} = 0.0V	0V to 3.6V
HIGH or LOW State	0V to V_{CC}
Output Current in I_{OH}/I_{OL}	
V_{CC} = 3.0V to 3.6V	±24 mA
V_{CC} = 2.3V to 2.7V	±18 mA
V_{CC} = 1.65V to 1.95V	±6 mA
V_{CC} = 1.4V to 1.6V	±4 mA
V_{CC} = 1.1V to 1.3V	±2 mA
V_{CC} = 0.9V	±0.1 mA
Free Air Operating Temperature (T_A)	−40°C to +85°C
Minimum Input Edge Rate ($\Delta t/\Delta V$)	
V_{IN} = 0.8V to 2.0V, V_{CC} = 3.0V	10 ns/V

Note 1: Absolute Maximum Ratings: are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: I_O Absolute Maximum Rating must be observed.

Note 3: Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	T_A = +25°C		T_A = −40°C to +85°C		Units	Conditions
			Min	Max	Min	Max		
V_{IH}	HIGH Level Input Voltage	0.90	0.65 x V_{CC}		0.65 x V_{CC}		V	
		1.10 ≤ V_{CC} ≤ 1.30	0.65 x V_{CC}		0.65 x V_{CC}			
		1.40 ≤ V_{CC} ≤ 1.60	0.65 x V_{CC}		0.65 x V_{CC}			
		1.65 ≤ V_{CC} ≤ 1.95	0.65 x V_{CC}		0.65 x V_{CC}			
		2.30 ≤ V_{CC} < 2.70	1.6		1.6			
		2.70 ≤ V_{CC} ≤ 3.60	2.0		2.0			
V_{IL}	LOW Level Input Voltage	0.90		0.35 x V_{CC}		0.35 x V_{CC}	V	
		1.10 ≤ V_{CC} ≤ 1.30		0.35 x V_{CC}		0.35 x V_{CC}		
		1.40 ≤ V_{CC} ≤ 1.60		0.35 x V_{CC}		0.35 x V_{CC}		
		1.65 ≤ V_{CC} ≤ 1.95		0.35 x V_{CC}		0.35 x V_{CC}		
		2.30 ≤ V_{CC} < 2.70		0.7		0.7		
		2.70 ≤ V_{CC} ≤ 3.60		0.8		0.8		
V_{OH}	HIGH Level Output Voltage	0.90	V_{CC} − 0.1		V_{CC} − 0.1		V	I_{OH} = −100 µA
		1.10 ≤ V_{CC} ≤ 1.30	V_{CC} − 0.1		V_{CC} − 0.1			
		1.40 ≤ V_{CC} ≤ 1.60	V_{CC} − 0.2		V_{CC} − 0.2			
		1.65 ≤ V_{CC} ≤ 1.95	V_{CC} − 0.2		V_{CC} − 0.2			
		2.30 ≤ V_{CC} < 2.70	V_{CC} − 0.2		V_{CC} − 0.2			
		2.70 ≤ V_{CC} ≤ 3.60	V_{CC} − 0.2		V_{CC} − 0.2			
		1.10 ≤ V_{CC} ≤ 1.30	0.75 x V_{CC}		0.75 x V_{CC}			I_{OH} = −2 mA
		1.40 ≤ V_{CC} ≤ 1.60	0.75 x V_{CC}		0.75 x V_{CC}			I_{OH} = −4 mA
		1.65 ≤ V_{CC} ≤ 1.95	1.25		1.25			I_{OH} = −6 mA
		2.30 ≤ V_{CC} < 2.70	2.0		2.0			
		2.30 ≤ V_{CC} < 2.70	1.8		1.8			I_{OH} = −12 mA
		2.70 ≤ V_{CC} ≤ 3.60	2.2		2.2			
		2.30 ≤ V_{CC} < 2.70	1.7		1.7			I_{OH} = −18 mA
		2.70 ≤ V_{CC} ≤ 3.60	2.4		2.4			
		2.70 ≤ V_{CC} ≤ 3.60	2.2		2.2			I_{OH} = −24 mA

DC Electrical Characteristics (Continued)

Symbol	Parameter	V_{CC} (V)	$T_A = +25°C$ Min	$T_A = +25°C$ Max	$T_A = -40°C$ to $+85°C$ Min	$T_A = -40°C$ to $+85°C$ Max	Units	Conditions
V_{OL}	LOW Level	0.90		0.1		0.1	V	I_{OL} = 100 µA
	Output Voltage	$1.10 \le V_{CC} \le 1.30$		0.1		0.1		
		$1.40 \le V_{CC} \le 1.60$		0.2		0.2		
		$1.65 \le V_{CC} \le 1.95$		0.2		0.2		
		$2.30 \le V_{CC} < 2.70$		0.2		0.2		
		$2.70 \le V_{CC} \le 3.60$		0.2		0.2		
		$1.10 \le V_{CC} \le 1.30$		0.25 x V_{CC}		0.25 x V_{CC}		I_{OL} = 2 mA
		$1.40 \le V_{CC} \le 1.60$		0.25 x V_{CC}		0.25 x V_{CC}		I_{OL} = 4 mA
		$1.65 \le V_{CC} \le 1.95$		0.3		0.3		I_{OL} = 6 mA
		$2.30 \le V_{CC} < 2.70$		0.4		0.4		I_{OL} = 12 mA
		$2.70 \le V_{CC} \le 3.60$		0.4		0.4		
		$2.30 \le V_{CC} < 2.70$		0.6		0.6		I_{OL} = 18 mA
		$2.70 \le V_{CC} \le 3.60$		0.4		0.4		
		$2.70 \le V_{CC} \le 3.60$		0.55		0.55		I_{OL} = 24 mA
I_{IN}	Input Leakage Current	0.90 to 3.60		±0.1		±0.5	µA	$0 \le V_I \le 3.6V$
I_{OZ}	3-STATE Output Leakage	0.90 to 3.60		±0.5		±0.5	µA	$V_I = V_{IH}$ or V_{IL} $0 \le V_O \le 3.6V$
I_{OFF}	Power Off Leakage Current	0		0.5		0.5	µA	$0 \le (V_I, V_O) \le 3.6V$
I_{CC}	Quiescent Supply Current	0.90 to 3.60		0.9		0.9	µA	$V_I = V_{CC}$ or GND
		0.90 to 3.60				±0.9		$V_{CC} \le V_I \le 3.6V$

AC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	$T_A = +25°C$ Min	$T_A = +25°C$ Typ	$T_A = +25°C$ Max	$T_A = -40°C$ to $+85°C$ Min	$T_A = -40°C$ to $+85°C$ Max	Units	Conditions	Figure Number
t_{PHL}	Propagation Delay	0.90		13				ns	C_L = 15 pF, R_L = 1 MΩ	Figures 1, 2
t_{PLH}		$1.10 \le V_{CC} \le 1.30$	3.0	6.0	9.8	1.9	14.9		C_L = 15 pF, R_L = 2 kΩ	
		$1.40 \le V_{CC} \le 1.60$	1.0	3.5	5.3	0.8	5.7			
		$1.65 \le V_{CC} \le 1.95$	0.9	3.0	4.3	0.8	4.6		C_L = 30 pF	
		$2.30 \le V_{CC} < 2.70$	0.8	2.0	2.8	0.7	3.0		R_L = 500Ω	
		$2.70 \le V_{CC} \le 3.60$	0.5	1.0	2.6	0.5	2.8			
t_{PZH}	Output	0.90		14				ns	C_L = 30 pF	Figures 1, 2
t_{PZL}	Enable Time	$1.10 \le V_{CC} \le 1.30$	3.0	6.0	9.7	2.0	16.4		R_U = 1kΩ	
		$1.40 \le V_{CC} \le 1.60$	1.2	4.0	6.0	1.0	7.5		R_D = 1kΩ	
		$1.65 \le V_{CC} \le 1.95$	1.0	3.0	4.5	0.9	5.0		S_1 = GND for t_{PZH}	
		$2.30 \le V_{CC} < 2.70$	0.8	2.0	3.0	0.7	3.4		$S_1 = V_I$ for t_{PZL}	
		$2.70 \le V_{CC} \le 3.60$	0.5	1.2	2.6	0.4	2.9		V_I = 2 x V_{CC}	
t_{PHZ}	Output	0.90		14				ns	C_L = 30 pF	Figures 1, 2
t_{PLZ}	Disable Time	$1.10 \le V_{CC} \le 1.30$	2.0	5.0	9.5	2.0	14.0		R_U = 1kΩ	
		$1.40 \le V_{CC} \le 1.60$	1.2	3.0	5.5	1.1	7.0		R_D = 1kΩ	
		$1.65 \le V_{CC} \le 1.95$	1.0	2.0	5.6	0.8	5.8		S_1 = GND for t_{PHZ}	
		$2.30 \le V_{CC} < 2.70$	0.8	1.5	4.2	0.5	5.0		$S_1 = V_I$ for t_{PLZ}	
		$2.70 \le V_{CC} \le 3.60$	0.5	1.0	3.9	0.4	4.2		V_I = 2 x V_{CC}	
C_{IN}	Input Capacitance	0		2.0				pF		
C_{OUT}	Output Capacitance	0		4.5				pF		
C_{PD}	Power Dissipation Capacitance	0.90 to 3.60		10				pF	V_I = 0V or V_{CC} f = 10 MHz	

AC Loading and Waveforms



FIGURE 1. AC Test Circuit



FIGURE 2. AC Waveforms

Symbol	V_{CC}					
	3.3V ± 0.3V	**2.5V ± 0.2V**	**1.8V ± 0.15V**	**1.5V ± 0.10V**	**1.2V ± 0.10V**	**0.9V**
V_{mi}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$
V_{mo}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$

Tape and Reel Specification

TAPE FORMAT for SC70

Package Designator	Tape Section	Number Cavities	Cavity Status	Cover Tape Status
P5X	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed

TAPE DIMENSIONS inches (millimeters)





SECTION B–B



SECTION A–A



BEND RADIUS NOT TO SCALE

Tape and Reel Specification (Continued)

TAPE FORMAT for MicroPak

Package Designator	Tape Section	Number Cavities	Cavity Status	Cover Tape Status
L6X	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed

TAPE DIMENSIONS inches (millimeters)



REEL DIMENSIONS inches (millimeters)



Tape Size	A	B	C	D	N	W1	W2	W3
8 mm	7.0 (177.8)	0.059 (1.50)	0.512 (13.00)	0.795 (20.20)	2.165 (55.00)	0.331 + 0.059/–0.000 (8.40 + 1.50/–0.00)	0.567 (14.40)	W1 + 0.078/–0.039 (W1 + 2.00/–1.00)

Physical Dimensions inches (millimeters) unless otherwise noted



NOTES:

A. CONFORMS TO EIAJ REGISTERED OUTLINE DRAWING SC88A.
B. DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH.
C. DIMENSIONS ARE IN MILLIMETERS.

MAA05ARevC

5-Lead SC70, EIAJ SC-88a, 1.25mm Wide
Package Number MAA05A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Notes:

1. JEDEC PACKAGE REGISTRATION IS ANTICIPATED
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y14.5M-1994

MAC06ARevB

6-Lead MicroPak, 1.0mm Wide
Package Number MAC06A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

AMEYA360
Components Supply Platform

Authorized Distribution Brand :

Website :

Welcome to visit www.ameya360.com

Contact Us :

- ### Address :

  401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
  Minhang District, Shanghai , China

- ### Sales :

  Direct +86 (21) 6401-6692

  Email amall@ameya360.com

  QQ 800077892

  Skype ameyasales1 ameyasales2

- ### Customer Service :

  Email service@ameya360.com

- ### Partnership :

  Tel +86 (21) 64016692-8333

  Email mkt@ameya360.com