


X.FL Series

0.94 mm Height, Micro Coaxial Connector



Features

- 1. Low Profile: 0.94 mm (1 mm Max.) mating height
- 2. The World Smallest Class Coaxial Connector
- 3. High Frequency Performance (V.S.W.R.): 1.3 Max. [DC to 3GHz]
 1.4 Max. [3GHz to 6GHz]
- 4. Extra Fine Cable: ϕ 0.81 mm outer diameter
- 5. User Friendly:
 - Click feeling when fully mated improves workability and assembly quality.
- 6. Satisfies RoHS requirements, Halogen-free*
 - *NOTE: X.FL is defined as halogen-free product in accordance with IEC61249-2-21. (Br: 900 ppm Max., CI: 900 ppm Max., total concentration of Br and CI: below 1500 ppm)

♦ X.FL Specifications

	X.FL	W.FL2	W.FL
Mating Height (Excluding the solder paste thickness)	X.FL-R-SMT-1(40)	W.FL2-R-SMT-1(10) W.FL2-R-SMT-1(10)	M: LT-WS-W-1-1.4 (1.55 Max.)
High Frequency Performance (V.S.W.R.)	1.3 Max. [DC to 3 G Hz] 1.4 Max. [3 GHz to 6 GHz]		
Cable Size	φ 0.81 Coaxial Cable		
Occupied Mounting Surface		mm²	FL is mountable on the PCB ayout of W.FL and W.FL2 Series.

◆ Application Example

Mobile phone, Notebook PC, PDA, wireless device, Electronic measuring equipment, Electronic toys and games, etc.

Specifications herein are subject to change without notice. Contact Hirose for latest specifications, drawings or availabilities.

Note: All dimensions in millimeters

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

> Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com