

1 Outlet, Direct Plug-In, 350 Joules, Timer - Protect It! Surge Suppressor

MODEL NUMBER: SK10TG











Highlights

- 1 outlets/direct plug-in
- 350 joule rating
- Timer selection switch for 1, 3, or 6 hours
- Diagnostic LEDs
- \$5,000 Ultimate Lifetime
 Insurance (USA & Canada only)

Applications

 Ideal for any desktop, network or home computing application requiring AC protection

Package Includes

- SK10TG surge suppressor
- Instruction sheet

Description

The SK10TG surge suppressor with timer offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 1 outlet and 350 joules of surge energy absorption. Timer selection switch for 1, 3, or 6 hours helps make connected devices more energy efficient. On/Off push button lets you shut off outlet at any time. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$5,000 Ultimate Lifetime Insurance (USA & Canada only).

Features

- 1 outlets / direct plug-in
- Surge suppression rating: 350 joules
- Timer Feature
- · EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$5,000 Ultimate Lifetime Insurance (USA and Canada Only)

Specifications

OVERVIEW		
Intended Application	Home/Office	
ОИТРИТ		
Frequency compatibility	50 / 60 Hz	
Output watts	1875	
Circuit Breaker (amps)	15	
Outlet quantity / type	1 NEMA 5-15P	





Outlet Type	NEMA 5-15P	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input connection type	NEMA 5-15P input plug	
Input plug features	120V, 15A	
Input cord length details	Direct Plug-In	
Voltage compatibility (VAC)	120	
UPC ASSIGNMENT		
Unit Carton UPC#	037332148308	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	350	
AC suppression response time	< 1ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
Clamping voltage (RMS)	400	
AC suppression surge current rating	27,000	
UL1449 let through rating	500, 400, 500	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (HWD/in)	2.76 x 2.76 x 1.50	
Unit Dimensions (HWD/cm)	7×7×3.8	
Unit weight (lbs)	.22	
Unit weight (kg)	.10	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Direct plug-in suppressor mounts directly to a wall receptacle	
Housing Color	Black	
Receptacle Color	Black	
Style	Direct plug-in	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
Approvals	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$5,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com