

UNCONTROLLED DOCUMENT

(LX)



PART NUMBER

LCD-S301C31TR

REV.

B

| REV. | E.C.N. NUMBER AND REVISION COMMENTS | DATE     |
|------|-------------------------------------|----------|
| A    | E.C.N. #11244.                      | 5.17.05  |
| B    | E.C.N. #11148.                      | 02.08.07 |



| PIN NO. | 1   | 2  | 3  | 4  | 5   | 6  | 7  | 8  |
|---------|-----|----|----|----|-----|----|----|----|
| SEGMENT | COM | E1 | D1 | C1 | DP1 | E2 | D2 | C2 |
| PIN NO. | 9   | 10 | 11 | 12 | 13  | 14 | 15 | 16 |
| SEGMENT | DP2 | E3 | D3 | C3 | B3  | A3 | F3 | G3 |
| PIN NO. | 17  | 18 | 19 | 20 | 21  | 22 | 23 | 24 |
| SEGMENT | B2  | A2 | F2 | G2 | B1  | A1 | F1 | G1 |

| CHARACTERISTICS    |               |
|--------------------|---------------|
| FLUID TYPE:        | TN            |
| BACKGROUND COLOR:  | GRAY          |
| VIEWING DIRECTION: | 6:00          |
| DISPLAY MODE:      | REFLECTIVE    |
| OPERATING VOLTAGE: | 5.0V A.C.     |
| OPERATING TEMP.    | 0°C TO 50°C   |
| STORAGE TEMP.      | -20°C TO 70°C |
| DRIVING METHODE:   | STATIC        |
| CONNECTION TYPE:   | 24 PINS       |

REPLACES PART #: LCD-S31C301TR

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.

B

PART NUMBER

LCD-S301C31TR

0.31" CHARACTER HEIGHT, TRIPLE DIGIT LCD GLASS,  
TN, REFLECTIVE, 24 PINS.

## CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

## RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
US WEB: www.lumex.com  
TW WEB: www.lumex.com.tw

DRAWN BY:

JC

CHECKED BY:

APPROVED BY:

DATE: 11.18.98

PAGE: 1 OF 1

SCALE: N/A

(Pb)

UNCONTROLLED DOCUMENT

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)