

	1	2	3	4	5	6	7																																																																																		
A								A																																																																																	
B								B																																																																																	
C	Conductor: [26AWG(0.16/7)Bare Copper]x4C Insulation: [PP6331 ID:0.95±0.03]x4C Jacket: PVC NOUL 65P							C																																																																																	
D	Black Red Green Yellow 120±10 A, B, C, D							D																																																																																	
E	SEC:A-A 140±10 E, F, G							E																																																																																	
F	<table><tr><td>P1</td><td>P2</td></tr><tr><td>1 BLACK</td><td>4</td></tr><tr><td>2 RED</td><td>3</td></tr><tr><td>3 GREEN</td><td>2</td></tr><tr><td>4 YELLOW</td><td>1</td></tr></table>							P1	P2	1 BLACK	4	2 RED	3	3 GREEN	2	4 YELLOW	1	F																																																																							
P1	P2																																																																																								
1 BLACK	4																																																																																								
2 RED	3																																																																																								
3 GREEN	2																																																																																								
4 YELLOW	1																																																																																								
G	<table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Title</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>03.07.13</td><td>Wilson</td></tr><tr><td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td>Approved</td><td>03.07.13</td><td>Groll</td></tr><tr><td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	03.07.13	Wilson	X.	±X					Approved	03.07.13	Groll	X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°								Angle	TOL								G
Scale	Free					Date	Name	Title																																																																																	
TOLERANCE						Drawn	03.07.13	Wilson																																																																																	
X.	±X					Approved	03.07.13	Groll																																																																																	
X.X	±X																																																																																								
X.XX	±X																																																																																								
DIM	TOL																																																																																								
X.°	±X°																																																																																								
X.X°	±X°																																																																																								
Angle	TOL																																																																																								
H	Unit: mm RoHS Compliant ASSMANN components 1940 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us AT-S-26-4/4/B-xx rev00 Sheet 1/1							H																																																																																	
	1	2	3	4	5	6	7																																																																																		

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com