

supplied in strips of 24. Simply snap off the desired number of positions required and insert into PC board. The modular terminal block can be plugged into the header strip at anytime.

- Accepts #22-16 AWG wire
- Because of accumulating tolerances, we recommend a maximum of 24 positions per row
- Header strips and terminal blocks sold separately


MATERIAL:

ELECTRICAL:

MECHANICAL:

Operating Temp:
22°F to 248°F (-30°C to 120°C)
Peak Temp: +393°F (+200°C)


- Use header strip to connect to PCB



3.5mm SPACING			
CAT. NO.	POSITIONS	A DIM.	CURRENT RATING
8722	2	.276 (7.0)	6 Amps
8723	3	.413 (10.5)	

CAT. NO. 8724

- Use header strip to connect to PCB



Recommended Mtg. Hole Size: .059 (1.50)

5mm SPACING			
CAT. NO.	POSITIONS	A DIM.	CURRENT RATING
8725	2	.394 (10.0)	10 Amps
8726	3	.591 (15.0)	

CAT. NO. 8727

NOTES

[illegible]

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com