

Request a Sample

## Customer Specification PART NO. 3543

#### Construction

				Diameters (In)		
1) Component 1		30 X 1 COND				
a) Conductor b) Insulation		24 (19/36) AWG TC 0.010" Wall, Nom. PVC		0.025 0.045		
						(1) Color(s)
Cond	Color	Cond	Color	Cond	Color	
1	BROWN	11	BROWN	21	BROWN	
2	RED	12	RED	22	RED	
3	ORANGE	13	ORANGE	23	ORANGE	
4	YELLOW	14	YELLOW	24	YELLOW	
5	GREEN	15	GREEN	25	GREEN	
6	BLUE	16	BLUE	26	BLUE	
7	VILOET	17	VIOLET	27	VIOLET	
8	SLATE	18	SLATE	28	SLATE	
9	WHITE	19	WHITE	29	WHITE	
10	BLACK	20	BLACK	30	BLACK	
2) Cable Assembly		30 Component	30 Components assembled parallel.		0.045 +/- 0.002 x	
				1.350 +/- 0.060	)	

**Applicable Specifications** 

1) UL	AWM/STYLE 2713	80°C / 150 V <sub>RMS</sub>
	VW-1	
2) Military		
a) Component 1	MIL-DTL-16878/1 (Type B)	105°C / 600 V <sub>RMS</sub>

#### Environmental

1) EU Directive 2011/65/EU(RoHS2):				
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C.			
2) REACH Regulation (EC 1907/2006):				
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.			
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.			

**Properties** 

Physical & Mechanical Properties					
1) Temperature Range	-55 to 105°C				
2) Bend Radius	10X Cable Diameter				
3) Pull Tension	112 Lbs, Maximum				
Electrical Properties	(For Engineering purposes only)				
1) Voltage Rating	600 V <sub>RMS</sub>				
2) Capacitance	32 pf/ft @1 kHz, Nominal Conductor to Conductor				
3) Inductance	0.19 μH/ft, Nominal				
4) Conductor DCR	23.9 Ω/1000ft @20°C, Nominal				

#### Other

Packaging	Flange x Traverse x Barrel (inches)
a) 100 FT	11 x 1.5 x 3 Continuous length
	[Spool dimensions may vary slightly]

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

#### ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.

# AMEYA360 Components Supply Platform

#### **Authorized Distribution Brand:**

























#### Website:

Welcome to visit www.ameya360.com

#### Contact Us:

#### > Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

#### > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

#### Customer Service :

Email service@ameya360.com

### Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com