



Part Number: AS32 0R530



Electrical Specifications:

Resistance @ 25°C	0.5 $\Omega \pm 25\%$
Max Steady State Current Up to 65°C	30.0 A
Max recommended energy rating (Joules)	300.00 J
Actual failure point of instantaneous energy (Joules)	600.00 J
Resistance @ 100% of Max Current	0.012 Ω
Body Temperature @ 100% Current rating	173°C
Dissipation Constant	78.20 mW/°C
Thermal Time Constant	55 seconds
Material Type	B
ROHS Compliant	YES
MSL (moisture sensitivity level)	#2

Mechanical Specifications:

D	29.0 ± 2.0 mm
T	7.8 ± 0.5 mm
S	17.1 ± 2.0 mm
Straight Leads Coating run down	5.0 ± 2.0 mm
L	22.0 ± 2.0 mm
A (Lead Width)	2.2 ± 0.2 mm
B	4.8 ± 0.2 mm
C (Lead Thickness)	0.9 ± 0.2 mm

Revision Date: 2/2/10

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com