

POWER TRANSFORMER PC MOUNT: WORLD SERIES

VPP16-620

Electrical Specifications (@25C)

- 1. Maximum Power: 10.0VA
- 2. Input: Series: 230VAC, 50/60Hz; Parallel: 115VAC, 50/60Hz
- 3. Output: Series¹: 16.0V CT@ 0.62A; Parallel²: 8.0V @ 1.25A
- 4. Voltage Regulation: 25% TYP @ full load to no load
- 5. Temperature Rise: 30C TYP (45C MAX allowed)
- 6. Insulation Resistance: 100MΩ
- 7. Hipot: 4000VAC between primary to secondary and windings to core.

Construction:

Dual bobbin construction with an insulated shroud, both made of a high temperature material that exceeds UL flammability requirements.

Safety:

Since the dual bobbin construction effectively reduces capacitance, electrostatic shielding is not required. World Series Transformers are designed and manufactured to meet the following agency approvals:



Agency File:

UL: File E53148, UL 5085-1 and 2 (formerly UL 506), General Purpose. UL: File E65390, UL 5085-1 and 3 (formerly UL1585), Class 2/3. CSA: File LR 221330. C22.2 NO. 66, General Purpose. TUV: File R72103639, EN 60950, (IEC950) information Technology Equipment.

A. Dimensions:						Units: In inches		
А	В	С	D	Е	F	G	н	
1.25	1.375	0.187	0.200	0.400	1.562	1.875	1.140	

B. PIN DIM. : 0.036 SQ

C. WT Lbs. : 0.53

D. Mounting Holes: 0.112 dia. x 2.0

Connections³:

Input: Series – Pin 1 to Pin 6, Jumper Pin 4 to Pin 3 Parallel – Pin 1 to Pin 6, Jumper Pin 1 to Pin 4 and Pin 3 to Pin 6 Output: Series – Pin 7 to Pin 12, Jumper Pin 9 to Pin 10 Parallel – Pin 7 to Pin 12, Jumper Pin 7 to Pin 10 and Pin 9 to Pin 12

RoHS Compliance: Meets the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.


¹ Inherently limited. No fusing required. Class 2 not wet, Class 3 wet.

³ Primary and secondary windings are designed to be connected in series or parallel. Winding are not intended to be used independently.


Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757


22520B Temescal Canyon Road Corona, California 92883






A







SCHEMATIC

Publish Date: November 7, 2012

² Inherently limited. No fusing required. Class 2.



Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

- > Sales :
 - Direct +86 (21) 6401-6692
 - Email amall@ameya360.com
 - QQ 800077892
 - Skype ameyasales1 ameyasales2

> Customer Service :

Email service@ameya360.com

> Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com