


3M™ Front Sole Grounder FSG1M

The Front Sole Grounder FSG1M provides improved floor contact by covering the ball of the foot with conductive rubber. Two D-Ring straps with hook and loop, and a back clasp provide a comfortable and secure fit.



! WARNING:

All 3M Shoe Grounding Straps and Assemblies should not be used in areas where the individual may come in contact with electrical circuitry exceeding 250 volts.

Specifications	Typical Value
Hook and Loop	3/4" Black
D-Ring	2
Elastic Strap	3/4" Black with clasp
Sole Exterior	<10 ⁵ ohms
Total Grounder*	Change to 9 x 10 ⁵ ohms
<small>*Meets the requirements of ANSI/ESD S20.20-2014. *ESD-SP9.2</small>	
Part Numbers	
FSG1M-S	Small Front Sole Grounder, 1 meg resistor
FSG1M-M	Medium Front Sole Grounder, 1 meg resistor
FSG1M-L	Large Front Sole Grounder, 1 meg resistor

How Sole Grounders Work

Sole grounders eliminate a charge on a person by electrically connecting the person to a grounded surface. A conductive ribbon placed inside the wearer's shoe or sock makes electrical contact with the skin through perspiration. The assembly contains a current-limiting resistor which protects the operator from accidental exposure to electricity. Sole grounders must be worn on both feet to maintain ground contact while walking.

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



Electronics Materials Solutions Division
Static Control Products
926 JR Industrial Drive
Sanford, NC 27332-9733
Toll-Free: 866-722-3736
International: 919-718-0000
Email: 3mstaticinfo@mmm.com
www.3Mstatic.com

Please recycle. Printed in USA.
© 3M 2014. All rights reserved.
78-9102-1614-8 JHA

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com