

Current Probes for Every Application



Key Specifications

	CP030	CP030A	CP031	CP031A	CP150	CP500
Max Continuous Current	30 A _{rms}	30 A _{rms}	30 A _{rms}	30 A _{rms}	150 A _{rms}	500 A _{rms}
Max Peak Current	50 A	50 A	50 A	50 A	500 A	700 A
Bandwidth	50 MHz	50 MHz	100 MHz	100 MHz	10 MHz	2 MHz
Minimum Sensitivity	10 mA/div	1 mA/div	10 mA/div	1 mA/div	100 mA/div	100 mA/div

- **Easy to Use**
 - No need to break the circuit or insert a shunt
 - Small form factors for use on crowded boards
- **Variety of Applications**
 - Bandwidths up to 100 MHz
 - Peak currents up to 700 A
 - Sensitivities down to 1mA/div
- **High Precision Measurements**
 - Low frequency accuracy of 1%
 - Integrated autozero capability
- **Fully Integrated with Teledyne LeCroy Oscilloscope**
 - No additional hardware is required
 - Power is supplied from oscilloscope ProBus connection
 - Automatic display of waveforms in Amps and calculated power traces scaled correctly in Watts
 - Degauss and Autozero directly from oscilloscope user interface
- **DCS015 Des skew Calibration Source**
 - Provides ability to precisely des skew voltage and current probes

For more information, please contact:



CP030



CP031



CP030A



CP031A



CP150



CP500



Key Features

- Max continuous currents ranging from 30 A_{rms} to 500 A_{rms}
- Max peak currents from 50 A_{peak} to 700 A_{peak}
- Wide bandwidths from 2 MHz to 100 MHz
- ProBus active probe interface with automatic scaling in A/div
- Autozero and degauss capabilities built into user interface
- Sensitivity down to 1 mA/div
- Precise voltage and current deskew with the DCS015 deskew calibration fixture

Ordering Information

Current Probes

CP030	30 A; 50 MHz Current Probe – AC/DC; 30 Arms; 50 A Peak Pulse
CP030A	30 A; 50 MHz High Sensitivity Current Probe – AC/DC; 30 Arms; 50 A Peak Pulse
CP031	30 A; 100 MHz Current Probe – AC/DC; 30 Arms; 50 A Peak Pulse
CP031A	30 A; 100 MHz High Sensitivity Current Probe – AC/DC; 30 Arms; 50 A Peak Pulse
CP150	150 A; 10 MHz Current Probe – AC/DC; 150 Arms; 500 A Peak Pulse
CP500	500 A; 2 MHz Current Probe – AC/DC; 500 Arms; 700 A Peak Pulse
DCS015	Deskew Calibration Source for CP031, CP031A, CP030, CP030A and AP015

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com