

## Digital Phase Shifter 4-Bit, 1.4 - 2.4 GHz

Rev. V2

### Features

- 4 Bit Digital Phase Shifter
- 360° Coverage with LSB = 22.5°
- Integral CMOS Driver
- Serial or Parallel Control
- Low DC Power Consumption
- Minimal Attenuation Variation over Phase Shift Range
- 50  $\Omega$  Impedance
- EAR99
- Lead-Free 4 mm 24-Lead PQFN Package
- RoHS\* Compliant

### Description

The MAPS-010143 is a GaAs pHEMT 4-bit digital phase shifter with an integral CMOS driver in a 4 mm PQFN plastic surface mount package. Step size is 22.5° providing phase shift from 0° to 360° in 22.5° steps. This design has been optimized to minimize variation in attenuation over the phase shift range.


The MAPS-010143 is ideally suited for use where high phase accuracy with minimum loss variation over the phase shift range are required. The 4 mm PQFN package provides a smaller footprint than is typically available for a digital phase shifter with an internal driver. Typical applications include communications antennas and phased array radars.

### Ordering Information <sup>1</sup>

| Part Number        | Package           |
|--------------------|-------------------|
| MAPS-010143-TR0500 | 500 piece reel    |
| MAPS-010143-000SMB | Sample Test Board |

1. Reference Application Note M513 for reel size information.

### Functional Schematic



### Pin Configuration <sup>2</sup>

| Pin No. | Function | Pin No. | Function     |
|---------|----------|---------|--------------|
| 1       | VEE      | 13      | GND          |
| 2       | P/S      | 14      | RF OUT       |
| 3       | GND      | 15      | GND          |
| 4       | GND      | 16      | GND          |
| 5       | RF IN    | 17      | SER OUT      |
| 6       | GND      | 18      | VCC          |
| 7       | GND      | 19      | D6           |
| 8       | GND      | 20      | D5           |
| 9       | GND      | 21      | D4           |
| 10      | GND      | 22      | D3 or LE     |
| 11      | GND      | 23      | D2 or CLK    |
| 12      | GND      | 24      | D1 or SER IN |

2. The exposed pad centered on the package bottom must be connected to RF and DC ground.

\* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

**ADVANCED:** Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

**PRELIMINARY:** Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400  
 • **India** Tel: +91.80.43537383 • **China** Tel: +86.21.2407.1588  
 Visit [www.macomtech.com](http://www.macomtech.com) for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

## Digital Phase Shifter 4-Bit, 1.4 - 2.4 GHz

Rev. V2

### Electrical Specifications:

Freq. = 1.4 - 2.4 GHz,  $T_A = 25^\circ\text{C}$ ,  $Z_0 = 50\Omega$ ,  $V_{CC} = +5.0\text{V}$ ,  $V_{EE} = -5.0\text{V}$

| Parameter                                                       | Test Conditions                                                                           | Units         | Min.                       | Typ.           | Max.                            |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------|----------------------------|----------------|---------------------------------|
| Operating Power <sup>3</sup>                                    | 1.4 - 2.4 GHz                                                                             | dBm           | —                          | —              | +17                             |
| Insertion Loss<br>(Any Phase State)                             | Any Phase State                                                                           | dB            | —                          | 3.2            | 5.8                             |
| Attenuation Variation                                           | Across All Phase States                                                                   | dB            | —                          | $\pm 0.5$      | —                               |
| RMS Attenuation Error <sup>4</sup>                              | All Values Relative to Insertion Loss at Reference Phase                                  | dB            | —                          | 0.35           | —                               |
| RMS Phase Error <sup>4</sup>                                    | All Values Relative to Reference Phase                                                    | deg           | —                          | 2              | —                               |
| Phase Accuracy <sup>5</sup><br>Relative to Reference Loss State | 22.5 Degree Bit                                                                           | deg           | —                          | $\pm 1.5$      | —                               |
|                                                                 | 45 Degree Bit                                                                             |               | —                          | $\pm 1.5$      | —                               |
|                                                                 | 90 Degree Bit                                                                             |               | —                          | $\pm 2$        | —                               |
|                                                                 | 180 Degree Bit                                                                            |               | —                          | $\pm 4$        | —                               |
|                                                                 | Sum of All Bits                                                                           |               | —                          | $\pm 2$        | —                               |
| VSWR                                                            | RF IN<br>RF OUT                                                                           | Ratio         | —<br>—                     | 1.5:1<br>1.5:1 | —<br>—                          |
| 1 dB Compression                                                | Reference State                                                                           | dBm           | —                          | 25             | —                               |
| Input IP3                                                       | Two-tone inputs up to +5 dBm                                                              | dBm           | —                          | 40             | —                               |
| $V_{CC}$<br>$V_{EE}$                                            | —<br>—                                                                                    | V             | 3.0<br>-5.5                | —<br>-5.0      | 5.5<br>-3.0                     |
| $V_{IL}$<br>$V_{IH}$                                            | LOW-level input voltage<br>HIGH-level input voltage                                       | V             | 0.0<br>$0.7 \times V_{CC}$ | —<br>—         | $0.3 \times V_{CC}$<br>$V_{CC}$ |
| $I_{IN}$ (Input Control Current)                                | $V_{IN} = V_{CC}$ or GND                                                                  | $\mu\text{A}$ | —                          | 1              | —                               |
| $V_{OH}$<br>$V_{OL}$                                            | For serial out; $I_{OH} = -100 \mu\text{A}$<br>For serial out; $I_{OL} = 100 \mu\text{A}$ | V             | $V_{CC} - 0.2$<br>—        | —<br>—         | —<br>0.2                        |
| $I_{CC}$<br>(Quiescent Supply Current)                          | $V_{cntrl} = V_{CC}$ or GND                                                               | mA            | —                          | —              | 2                               |
| $I_{EE}$                                                        | $V_{EE}$ min to max<br>$V_{in} = V_{IL}$ or $V_{IH}$                                      | mA            | -1.0                       | -0.1           | —                               |

3. Maximum operating power is the maximum power where the specifications are guaranteed.

4. RMS is calculated across all 15 amplitude or phase states relative to the amplitude or phase in the  $0^\circ$  phase state at a given frequency.


5. This phase shifter is guaranteed to have monotonic phase shift.

## Digital Phase Shifter 4-Bit, 1.4 - 2.4 GHz


Rev. V2

### Typical Performance Curves


**$RF_{IN}$  Return Loss vs. Frequency (All States)**




**$RF_{OUT}$  Return Loss vs. Frequency (All States)**




**Mean RMS Phase Error vs. Frequency**




**Mean RMS Amplitude Error vs. Frequency**



**Phase Error (degrees) vs. State**



**Amplitude Error (dB) vs. State**




## Digital Phase Shifter 4-Bit, 1.4 - 2.4 GHz


Rev. V2

### Typical Performance Curves

Amplitude Variation vs. Phase State



Phase Shift vs. Frequency (All States)



### Absolute Maximum Ratings<sup>6,7</sup>

| Parameter                         | Absolute Maximum                        |
|-----------------------------------|-----------------------------------------|
| Max. Input Power<br>1.4 - 2.4 GHz | +25 dBm                                 |
| $V_{CC}$                          | $-0.5V \leq V_{CC} \leq +7.0V$          |
| $V_{EE}$                          | $-7.0V \leq V_{EE} \leq +0.5V$          |
| D1-D4, P/S, LE, CLK or<br>SER IN  | $-0.5V \leq V_{IN} \leq V_{CC} + 0.5V$  |
| SER OUT                           | $-0.5V \leq V_{OUT} \leq V_{CC} + 0.5V$ |
| Operating Temperature             | $-40^{\circ}C$ to $+85^{\circ}C$        |
| Storage Temperature               | $-65^{\circ}C$ to $+125^{\circ}C$       |

6. Exceeding any one or combination of these limits may cause permanent damage to this device.  
7. M/A-COM Technology Solutions does not recommend sustained operation near these survivability limits.

### Handling Procedures

Please observe the following precautions to avoid damage:

### Static Sensitivity

Gallium Arsenide and Silicon Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.

### Modes of Operation: Serial and Direct Parallel

#### Serial Mode

The serial control interface (SERIN, CLK, LE, SEROUT) is compatible with the SPI protocol. SPI mode is activated when P/S is kept high. The 6-bit serial word must be loaded with the MSB first. After shifting in the 6 bit word, a rising edge on LE will set the phase shifter to the desired state. While LE is high the CLK is masked to protect the data while implementing the change. SEROUT is SERIN delayed by 6 clock cycles.

When P/S is low, the serial control interface is disabled. When P/S is set high, Pins 22, 23, and 24 have the LE, CLK, and SER IN function.

In serial mode operation, the outputs will stay constant while LE is kept low.

#### Direct Parallel Mode

The parallel mode is enabled when P/S is set low. In the direct parallel mode, the phase shifter is controlled by the parallel control inputs directly. When P/S is set low, Pins 22, 23, and 24 have the D3, D2, and D1 function.

#### Mode Truth Table <sup>8,9</sup>

| P/S | LE  | Mode            |
|-----|-----|-----------------|
| 1   | X   | Serial          |
| 0   | N/A | Direct Parallel |

8. There are two dummy bits (D1 & D2), that must be sent in the serial mode. This is because the 4 bit phase shifter uses the same driver as the 6 bit phase shifter.  
9. In the parallel mode, D1 and D2 should be tied to ground or to V<sub>CC</sub>.

#### Truth Table (Digital Phase Shifter) <sup>10</sup>

| D6 | D5 | D4 | D3 | D2 | D1 | Phase Shift     |
|----|----|----|----|----|----|-----------------|
| 0  | 0  | 0  | 0  | X  | X  | Loss, Reference |
| 0  | 0  | 0  | 0  | X  | X  | N/A             |
| 0  | 0  | 0  | 0  | X  | X  | N/A             |
| 0  | 0  | 0  | 1  | X  | X  | 22.5 deg        |
| 0  | 0  | 1  | 0  | X  | X  | 45 deg          |
| 0  | 1  | 0  | 0  | X  | X  | 90 deg          |
| 1  | 0  | 0  | 0  | X  | X  | 180 deg         |
| 1  | 1  | 1  | 1  | X  | X  | 337.5 deg       |

10. 0 = CMOS Low; 1 = CMOS High, X is CMOS Low or High


### Serial Interface Timing Characteristics

| Symbol           | Parameter                           | Typical Performance |      |       | Units |
|------------------|-------------------------------------|---------------------|------|-------|-------|
|                  |                                     | -40°C               | 25°C | +85°C |       |
| t <sub>SCK</sub> | Min. Serial Clock Period            | 100                 | 100  | 100   | ns    |
| t <sub>CS</sub>  | Min. Control Set-up Time            | 20                  | 20   | 20    | ns    |
| t <sub>CH</sub>  | Min. Control Hold Time              | 20                  | 20   | 20    | ns    |
| t <sub>LS</sub>  | Min. LE Set-up Time                 | 10                  | 10   | 10    | ns    |
| t <sub>LEW</sub> | Min. LE Pulse Width                 | 10                  | 10   | 10    | ns    |
| t <sub>LH</sub>  | Min. Serial Clock Hold Time from LE | 10                  | 10   | 10    | ns    |
| t <sub>LES</sub> | Min. LE Pulse Spacing               | 630                 | 630  | 630   | ns    |


## Functionality

### Modes of Operation: Serial and Direct Parallel

### Serial Input Interface Timing Diagram



### Lead Free 4 mm 24-Lead PQFN<sup>†</sup>



<sup>†</sup> Reference Application Note S2083 for lead-free solder reflow recommendations.  
 Meets JEDEC moisture sensitivity level 1 requirements.  
 Plating is 100% matte tin over copper.

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com