

## Part Number System for Corrugated Loom Tubing

| CLT                                  | 100                                                                                                                                     | N                                             | — | C                                                                                                                                                                                    | 630                                                                                                                  |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Type                                 | Bundle Diameter                                                                                                                         | Material                                      |   | Package Size                                                                                                                                                                         | Color Suffix                                                                                                         |
| CLT = Slit Wall<br>CLTS = Solid Wall | 25 = 1/4"<br>35 = 5/16"<br>38 = 3/8"<br>50 = 1/2"<br>62 = 5/8"<br>75 = 3/4"<br>100 = 1"<br>125 = 1 1/4"<br>150 = 1 1/2"<br>188 = 1 7/8" | N = Heat Stabilized Nylon<br>F = Polyethylene |   | X = 10'<br>L = 50'<br>C = 100'<br>T = 200'<br>D = 500'<br>.75M = 750'<br>125M = 1,250'<br>2M = 2,000'<br>2.5M = 2,500'<br>4M = 4,000'<br>5M = 5,000'<br>7M = 7,000'<br>10M = 10,000' | 630 = Heat Stabilized Black Nylon 6<br>20 = Black Polyethylene<br>3 = Orange Polyethylene<br>4 = Yellow Polyethylene |

## Corrugated Loom Tubing – Slit



- Provides protection for cables
- Packaged on a reel for easy handling and dispensing of product
- For indoor use only

- Available in Nylon or Polyethylene, this product features a lengthwise slit which makes it easy to install onto a bundle of wires or a pre-assembled harness assembly
- Crush, impact and abrasion resistant

| Part Number   | Material     | Color  | Length Per Reel |        | Inside Diameter |      | Outside Diameter |      | Temperature Range            | Std. Pkg. Qty.* |
|---------------|--------------|--------|-----------------|--------|-----------------|------|------------------|------|------------------------------|-----------------|
|               |              |        | Ft.             | m      | In.             | mm   | In.              | mm   |                              |                 |
| Slit Wall     |              |        |                 |        |                 |      |                  |      |                              |                 |
| CLT25F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT25F-C4     | Polyethylene | Yellow | 100             | 30.5   | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT25F-C20    | Polyethylene | Black  | 100             | 30.5   | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT25F-10M20  | Polyethylene | Black  | 10,000          | 3048.0 | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT35F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT35F-C4     | Polyethylene | Yellow | 100             | 30.5   | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT35F-C20    | Polyethylene | Black  | 100             | 30.5   | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT35F-7M20   | Polyethylene | Black  | 7,000           | 2133.6 | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT38F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT38F-C4     | Polyethylene | Yellow | 100             | 30.5   | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT38F-C20    | Polyethylene | Black  | 100             | 30.5   | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT38F-5M20   | Polyethylene | Black  | 5,000           | 1524.0 | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT50F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT50F-C4     | Polyethylene | Yellow | 100             | 30.5   | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT50F-C20    | Polyethylene | Black  | 100             | 30.5   | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT50F-4M20   | Polyethylene | Black  | 4,000           | 1219.2 | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT62F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT62F-C4     | Polyethylene | Yellow | 100             | 30.5   | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT62F-C20    | Polyethylene | Black  | 100             | 30.5   | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT62F-2.5M20 | Polyethylene | Black  | 2,500           | 762.0  | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1               |
| CLT75F-C3     | Polyethylene | Orange | 100             | 30.5   | 0.76            | 19.3 | 0.94             | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1               |

\*Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Table continues on page C3.12

A.  
System  
Overview

## Corrugated Loom Tubing – Slit (continued)

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

| Part Number    | Material     | Color  | Length<br>Per Reel |       | Inside<br>Diameter |      | Outside<br>Diameter |      | Temperature<br>Range         | Std.<br>Pkg.<br>Qty.* |
|----------------|--------------|--------|--------------------|-------|--------------------|------|---------------------|------|------------------------------|-----------------------|
|                |              |        | Ft.                | m     | In.                | mm   | In.                 | mm   |                              |                       |
| CLT75F-C4      | Polyethylene | Yellow | 100                | 30.5  | 0.76               | 19.3 | 0.94                | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT75F-C20     | Polyethylene | Black  | 100                | 30.5  | 0.76               | 19.3 | 0.94                | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT75F-2M20    | Polyethylene | Black  | 2,000              | 609.6 | 0.76               | 19.3 | 0.94                | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT100F-X4     | Polyethylene | Yellow | 10                 | 3.1   | 0.92               | 23.2 | 1.09                | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT100F-C3     | Polyethylene | Orange | 100                | 30.5  | 0.92               | 23.2 | 1.09                | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT100F-C4     | Polyethylene | Yellow | 100                | 30.5  | 0.92               | 23.2 | 1.09                | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT100F-C20    | Polyethylene | Black  | 100                | 30.5  | 0.92               | 23.2 | 1.09                | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT100F-125M20 | Polyethylene | Black  | 1,250              | 381.0 | 0.92               | 23.2 | 1.09                | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT125F-L3     | Polyethylene | Orange | 50                 | 15.2  | 1.29               | 32.8 | 1.50                | 38.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT125F-L4     | Polyethylene | Yellow | 50                 | 15.2  | 1.29               | 32.8 | 1.50                | 38.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT125F-L20    | Polyethylene | Black  | 50                 | 15.2  | 1.29               | 32.8 | 1.50                | 38.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT125F-.75M20 | Polyethylene | Black  | 750                | 228.6 | 1.29               | 32.8 | 1.50                | 38.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-X3     | Polyethylene | Orange | 10                 | 3.1   | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-X4     | Polyethylene | Yellow | 10                 | 3.1   | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-T20    | Polyethylene | Black  | 200                | 61.0  | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-D3     | Polyethylene | Orange | 500                | 152.4 | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-D4     | Polyethylene | Yellow | 500                | 152.4 | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT150F-D20    | Polyethylene | Black  | 500                | 152.4 | 1.48               | 37.6 | 1.73                | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT188F-X3     | Polyethylene | Orange | 10                 | 3.1   | 1.88               | 47.8 | 2.17                | 55.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT188F-X4     | Polyethylene | Yellow | 10                 | 3.1   | 1.88               | 47.8 | 2.17                | 55.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |
| CLT188F-X20    | Polyethylene | Black  | 10                 | 3.1   | 1.88               | 47.8 | 2.17                | 55.1 | -40°F – 122°F (-40°C – 50°C) | 1                     |

### Solid Wall

|                |              |        |        |        |      |      |      |      |                              |   |
|----------------|--------------|--------|--------|--------|------|------|------|------|------------------------------|---|
| CLTS25F-C      | Polyethylene | Black  | 100    | 30.5   | 0.28 | 7.0  | 0.40 | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS25F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.28 | 7.0  | 0.40 | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS25F-10M    | Polyethylene | Black  | 10,000 | 3048.0 | 0.28 | 7.0  | 0.40 | 10.1 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS35F-C      | Polyethylene | Black  | 100    | 30.5   | 0.35 | 8.9  | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS35F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.35 | 8.9  | 0.50 | 12.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS38F-C      | Polyethylene | Black  | 100    | 30.5   | 0.42 | 10.5 | 0.56 | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS38F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.42 | 10.5 | 0.56 | 14.1 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS50F-C      | Polyethylene | Black  | 100    | 30.5   | 0.51 | 12.8 | 0.67 | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS50F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.51 | 12.8 | 0.67 | 17.0 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS62F-C      | Polyethylene | Black  | 100    | 30.5   | 0.65 | 16.5 | 0.82 | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS62F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.65 | 16.5 | 0.82 | 20.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS75F-C      | Polyethylene | Black  | 100    | 30.5   | 0.76 | 19.3 | 0.94 | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS75F-C3     | Polyethylene | Orange | 100    | 30.5   | 0.76 | 19.3 | 0.94 | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS75F-2M     | Polyethylene | Black  | 2,000  | 609.6  | 0.76 | 19.3 | 0.94 | 23.8 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS100F-C     | Polyethylene | Black  | 100    | 30.5   | 0.92 | 23.2 | 1.09 | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS100F-C3    | Polyethylene | Orange | 100    | 30.5   | 0.92 | 23.2 | 1.09 | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS100F-1.25M | Polyethylene | Black  | 1,250  | 381.0  | 0.92 | 23.2 | 1.09 | 27.7 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS150F-D     | Polyethylene | Black  | 500    | 152.4  | 1.48 | 37.6 | 1.73 | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1 |
| CLTS150F-D3    | Polyethylene | Orange | 500    | 152.4  | 1.48 | 39.1 | 1.73 | 43.9 | -40°F – 122°F (-40°C – 50°C) | 1 |

\*Reel packaging may contain splices. Contact Panduit Customer Service for further information.

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index

Order number of reels required, in multiples of Standard Package Quantity.

## Corrugated Loom Tubing – Slit (continued)

| Part Number     | Material                | Color | Length Per Reel |        | Inside Diameter |      | Outside Diameter |      | Temperature Range             | Std. Pkg. Qty.* |
|-----------------|-------------------------|-------|-----------------|--------|-----------------|------|------------------|------|-------------------------------|-----------------|
|                 |                         |       | Ft.             | m      | In.             | mm   | In.              | mm   |                               |                 |
| Nylon Slit      |                         |       |                 |        |                 |      |                  |      |                               |                 |
| CLT25N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT25N-10M630   | Heat Stabilized Nylon 6 | Black | 10,000          | 3048.0 | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT35N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT38N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT38N-5M630    | Heat Stabilized Nylon 6 | Black | 5,000           | 1524.0 | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT50N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT50N-4M630    | Heat Stabilized Nylon 6 | Black | 4,000           | 1219.2 | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT62N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.65            | 16.5 | 0.83             | 20.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT62N-2.5M630  | Heat Stabilized Nylon 6 | Black | 2,500           | 762.0  | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT75N-C630     | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.76            | 19.3 | 0.94             | 23.8 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT75N-2M630    | Heat Stabilized Nylon 6 | Black | 2,000           | 609.6  | 0.76            | 19.3 | 0.94             | 23.8 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT100N-C630    | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.92            | 23.2 | 1.09             | 27.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT100N-125M630 | Heat Stabilized Nylon 6 | Black | 1,250           | 381.0  | 0.92            | 23.2 | 1.09             | 27.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT125N-L630    | Heat Stabilized Nylon 6 | Black | 50              | 15.2   | 1.29            | 32.8 | 1.50             | 38.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT125N-.75M630 | Heat Stabilized Nylon 6 | Black | 750             | 228.6  | 1.29            | 32.8 | 1.50             | 38.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT150N-D630    | Heat Stabilized Nylon 6 | Black | 500             | 152.4  | 1.48            | 37.6 | 1.73             | 43.9 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLT188N-6C630   | Heat Stabilized Nylon 6 | Black | 600             | 183.0  | 1.88            | 47.8 | 2.17             | 55.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| Nylon Solid     |                         |       |                 |        |                 |      |                  |      |                               |                 |
| CLTS25N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS25N-10M     | Heat Stabilized Nylon 6 | Black | 10,000          | 3048.0 | 0.28            | 7.0  | 0.40             | 10.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS35N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.35            | 8.9  | 0.50             | 12.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS38N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.42            | 10.5 | 0.56             | 14.1 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS50N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.51            | 12.8 | 0.67             | 17.0 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS62N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.65            | 16.5 | 0.82             | 20.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS75N-C       | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.76            | 19.3 | 0.94             | 23.8 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS75N-2M      | Heat Stabilized Nylon 6 | Black | 2,000           | 609.6  | 0.76            | 19.3 | 0.94             | 23.8 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS100N-C      | Heat Stabilized Nylon 6 | Black | 100             | 30.5   | 0.92            | 23.2 | 1.09             | 27.7 | -40°F – 230°F (-40°C – 110°C) | 1               |
| CLTS125N-L      | Heat Stabilized Nylon 6 | Black | 50              | 15.2   | 1.29            | 32.8 | 1.50             | 38.1 | -40°F – 230°F (-40°C – 110°C) | 1               |

\*Reel packaging may contain splices. Contact Panduit Customer Service for further information.

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com