



NOTE:

1. ELECTRICAL CHARACTERISTIC:
 - 1) VOLTAGE CURRENT RATING: 0.5AMP, 100V AC
 - 2) INSULATION RESISTANCE: 100MΩ MIN;
 - 3) CONTACT RESISTANCE: 30mΩ MAX;
 - 4) DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S.
2. Mechanical:
 - 1) Mating Force: 35 N MAX
 - 2) Unmating Force: 10 N MIN.
3. DIMENSIONS MARKED '▼' TO BE CHECKED BY Q.C & IPQC.

Bill of materials:

3	HOUSING	PA9T+30%GF, UL94 V-0	1	UL 94V-0	X ±0.3	X' ±2"
2	SHELL	SPCC/STEEL	1	PLATED Ni	.X ±0.2	.X' ±1"
1	TERMINAL	COPPER ALLOY (C2680)	4	Gold flash on contact tin on tail	.XX ±0.15	.XX"
NO	PARTS	MATERIAL	QTY	FINISHING	.XXX ±0.10	.XXX"

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com