


59020 Mini Firecracker Features and Benefits



Features

- 2 part magnetically operated proximity sensor
- Normally open contact
- Customer defined sensitivity
- Choice of cable length and connector


Benefits

- Quick and easy to install
- No standby power requirement
- Operates through non-ferrous materials such as wood, plastic or aluminium
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination

Applications

- Position and limit sensing
- Security
- Level sensing
- Linear actuators

DIMENSIONS (in) mm



	A Max	B Max	C NOM.
57020	(.201) 5,10	(.600) 15,24	-
59020	(.201) 5,10	(.600) 15,24	Table 3 ± (.393) 10,00

CUSTOMER OPTIONS - Switching Specifications

TABLE 1			Normally Open
Contact Type			I
Switch Type			I
Power	Watt - max.		10
	Vdc - max.		170
Voltage	Switching		175
	Breakdown		
Current	Switching	A - max.	0.5
	Carry	A - max.	0.5
Resistance	Contact, Initial	Ω - max.	0.2
	Insulation	Ω - min.	10 ¹⁰
Capacitance	Contact	pF - typ.	0.2
Temperature	Operating	°C	-40 to +105
	Storage	°C	-65 to +105
Time	Operate	ms - max.	1.0
	Release	ms - max.	1.0
Shock	11ms 1/2 sine	G - max.	100
Vibration	50-2000 Hz	G - max.	30

CUSTOMER OPTIONS - Sensitivity, Cable Length and Termination Specification

TABLE 2							TABLE 3		TABLE 4			
Sensitivity Options:- Activate Distances are approximate using Hamlin 57020 actuator as illustrated. Switch AT before modification							Cable Type:- 24 AWG 7/32 PVC 105°C UL1430/UL1569		Termination Options:-			
							Standard Lengths		SELECT OPTION	DESCRIPTION		
Switch Type	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	SELECT OPTION	CABLE LENGTH (in) mm	A	Tinned leads		
I	Normally Open	6-10 (.236) 6,0	10-15 (.177) 4,5	13-19 (.157) 4,0			01	(3,94) 100	C	6.35mm fastons		
							02	(11,81) 300	D	AMP MTE 2.54mm pitch		
							03	(19,69) 500	E	JST XHP 2.5mm pitch		
							04	(29,53) 750				
							05	(39,37) 1000				

ORDERING INFORMATION

N.B. 57020 actuator sold separately

59020 - I - X - XX - X

Series 59020

Switch Type

Sensitivity

Cable Length

Termination

Table 1

Table 2

Table 3

Table 4

Hamlin USA Tel: +1 920 648 3000 • Fax: +1 920 648 3001 • Email: sales.us@hamlin.com
Hamlin UK Tel: +44 (0)1379 649700 • Fax: +44 (0)1379 649702 • Email: sales.uk@hamlin.com
Hamlin Germany Tel: +49 (0) 6181 953660 • Fax: +49 (0) 6181 953666 • Email: sales.de@hamlin.com
Hamactrol France Tel: +33 (0) 1 4687 0202 • Fax: +33 (0) 1 4686 6786 • Email: sales.fr@hamlin.com

ISSUE No: 4 DATE: 1/5/3

DETAILS PROVIDED ON THIS DATA SHEET ARE PROVIDED FOR INFORMATION PURPOSES ONLY AND SHOULD NOT BE RELIED UPON AS BEING ACCURATE FOR ANY PARTICULAR PURPOSE. Product performance may be affected by the application to which the product is put. Upon request, HAMLIN will assist purchasers by providing information specific to any particular application. HAMLIN disclaims any and all liability whatsoever for any purchaser's reliance upon the information contained on this data sheet without further consultation with authorised representatives of HAMLIN.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com