



ALL NEW PRODUCTS!



STANDARD PACK 1,000/BAG

HEYClip™ Releasable Type "T" Rivets


- The "T" style rivet is designed with a **large finger grip**, knob-shaped head for optimal installation and removal by simply pushing or pulling the rivet from the hole.
- Can be used multiple times.
- Part Description Key: KR X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Material: Nylon 6. Nylon 6/6 UL 94V-0 available by special order, consult Heyco.
- Standard Pack - 1,000/bag.

WILL FIT THESE PANELS				PART NO.		DESCRIPTION	PART DIMENSIONS						STYLE			
MOUNTING HOLE DIA.		PANEL THICKNESS		Black	White		A Length		B Head Height		C Head Diameter					
in.	mm.	Min. in.	Max. mm.					in.	mm.	in.	mm.	in.	mm.			
KR Series																
.122	3,1	.04	1,0	.08	2,0	9088	9089	KR 122-039		.14	3,5					
		.08	2,0	.12	3,0	9090	9091	KR 122-079		.18	4,5					
		.12	3,0	.16	4,0	9092	9093	KR 122-118		.22	5,5					
		.16	4,0	.20	5,0	9094	9095	KR 122-157		.26	6,5	.32	8,0	.39	10,0	1
		.20	5,0	.24	6,0	9194	9195	KR 122-197		.30	7,5					
		.22	5,5	.26	6,5	9096	9097	KR 122-217		.32	8,0					
.142	3,6	.04	1,0	.08	2,0	9098	9099	KR 142-039		.14	3,5					
		.08	2,0	.12	3,0	9100	9101	KR 142-079		.18	4,5					
		.12	3,0	.16	4,0	9102	9103	KR 142-118		.22	5,5					
		.14	3,5	.18	4,5	9104	9105	KR 142-137		.24	6,0	.32	8,0	.39	10,0	2
		.18	4,5	.22	5,5	9106	9107	KR 142-177		.28	7,0					
		.22	5,5	.26	6,5	9196	9197	KR 142-217		.32	8,0					
.161	4,1	.10	2,5	.14	3,5	9108	9109	KR 161-098		.20	5,0					
		.14	3,5	.18	4,5	9110	9111	KR 161-137		.24	6,0					
		.18	4,5	.22	5,5	9112	9113	KR 161-177		.28	7,0					
		.22	5,5	.26	6,5	9114	9115	KR 161-217		.32	8,0	.32	8,0	.47	12,0	2
		.26	6,5	.30	7,5	9198	9199	KR 161-256		.35	9,0					
		.30	7,5	.34	8,5	9116	9117	KR 161-295		.39	10,0					

Standard colors black and white.



KR Series



DF Series

HEYClip™ Drive Fasteners

- Heyco Drive Fasteners help secure and fasten components and/or panels to a wide variety of materials such as wood, metal, particle board, plastic and rubber.
- Hollow body design increases flexibility, for easy installation.
- Part Description Key: DF X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).

WILL FIT THESE PANELS				PART NO.		DESCRIPTION	PART DIMENSIONS								
MOUNTING HOLE DIA.		PANEL THICKNESS		Black	Natural		A Length		B Head Height		C Head Diameter				
in.	mm.	Min. in.	Max. mm.					in.	mm.	in.	mm.	in.	mm.		
DF Series															
.125	3,2	.04	1,0	.18	4,5	9201	9202	DF 125-039		.51	13,0	.06	1,5	.31	8,0
.154	3,9	.04	1,0	.20	5,0	9203	9204	DF 154-039		.55	14,0	.06	1,6	.35	9,0
.185	4,7	.04	1,0	.22	5,5	9205	9206	DF 185-039		.59	15,0	.07	1,7	.39	10,0
.307	7,8	.06	1,5	.28	7,0	9207	9208	DF 307-059		.75	19,0	.09	2,2	.55	14,0
.217	5,5	.24	6,0	.35	9,0	9209	9210	DF 217-236		.71	18,0	.08	2,0	.47	12,0

Standard colors black and natural.

Material	KR Series Nylon 6	DF Series Acetal (POM)
Flammability Rating	94V-2	94-HB
Temperature Rating	-0.4°F (-18°C) to 185°F (85°C)	-0.4°F (-18°C) to 220°F (104°C)

Quick Specs

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com