

# FAN5400/FAN5401/FAN5402/ FAN5403/ FAN5404/ FAN5405 USB-Compliant Single-Cell Li-Ion Switching Charger with USB-OTG Boost Regulator

## Features

- Fully Integrated, High-Efficiency Charger for Single-Cell Li-Ion and Li-Polymer Battery Packs
- Faster Charging than Linear
- Charge Voltage Accuracy:  $\pm 0.5\%$  at  $25^{\circ}\text{C}$   
 $\pm 1\%$  from  $0$  to  $125^{\circ}\text{C}$
- $\pm 5\%$  Input Current Regulation Accuracy
- $\pm 5\%$  Charge Current Regulation Accuracy
- 20 V Absolute Maximum Input Voltage
- 6 V Maximum Input Operating Voltage
- 1.25 A Maximum Charge Rate
- Programmable through High-Speed I<sup>2</sup>C Interface (3.4 Mb/s) with Fast Mode Plus Compatibility
  - Input Current
  - Fast-Charge / Termination Current
  - Charger Voltage
  - Termination Enable
- 3 MHz Synchronous Buck PWM Controller with Wide Duty Cycle Range
- Small Footprint 1  $\mu\text{H}$  External Inductor
- Safety Timer with Reset Control
- 1.8 V Regulated Output from VBUS for Auxiliary Circuits
- Weak Input Sources Accommodated by Reducing Charging Current to Maintain Minimum VBUS Voltage
- Low Reverse Leakage to Prevent Battery Drain to VBUS
- 5 V, 300 mA Boost Mode for USB OTG for 2.5 to 4.5 V Battery Input

## Applications

- Cell Phones, Smart Phones, PDAs
- Tablet, Portable Media Players
- Gaming Device, Digital Cameras

## Description

The FAN5400 family (FAN540X) combines a highly integrated switch-mode charger, to minimize single-cell Lithium-ion (Li-ion) charging time from a USB power source, and a boost regulator to power a USB peripheral from the battery.

The charging parameters and operating modes are programmable through an I<sup>2</sup>C Interface that operates up to 3.4 Mbps. The charger and boost regulator circuits switch at 3 MHz to minimize the size of external passive components.

The FAN540X provides battery charging in three phases: conditioning, constant current, and constant voltage.

To ensure USB compliance and minimize charging time, the input current is limited to the value set through the I<sup>2</sup>C host. Charge termination is determined by a programmable minimum current level. A safety timer with reset control provides a safety backup for the I<sup>2</sup>C host.

The integrated circuit (IC) automatically restarts the charge cycle when the battery falls below an internal threshold. If the input source is removed, the IC enters a high-impedance mode with leakage from the battery to the input prevented. Charge status is reported back to the host through the I<sup>2</sup>C port. Charge current is reduced when the die temperature reaches  $120^{\circ}\text{C}$ .

The FAN540X can operate as a boost regulator on command from the system. The boost regulator includes a soft-start that limits inrush current from the battery.

The FAN540X is available in a 1.96 x 1.87 mm, 20-bump, 0.4 mm pitch, WLCSP package.




Figure 1. Typical Application (FAN5403-05 Pin Out)

All trademarks are the property of their respective owners.

## Ordering Information

| Part Number | Temperature Range | Package                                                                                      | PN Bits: IC_INFO[4:3] | Packing Method |
|-------------|-------------------|----------------------------------------------------------------------------------------------|-----------------------|----------------|
| FAN5400UCX  | -40 to 85°C       | 20- Bump, Wafer-Level Chip-Scale Package (WLCSP), 0.4mm Pitch, Estimated Size: 1.96 x 1.87mm | 01                    | Tape and Reel  |
| FAN5401UCX  | -40 to 85°C       |                                                                                              | 00                    | Tape and Reel  |
| FAN5402UCX  | -40 to 85°C       |                                                                                              | 01                    | Tape and Reel  |
| FAN5403UCX  | -40 to 85°C       |                                                                                              | 10                    | Tape and Reel  |
| FAN5404UCX  | -40 to 85°C       |                                                                                              | 11                    | Tape and Reel  |
| FAN5405UCX  | -40 to 85°C       |                                                                                              | 10                    | Tape and Reel  |

**Table 1. Feature Comparison Summary**

| Part Number | PN Bits: REG3[4:3] | Slave Address | Automatic Charge | Special Charger <sup>(1)</sup> | Safety Limits | Battery Absent Behavior | E2 Pin                   | VREG (E3 Pin) |
|-------------|--------------------|---------------|------------------|--------------------------------|---------------|-------------------------|--------------------------|---------------|
| FAN5400     | 01                 | 1101011       | Yes              | No                             | No            | OFF                     | AUXPWR (Connect to VBAT) | PMID          |
| FAN5401     | 00                 | 1101011       | No               | No                             | No            | OFF                     |                          |               |
| FAN5402     | 01                 | 1101011       | Yes              | No                             | No            | ON                      |                          |               |
| FAN5403     | 10                 | 1101011       | Yes              | Yes                            | Yes           | OFF                     | DISABLE                  | 1.8V          |
| FAN5404     | 11                 | 1101011       | No               | Yes                            | Yes           | OFF                     |                          |               |
| FAN5405     | 10                 | 1101010       | Yes              | Yes                            | Yes           | ON                      |                          |               |

**Note:**

1. Special charger is a current limited charger that is not a USB compliant source.

**Table 2. Recommended External Components**

| Component        | Description                        | Vendor                                        | Parameter        | Typ. | Unit       |
|------------------|------------------------------------|-----------------------------------------------|------------------|------|------------|
| L1               | 1 $\mu$ H, 20%, 1.3 A, 2016        | Murata: LQM2MPN1R0M or Equivalent             | L                | 1.0  | $\mu$ H    |
|                  |                                    |                                               | DCR (Series R)   | 85   | m $\Omega$ |
| C <sub>BAT</sub> | 10 $\mu$ F, 20%, 6.3 V, X5R, 0603  | Murata: GRM188R60J106M<br>TDK: C1608X5R0J106M | C                | 10   | $\mu$ F    |
| C <sub>MID</sub> | 4.7 $\mu$ F, 10%, 6.3 V, X5R, 0603 | Murata: GRM188R60J475K<br>TDK: C1608X5R0J475K | C <sup>(2)</sup> | 4.7  | $\mu$ F    |
| C <sub>BUS</sub> | 1.0 $\mu$ F, 10%, 25 V, X5R, 0603  | Murata GRM188R61E105K<br>TDK: C1608X5R1E105M  | C                | 1.0  | $\mu$ F    |

**Note:**

2. 6.3 V rating is sufficient for C<sub>MID</sub> since PMID is protected from over-voltage surges on VBUS by Q3 (Figure 3).

## Block Diagram




Figure 2. IC and System Block Diagram




Figure 3. Power Stage

## Pin Configuration



Figure 4. WLCSP-20 Pin Assignments

## Pin Definitions

| Pin #  | Name    | Part #                          | Description                                                                                                                                                                                                                                                      |
|--------|---------|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A1, A2 | VBUS    | ALL                             | <b>Charger Input Voltage</b> and USB-OTG output voltage. Bypass with a 1 $\mu$ F capacitor to PGND.                                                                                                                                                              |
| A3     | NC      | ALL                             | <b>No Connect.</b> No external connection is made between this pin and the IC's internal circuitry.                                                                                                                                                              |
| A4     | SCL     | ALL                             | <b>I<sup>2</sup>C Interface Serial Clock.</b> This pin should not be left floating.                                                                                                                                                                              |
| B1-B3  | PMID    | ALL                             | <b>Power Input Voltage.</b> Power input to the charger regulator, bypass point for the input current sense, and high-voltage input switch. Bypass with a minimum of 4.7 $\mu$ F, 6.3 V capacitor to PGND.                                                        |
| B4     | SDA     | ALL                             | <b>I<sup>2</sup>C Interface Serial Data.</b> This pin should not be left floating.                                                                                                                                                                               |
| C1-C3  | SW      | ALL                             | <b>Switching Node.</b> Connect to output inductor.                                                                                                                                                                                                               |
| C4     | STAT    | ALL                             | <b>Status.</b> Open-drain output indicating charge status. The IC pulls this pin LOW when charge is in process.                                                                                                                                                  |
| D1-D3  | PGND    | ALL                             | <b>Power Ground.</b> Power return for gate drive and power transistors. The connection from this pin to the bottom of C <sub>MID</sub> should be as short as possible.                                                                                           |
| D4     | OTG     | ALL                             | <b>On-The-Go.</b> Enables boost regulator in conjunction with OTG_EN and OTG_PL bits (see Table 16). On VBUS Power-On Reset (POR), this pin sets the input current limit for t <sub>15MIN</sub> charging.                                                        |
| E1     | CSIN    | ALL                             | <b>Current-Sense Input.</b> Connect to the sense resistor in series with the battery. The IC uses this node to sense current into the battery. Bypass this pin with a 0.1 $\mu$ F capacitor to PGND.                                                             |
| E2     | AUXPWR  | FAN5400,<br>FAN5401,<br>FAN5402 | <b>Auxiliary Power.</b> Connect to the battery pack to provide IC power during High-Impedance Mode. Bypass with a 1 $\mu$ F capacitor to PGND.                                                                                                                   |
| E2     | DISABLE | FAN5403,<br>FAN5404,<br>FAN5405 | <b>Charge Disable.</b> If this pin is HIGH, charging is disabled. When LOW, charging is controlled by the I <sup>2</sup> C registers. When this pin is HIGH, the 15-minute timer is reset. This pin does not affect the 32-second timer.                         |
| E3     | VREG    | ALL                             | <b>Regulator Output.</b> Connect to a 1 $\mu$ F capacitor to PGND. This pin can supply up to 2 mA of DC load current. For FAN5400-FAN5402, the output voltage is PMID, which is limited to 6.5 V. For FAN5403-FAN5405, the output voltage is regulated to 1.8 V. |
| E4     | VBAT    | ALL                             | <b>Battery Voltage.</b> Connect to the positive (+) terminal of the battery pack. Bypass with a 0.1 $\mu$ F capacitor to PGND if the battery is connected through long leads.                                                                                    |

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol                | Parameter                                                       |                                       | Min. | Max.               | Unit |
|-----------------------|-----------------------------------------------------------------|---------------------------------------|------|--------------------|------|
| V <sub>BUS</sub>      | VBUS Voltage                                                    | Continuous                            | −1.4 | 20.0               | V    |
|                       |                                                                 | Pulsed, 100 ms Maximum Non-Repetitive | −2.0 |                    |      |
| V <sub>STAT</sub>     | STAT Voltage                                                    |                                       | −0.3 | 16.0               | V    |
| V <sub>I</sub>        | PMID Voltage                                                    |                                       |      | 7.0                | V    |
|                       | SW, CSIN, VBAT, AUXPWR, DISABLE Voltage                         |                                       | −0.3 | 7.0                |      |
| V <sub>O</sub>        | Voltage on Other Pins                                           |                                       | −0.3 | 6.5 <sup>(3)</sup> | V    |
| $\frac{dV_{BUS}}{dt}$ | Maximum VBUS Slope above 5.5 V when Boost or Charger are Active |                                       |      | 4                  | V/μs |
| ESD                   | Electrostatic Discharge Protection Level                        | Human Body Model per JESD22-A114      | 2000 |                    | V    |
|                       |                                                                 | Charged Device Model per JESD22-C101  | 500  |                    |      |
| T <sub>J</sub>        | Junction Temperature                                            |                                       | −40  | +150               | °C   |
| T <sub>STG</sub>      | Storage Temperature                                             |                                       | −65  | +150               | °C   |
| T <sub>L</sub>        | Lead Soldering Temperature, 10 Seconds                          |                                       |      | +260               | °C   |

### Note:

3. Lesser of 6.5 V or  $V_I + 0.3$  V.

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol                | Parameter                                                                                                          |                       | Min. | Max. | Units      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------|------|------|------------|
| $V_{BUS}$             | Supply Voltage                                                                                                     |                       | 4    | 6    | V          |
| $V_{BAT(MAX)}$        | Maximum Battery Voltage when Boost enabled                                                                         |                       |      | 4.5  | V          |
| $\frac{dV_{BUS}}{dt}$ | Negative VBUS Slew Rate during VBUS Short Circuit, $C_{MID} \leq 4.7 \mu F$ , see <i>VBUS Short While Charging</i> | $T_A \leq 60^\circ C$ |      | 4    | V/ $\mu$ s |
|                       |                                                                                                                    | $T_A \geq 60^\circ C$ |      | 2    |            |
| $T_A$                 | Ambient Temperature                                                                                                |                       | −30  | +85  | °C         |
| $T_J$                 | Junction Temperature (see <i>Thermal Regulation and Protection</i> section)                                        |                       | −30  | +120 | °C         |

## Thermal Properties

Junction-to-ambient thermal resistance is a function of application and board layout. This data is measured with four-layer 2s2p boards in accordance to JEDEC standard JESD51. Special attention must be paid not to exceed junction temperature  $T_{J(max)}$  at a given ambient temperature  $T_A$ . For measured data, see Table 11.

| Symbol        | Parameter                              | Typical | Units |
|---------------|----------------------------------------|---------|-------|
| $\theta_{JA}$ | Junction-to-Ambient Thermal Resistance | 60      | °C/W  |
| $\theta_{JB}$ | Junction-to-PCB Thermal Resistance     | 20      | °C/W  |

## Electrical Specifications

Unless otherwise specified: according to the circuit of Figure 1; recommended operating temperature range for  $T_J$  and  $T_A$ ;  $V_{BUS}=5.0$  V; HZ\_MODE; OPA\_MODE=0; (Charge Mode); SCL, SDA, OTG=0 or 1.8 V; and typical values are for  $T_J=25^\circ\text{C}$ .

| Symbol                               | Parameter                                         | Conditions                                                                                                                   | Min.           | Typ. | Max.  | Units |    |
|--------------------------------------|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------------|------|-------|-------|----|
| Power Supplies                       |                                                   |                                                                                                                              |                |      |       |       |    |
| I <sub>VBUS</sub>                    | VBUS Current                                      | V <sub>BUS</sub> > V <sub>BUS(min)</sub> , PWM Switching                                                                     |                | 10   |       | mA    |    |
|                                      |                                                   | V <sub>BUS</sub> > V <sub>BUS(min)</sub> ; PWM Enabled, Not Switching (Battery OVP Condition); I <sub>IN</sub> Setting=100mA |                | 2.5  |       | mA    |    |
|                                      |                                                   | 0°C < T <sub>J</sub> < 85°C, HZ_MODE=1<br>V <sub>BAT</sub> < V <sub>LOWV</sub> , 32S Mode                                    |                | 63   | 90    | μA    |    |
| I <sub>LKG</sub>                     | VBAT to VBUS Leakage Current                      | 0°C < T <sub>J</sub> < 85°C, HZ_MODE=1, V <sub>BAT</sub> =4.2 V, V <sub>BUS</sub> =0 V                                       |                | 0.2  | 5.0   | μA    |    |
| I <sub>BAT</sub>                     | Battery Discharge Current in High-Impedance Mode  | 0°C < T <sub>J</sub> < 85°C, HZ_MODE=1, V <sub>BAT</sub> =4.2 V                                                              |                |      | 20    | μA    |    |
|                                      |                                                   | FAN5403-05, DISABLE=1, 0°C < T <sub>J</sub> < 85°C, V <sub>BAT</sub> =4.2 V                                                  |                |      | 10    |       |    |
| Charger Voltage Regulation           |                                                   |                                                                                                                              |                |      |       |       |    |
| V <sub>OREG</sub>                    | Charge Voltage Range                              |                                                                                                                              | 3.5            |      | 4.4   | V     |    |
|                                      | Charge Voltage Accuracy                           | T <sub>A</sub> =25°C                                                                                                         | −0.5%          |      | +0.5% |       |    |
|                                      |                                                   | T <sub>J</sub> =0 to 125°C                                                                                                   | −1%            |      | +1%   |       |    |
| Charging Current Regulation          |                                                   |                                                                                                                              |                |      |       |       |    |
| I <sub>OCHRG</sub>                   | Output Charge Current Range                       | V <sub>LOWV</sub> < V <sub>BAT</sub> < V <sub>OREG</sub><br>V <sub>BUS</sub> > V <sub>SLP</sub> , R <sub>SENSE</sub> =68 mΩ  |                | 550  |       | 1250  | mA |
|                                      | Charge Current Accuracy Across R <sub>SENSE</sub> | 20 mV ≤ V <sub>I<sub>REG</sub></sub> ≤ 40 mV                                                                                 | FAN5400-02     | 95   | 100   | 105   | %  |
|                                      |                                                   |                                                                                                                              | FAN5403-05     | 92   | 97    | 102   |    |
|                                      |                                                   | V <sub>I<sub>REG</sub></sub> > 40 mV                                                                                         | FAN5400-02     | 97   | 100   | 103   |    |
|                                      |                                                   |                                                                                                                              | FAN5403-05     | 94   | 97    | 100   |    |
| Weak Battery Detection               |                                                   |                                                                                                                              |                |      |       |       |    |
| V <sub>LOWV</sub>                    | Weak Battery Threshold Range                      |                                                                                                                              | 3.4            |      | 3.7   | V     |    |
|                                      | Weak Battery Threshold Accuracy                   |                                                                                                                              | −5             |      | +5    | %     |    |
|                                      | Weak Battery Deglitch Time                        | Rising Voltage, 2 mV Overdrive                                                                                               |                | 30   |       | ms    |    |
| Logic Levels: DISABLE, SDA, SCL, OTG |                                                   |                                                                                                                              |                |      |       |       |    |
| V <sub>I<sub>H</sub></sub>           | High-Level Input Voltage                          |                                                                                                                              | 1.05           |      |       | V     |    |
| V <sub>I<sub>L</sub></sub>           | Low-Level Input Voltage                           |                                                                                                                              |                |      | 0.4   | V     |    |
| I <sub>IN</sub>                      | Input Bias Current                                | Input Tied to GND or V <sub>IN</sub>                                                                                         |                | 0.01 | 1.00  | μA    |    |
| Charge Termination Detection         |                                                   |                                                                                                                              |                |      |       |       |    |
| I <sub>(TERM)</sub>                  | Termination Current Range                         | V <sub>BAT</sub> > V <sub>OREG</sub> − V <sub>RCH</sub> , V <sub>BUS</sub> > V <sub>SLP</sub> , R <sub>SENSE</sub> =68 mΩ    |                | 50   |       | 400   | mA |
|                                      | Termination Current Accuracy                      | [V <sub>CSIN</sub> − V <sub>BAT</sub> ] from 3 mV to 20 mV                                                                   |                | −25  |       | +25   | %  |
|                                      |                                                   | [V <sub>CSIN</sub> − V <sub>BAT</sub> ] from 20 mV to 40 mV                                                                  |                | −5   |       | +5    |    |
|                                      |                                                   | Termination Current Deglitch Time                                                                                            | 2 mV Overdrive |      |       | 30    |    |
| 1.8V Linear Regulator                |                                                   |                                                                                                                              |                |      |       |       |    |
| V <sub>REG</sub>                     | 1.8V Regulator Output                             | I <sub>REG</sub> from 0 to 2 mA, FAN5403-05                                                                                  |                | 1.7  | 1.8   | 1.9   | V  |

Continued on the following page...

## Electrical Specifications

Unless otherwise specified: according to the circuit of Figure 1; recommended operating temperature range for  $T_J$  and  $T_A$ ;  $V_{BUS}=5.0$  V;  $HZ\_MODE$ ;  $OPA\_MODE=0$ ; (Charge Mode); SCL, SDA, OTG=0 or 1.8 V; and typical values are for  $T_J=25^\circ\text{C}$ .

| Symbol                                                  | Parameter                                                                     | Conditions                                                                                   | Min. | Typ.  | Max. | Units |
|---------------------------------------------------------|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|------|-------|------|-------|
| Input Power Source Detection                            |                                                                               |                                                                                              |      |       |      |       |
| V <sub>IN(MIN)1</sub>                                   | VBUS Input Voltage Rising                                                     | To Initiate and Pass VBUS Validation                                                         |      | 4.29  | 4.42 | V     |
| V <sub>IN(MIN)2</sub>                                   | Minimum VBUS during Charge                                                    | During Charging                                                                              |      | 3.71  | 3.94 | V     |
| t <sub>VBUS_VALID</sub>                                 | VBUS Validation Time                                                          |                                                                                              |      | 30    |      | ms    |
| Special Charger (V <sub>BUS</sub> ) (FAN5403 – FAN5405) |                                                                               |                                                                                              |      |       |      |       |
| V <sub>SP</sub>                                         | Special Charger Setpoint Accuracy                                             |                                                                                              | –3   |       | +3   | %     |
| Input Current Limit                                     |                                                                               |                                                                                              |      |       |      |       |
| I <sub>INLIM</sub>                                      | Input Current Limit Threshold                                                 | I <sub>IN</sub> Set to 100 mA                                                                | 88   | 93    | 98   | mA    |
|                                                         |                                                                               | I <sub>IN</sub> Set to 500 mA                                                                | 450  | 475   | 500  |       |
| V <sub>REF</sub> Bias Generator                         |                                                                               |                                                                                              |      |       |      |       |
| V <sub>REF</sub>                                        | Bias Regulator Voltage                                                        | V <sub>BUS</sub> > V <sub>IN(MIN)</sub> or V <sub>BAT</sub> > V <sub>BAT(MIN)</sub>          |      |       | 6.5  | V     |
|                                                         | Short-Circuit Current Limit                                                   |                                                                                              |      | 20    |      | mA    |
| Battery Recharge Threshold                              |                                                                               |                                                                                              |      |       |      |       |
| V <sub>RCH</sub>                                        | Recharge Threshold                                                            | Below V <sub>(OREG)</sub>                                                                    | 100  | 120   | 150  | mV    |
|                                                         | Deglintch Time                                                                | V <sub>BAT</sub> Falling Below V <sub>RCH</sub> Threshold                                    |      | 130   |      | ms    |
| STAT Output                                             |                                                                               |                                                                                              |      |       |      |       |
| V <sub>STAT(OL)</sub>                                   | STAT Output Low                                                               | I <sub>STAT</sub> =10 mA                                                                     |      |       | 0.4  | V     |
| I <sub>STAT(OH)</sub>                                   | STAT High Leakage Current                                                     | V <sub>STAT</sub> =5 V                                                                       |      |       | 1    | μA    |
| Battery Detection                                       |                                                                               |                                                                                              |      |       |      |       |
| I <sub>DETECT</sub>                                     | Battery Detection Current before Charge Done (Sink Current) <sup>(4)</sup>    | Begins after Termination Detected and V <sub>BAT</sub> ≤ V <sub>OREG</sub> –V <sub>RCH</sub> |      | –0.80 |      | mA    |
| t <sub>DETECT</sub>                                     | Battery Detection Time                                                        |                                                                                              |      | 262   |      | ms    |
| Sleep Comparator                                        |                                                                               |                                                                                              |      |       |      |       |
| V <sub>SLP</sub>                                        | Sleep-Mode Entry Threshold, V <sub>BUS</sub> – V <sub>BAT</sub>               | 2.3 V ≤ V <sub>BAT</sub> ≤ V <sub>OREG</sub> , V <sub>BUS</sub> Falling                      | 0    | 0.04  | 0.10 | V     |
| V <sub>SLP_EXIT</sub>                                   | Deglintch Time for VBUS Rising Above V <sub>SLP</sub> + V <sub>SLP_EXIT</sub> | Rising Voltage                                                                               |      | 30    |      | ms    |
| Power Switches (see Figure 3)                           |                                                                               |                                                                                              |      |       |      |       |
| R <sub>DS(ON)</sub>                                     | Q3 On Resistance (VBUS to PMID)                                               | I <sub>IN(LIMIT)</sub> =500 mA                                                               |      | 180   | 250  | mΩ    |
|                                                         | Q1 On Resistance (PMID to SW)                                                 |                                                                                              |      | 130   | 225  |       |
|                                                         | Q2 On Resistance (SW to GND)                                                  |                                                                                              |      | 150   | 225  |       |
| Charger PWM Modulator                                   |                                                                               |                                                                                              |      |       |      |       |
| f <sub>SW</sub>                                         | Oscillator Frequency                                                          |                                                                                              | 2.7  | 3.0   | 3.3  | MHz   |
| D <sub>MAX</sub>                                        | Maximum Duty Cycle                                                            |                                                                                              |      |       | 100  | %     |
| D <sub>MIN</sub>                                        | Minimum Duty Cycle                                                            |                                                                                              |      | 0     |      | %     |
| I <sub>SYNC</sub>                                       | Synchronous to Non-Synchronous Current Cut-Off Threshold <sup>(5)</sup>       | Low-Side MOSFET (Q2) Cycle-by-Cycle Current Limit                                            |      | 140   |      | mA    |

Continued on the following page...

## Electrical Specifications

Unless otherwise specified: according to the circuit of Figure 1; recommended operating temperature range for  $T_J$  and  $T_A$ ;  $V_{BUS}=5.0\text{ V}$ ;  $HZ\_MODE$ ;  $OPA\_MODE=0$ ; (Charge Mode); SCL, SDA, OTG=0 or 1.8 V; and typical values are for  $T_J=25^\circ\text{C}$ .

| Symbol                                       | Parameter                                   | Conditions                                                           | Min. | Typ. | Max. | Units |
|----------------------------------------------|---------------------------------------------|----------------------------------------------------------------------|------|------|------|-------|
| Boost Mode Operation (OPA_MODE=1, HZ_MODE=0) |                                             |                                                                      |      |      |      |       |
| V <sub>BOOST</sub>                           | Boost Output Voltage at VBUS                | 2.5 V < V <sub>BAT</sub> < 4.5 V, I <sub>LOAD</sub> from 0 to 200 mA | 4.80 | 5.07 | 5.17 | V     |
|                                              |                                             | 2.7 V < V <sub>BAT</sub> < 4.5 V, I <sub>LOAD</sub> from 0 to 200 mA | 4.85 | 5.07 | 5.17 |       |
| I <sub>BAT(BOOST)</sub>                      | Boost Mode Quiescent Current                | PFM Mode, V <sub>BAT</sub> =3.6 V, I <sub>OUT</sub> =0               |      | 140  | 300  | μA    |
| I <sub>LIMPK(BST)</sub>                      | Q2 Peak Current Limit                       |                                                                      | 1100 | 1380 | 1660 | mA    |
| UVLO <sub>BST</sub>                          | Minimum Battery Voltage for Boost Operation | While Boost Active                                                   |      | 2.42 |      | V     |
|                                              |                                             | To Start Boost Regulator                                             |      | 2.58 | 2.70 |       |
| VBUS Load Resistance                         |                                             |                                                                      |      |      |      |       |
| R <sub>VBUS</sub>                            | VBUS to PGND Resistance                     | Normal Operation                                                     |      | 1500 |      | KΩ    |
|                                              |                                             | Charger Validation                                                   |      | 100  |      | Ω     |
| Protection and Timers                        |                                             |                                                                      |      |      |      |       |
| VBUS <sub>OV</sub> P                         | VBUS Over-Voltage Shutdown                  | V <sub>BUS</sub> Rising                                              | 6.09 | 6.29 | 6.49 | V     |
|                                              | Hysteresis                                  | V <sub>BUS</sub> Falling                                             |      | 100  |      | mV    |
| I <sub>LIMPK(CHG)</sub>                      | Q1 Cycle-by-Cycle Peak Current Limit        | Charge Mode                                                          |      | 2.3  |      | A     |
| V <sub>SHORT</sub>                           | Battery Short-Circuit Threshold             | V <sub>BAT</sub> Rising                                              | 1.95 | 2.00 | 2.05 | V     |
|                                              | Hysteresis                                  | V <sub>BAT</sub> Falling                                             |      | 100  |      |       |
| I <sub>SHORT</sub>                           | Linear Charging Current                     | V <sub>BAT</sub> < V <sub>SHORT</sub>                                | 20   | 30   | 40   | mA    |
| T <sub>SHUTDWN</sub>                         | Thermal Shutdown Threshold <sup>(6)</sup>   | T <sub>J</sub> Rising                                                |      | 145  |      | °C    |
|                                              | Hysteresis <sup>(6)</sup>                   | T <sub>J</sub> Falling                                               |      | 10   |      |       |
| T <sub>CF</sub>                              | Thermal Regulation Threshold <sup>(6)</sup> | Charge Current Reduction Begins                                      |      | 120  |      | °C    |
| t <sub>INT</sub>                             | Detection Interval                          |                                                                      |      | 2.1  |      | s     |
| t <sub>32S</sub>                             | 32-Second Timer <sup>(7)</sup>              | Charger Enabled                                                      | 20.5 | 25.2 | 28.0 | s     |
|                                              |                                             | Charger Disabled                                                     | 18.0 | 25.2 | 34.0 |       |
| t <sub>15MIN</sub>                           | 15-Minute Timer                             | 15-Minute Mode (FAN5400, FAN5402, FAN5404, FAN5405)                  | 12.0 | 13.5 | 15.0 | min   |
| Δt <sub>LF</sub>                             | Low-Frequency Timer Accuracy                | Charger Inactive                                                     | −25  |      | 25   | %     |

### Notes:

- Negative current is current flowing from the battery to  $V_{BUS}$  (discharging the battery).
- Q2 always turns on for 60 ns, then turns off if current is below  $I_{SYNC}$ .
- Guaranteed by design; not tested in production.
- This tolerance (%) applies to all timers on the IC, including soft-start and deglitching timers.

## I<sup>2</sup>C Timing Specifications

Guaranteed by design.

| Symbol                                | Parameter                                                                            | Conditions                               | Min.                 | Typ. | Max. | Units |
|---------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------|----------------------|------|------|-------|
| f <sub>SCL</sub>                      | SCL Clock Frequency                                                                  | Standard Mode                            |                      |      | 100  | kHz   |
|                                       |                                                                                      | Fast Mode                                |                      |      | 400  |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      |      | 3400 |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      |      | 1700 |       |
| t <sub>BUF</sub>                      | Bus-Free Time between STOP and START Conditions                                      | Standard Mode                            |                      | 4.7  |      | μs    |
|                                       |                                                                                      | Fast Mode                                |                      | 1.3  |      |       |
| t <sub>HD;STA</sub>                   | START or Repeated START Hold Time                                                    | Standard Mode                            |                      | 4    |      | μs    |
|                                       |                                                                                      | Fast Mode                                |                      | 600  |      | ns    |
|                                       |                                                                                      | High-Speed Mode                          |                      | 160  |      | ns    |
| t <sub>LOW</sub>                      | SCL LOW Period                                                                       | Standard Mode                            |                      | 4.7  |      | μs    |
|                                       |                                                                                      | Fast Mode                                |                      | 1.3  |      | μs    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      | 160  |      | ns    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      | 320  |      | ns    |
| t <sub>HIGH</sub>                     | SCL HIGH Period                                                                      | Standard Mode                            |                      | 4    |      | μs    |
|                                       |                                                                                      | Fast Mode                                |                      | 600  |      | ns    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      | 60   |      | ns    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      | 120  |      | ns    |
| t <sub>SU;STA</sub>                   | Repeated START Setup Time                                                            | Standard Mode                            |                      | 4.7  |      | μs    |
|                                       |                                                                                      | Fast Mode                                |                      | 600  |      | ns    |
|                                       |                                                                                      | High-Speed Mode                          |                      | 160  |      | ns    |
| t <sub>SU;DAT</sub>                   | Data Setup Time                                                                      | Standard Mode                            |                      | 250  |      | ns    |
|                                       |                                                                                      | Fast Mode                                |                      | 100  |      |       |
|                                       |                                                                                      | High-Speed Mode                          |                      | 10   |      |       |
| t <sub>HD;DAT</sub>                   | Data Hold Time                                                                       | Standard Mode                            | 0                    |      | 3.45 | μs    |
|                                       |                                                                                      | Fast Mode                                | 0                    |      | 900  | ns    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF | 0                    |      | 70   | ns    |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF | 0                    |      | 150  | ns    |
| t <sub>RCL</sub>                      | SCL Rise Time                                                                        | Standard Mode                            | 20+0.1C <sub>B</sub> |      | 1000 | ns    |
|                                       |                                                                                      | Fast Mode                                | 20+0.1C <sub>B</sub> |      | 300  |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      | 10   | 80   |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      | 20   | 160  |       |
| t <sub>FCL</sub>                      | SCL Fall Time                                                                        | Standard Mode                            | 20+0.1C <sub>B</sub> |      | 300  | ns    |
|                                       |                                                                                      | Fast Mode                                | 20+0.1C <sub>B</sub> |      | 300  |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      | 10   | 40   |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      | 20   | 80   |       |
| t <sub>RDA</sub><br>t <sub>RCL1</sub> | SDA Rise Time<br>Rise Time of SCL after a Repeated START Condition and after ACK Bit | Standard Mode                            | 20+0.1C <sub>B</sub> |      | 1000 | ns    |
|                                       |                                                                                      | Fast Mode                                | 20+0.1C <sub>B</sub> |      | 300  |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 100 pF |                      | 10   | 80   |       |
|                                       |                                                                                      | High-Speed Mode, C <sub>B</sub> ≤ 400 pF |                      | 20   | 160  |       |

Continued on the following page...

## I<sup>2</sup>C Timing Specifications

Guaranteed by design.

| Symbol       | Parameter                    | Conditions                         | Min. | Typ.        | Max. | Units   |
|--------------|------------------------------|------------------------------------|------|-------------|------|---------|
| $t_{FDA}$    | SDA Fall Time                | Standard Mode                      |      | $20+0.1C_B$ | 300  | ns      |
|              |                              | Fast Mode                          |      | $20+0.1C_B$ | 300  |         |
|              |                              | High-Speed Mode, $C_B \leq 100$ pF |      | 10          | 80   |         |
|              |                              | High-Speed Mode, $C_B \leq 400$ pF |      | 20          | 160  |         |
| $t_{SU;STO}$ | Stop Condition Setup Time    | Standard Mode                      |      | 4           |      | $\mu$ s |
|              |                              | Fast Mode                          |      | 600         |      | ns      |
|              |                              | High-Speed Mode                    |      | 160         |      | ns      |
| $C_B$        | Capacitive Load for SDA, SCL |                                    |      |             | 400  | pF      |

## Timing Diagrams





Figure 5. I<sup>2</sup>C Interface Timing for Fast and Slow Modes



Note A: First rising edge of SCLH after Repeated Start and after each ACK bit.

Figure 6. I<sup>2</sup>C Interface Timing for High-Speed Mode

## Charge Mode Typical Characteristics

Unless otherwise specified, circuit of Figure 1,  $V_{OREG}=4.2\text{ V}$ ,  $V_{BUS}=5.0\text{ V}$ , and  $T_A=25^\circ\text{C}$ .




Figure 7. Battery Charge Current vs.  $V_{BUS}$  with  $I_{INLIM}=100\text{ mA}$




Figure 9. Charger Efficiency, No  $I_{INLIM}$ ,  $I_{CHARGE}=1,250\text{ mA}$




Figure 8. Battery Charge Current vs.  $V_{BUS}$  with  $I_{INLIM}=500\text{ mA}$




Figure 10. Charger Efficiency vs.  $V_{BUS}$ ,  $I_{INLIM}=500\text{ mA}$




Figure 11. Auto-Charge Startup at  $V_{BUS}$  Plug-in,  $I_{INLIM}=100\text{ mA}$ ,  $OTG=1$ ,  $V_{BAT}=3.4\text{ V}$




Figure 12. Auto-Charge Startup at  $V_{BUS}$  Plug-in,  $I_{INLIM}=500\text{ mA}$ ,  $OTG=1$ ,  $V_{BAT}=3.4\text{ V}$

## Charge Mode Typical Characteristics

Unless otherwise specified, circuit of Figure 1,  $V_{OREG}=4.2\text{ V}$ ,  $V_{BUS}=5.0\text{ V}$ , and  $T_A=25^\circ\text{C}$ .




Figure 13. AutoCharge Startup with 300mA Limited Charger / Adaptor,  $I_{INLIM}=500\text{ mA}$ ,  $OTG=1$ ,  $V_{BAT}=3.4\text{ V}$




Figure 14. Charger Startup with HZ\_MODE Bit Reset,  $I_{INLIM}=500\text{ mA}$ ,  $I_{OCHARGE}=950\text{ mA}$ ,  $OREG=4.2\text{ V}$ ,  $V_{BAT}=3.6\text{ V}$




Figure 15. Battery Removal / Insertion during Charging,  $V_{BAT}=3.9\text{ V}$ ,  $I_{OCHARGE}=950\text{ mA}$ , No  $I_{INLIM}$ ,  $TE=0$




Figure 16. Battery Removal / Insertion during Charging,  $V_{BAT}=3.9\text{ V}$ ,  $I_{OCHARGE}=950\text{ mA}$ , No  $I_{INLIM}$ ,  $TE=1$

## Charge Mode Typical Characteristics

Unless otherwise specified, circuit of Figure 1,  $V_{\text{OREG}}=4.2\text{ V}$ ,  $V_{\text{BUS}}=5.0\text{ V}$ , and  $T_A=25^\circ\text{C}$ .





Figure 17. No Battery at  $V_{\text{BUS}}$  Power-up; FAN5400, FAN5403 Figure 18. No Battery at  $V_{\text{BUS}}$  Power-up; FAN5402, FAN5405




Figure 19.  $V_{\text{BUS}}$  Current in High-Impedance Mode with Battery Open




Figure 20.  $V_{\text{REG}}$  1.8V Output Regulation

## Boost Mode Typical Characteristics

Unless otherwise specified, using circuit of Figure 1,  $V_{BAT}=3.6\text{ V}$ ,  $T_A=25^\circ\text{C}$ .




Figure 21. Efficiency vs.  $V_{BAT}$




Figure 22. Efficiency Over Temperature




Figure 23. Output Regulation vs.  $V_{BAT}$




Figure 24. Output Regulation Over Temperature




Figure 25. Quiescent Current




Figure 26. High-Impedance Mode Battery Current

## Boost Mode Typical Characteristics

Unless otherwise specified, using circuit of Figure 1,  $V_{BAT}=3.6\text{ V}$ ,  $T_A=25^\circ\text{C}$ .




Figure 27. Boost PWM Waveform




Figure 28. Boost PFM Waveform




Figure 29. Output Ripple vs.  $V_{BAT}$




Figure 30. Output Ripple vs. Temperature

## Boost Mode Typical Characteristics

Unless otherwise specified, using circuit of Figure 1,  $V_{BAT}=3.6\text{ V}$ ,  $T_A=25^\circ\text{C}$ .




Figure 31. Startup,  $3.6\text{ V}_{BAT}$ ,  $44\ \Omega$  Load, Additional  $10\ \mu\text{F}$ , X5R Across  $V_{BUS}$




Figure 32.  $V_{BUS}$  Fault Response,  $3.6\text{ V}_{BAT}$




Figure 33. Load Transient,  $5\text{-}155\text{-}5\text{ mA}$ ,  $t_R=t_F=100\text{ ns}$




Figure 34. Load Transient,  $5\text{-}255\text{-}5\text{ mA}$ ,  $t_R=t_F=100\text{ ns}$

## Circuit Description / Overview

When charging batteries with a current-limited input source, such as USB, a switching charger's high efficiency over a wide range of output voltages minimizes charging time.

FAN540X combines a highly integrated synchronous buck regulator for charging with a synchronous boost regulator, which can supply 5 V to USB On-The-Go (OTG) peripherals. The regulator employs synchronous rectification for both the charger and boost regulators to maintain high efficiency over a wide range of battery voltages and charge states.

The FAN540X has three operating modes:

1. **Charge Mode:**  
Charges a single-cell Li-ion or Li-polymer battery.
2. **Boost Mode:**  
Provides 5 V power to USB-OTG with an integrated synchronous rectification boost regulator using the battery as input.
3. **High-Impedance Mode:**  
Both the boost and charging circuits are OFF in this mode. Current flow from VBUS to the battery or from the battery to VBUS is blocked in this mode. This mode consumes very little current from VBUS or the battery.

Note: Default settings are denoted by **bold typeface**.

### Charge Mode

In Charge Mode, FAN540X employs four regulation loops:

1. **Input Current:** Limits the amount of current drawn from VBUS. This current is sensed internally and can be programmed through the I<sup>2</sup>C interface.
2. **Charging Current:** Limits the maximum charging current. This current is sensed using an external R<sub>SENSE</sub> resistor.
3. **Charge Voltage:** The regulator is restricted from exceeding this voltage. As the internal battery voltage rises, the battery's internal impedance and R<sub>SENSE</sub> work in conjunction with the charge voltage regulation to decrease the amount of current flowing to the battery. Battery charging is completed when the voltage across R<sub>SENSE</sub> drops below the I<sub>TERM</sub> threshold.
4. **Temperature:** If the IC's junction temperature reaches 120°C, charge current is continuously reduced until the IC's temperature stabilizes at 120°C.

In addition, the FAN5403-05 employ an additional loop to limit the amount of drop on VBUS to a programmable voltage (V<sub>SP</sub>) to accommodate "special chargers" that limit current to a lower current than might be available from a "normal" USB wall charger.

### Battery Charging Curve

If the battery voltage is below V<sub>SHORT</sub>, a linear current source pre-charges the battery until V<sub>BAT</sub> reaches V<sub>SHORT</sub>. The PWM charging circuit is then started and the battery is charged

with a constant current if sufficient input power is available. The current slew rate is limited to prevent overshoot.

The FAN540X is designed to work with a current-limited input source at VBUS. During the current regulation phase of charging, I<sub>INLIM</sub> or the programmed charging current limits the amount of current available to charge the battery and power the system. The effect of I<sub>INLIM</sub> on I<sub>CHARGE</sub> can be seen in Figure 36.




Figure 35. Charge Curve, I<sub>CHARGE</sub> Not Limited by I<sub>INLIM</sub>




Figure 36. Charge Curve, I<sub>INLIM</sub> Limits I<sub>CHARGE</sub>

Assuming that V<sub>OREG</sub> is programmed to the cell's fully charged "float" voltage, the current that the battery accepts with the PWM regulator limiting its output (sensed at V<sub>BAT</sub>) to V<sub>OREG</sub> declines, and the charger enters the voltage regulation phase of charging. When the current declines to the programmed I<sub>TERM</sub> value, the charge cycle is complete. Charge current termination can be disabled by resetting the TE bit (REG1[3]).

The charger output or "float" voltage can be programmed by the OREG bits from 3.5 V to 4.44 V in 20 mV increments, as shown in Table 3.

**Table 3. OREG Bits (OREG[7:2]) vs. Charger  $V_{OUT}$  ( $V_{OREG}$ ) Float Voltage**

| Decimal | Hex | VOREG | Decimal | Hex | VOREG |
|---------|-----|-------|---------|-----|-------|
| 0       | 00  | 3.50  | 32      | 20  | 4.14  |
| 1       | 01  | 3.52  | 33      | 21  | 4.16  |
| 2       | 02  | 3.54  | 34      | 22  | 4.18  |
| 3       | 03  | 3.56  | 35      | 23  | 4.20  |
| 4       | 04  | 3.58  | 36      | 24  | 4.22  |
| 5       | 05  | 3.60  | 37      | 25  | 4.24  |
| 6       | 06  | 3.62  | 38      | 26  | 4.26  |
| 7       | 07  | 3.64  | 39      | 27  | 4.28  |
| 8       | 08  | 3.66  | 40      | 28  | 4.30  |
| 9       | 09  | 3.68  | 41      | 29  | 4.32  |
| 10      | 0A  | 3.70  | 42      | 2A  | 4.34  |
| 11      | 0B  | 3.72  | 43      | 2B  | 4.36  |
| 12      | 0C  | 3.74  | 44      | 2C  | 4.38  |
| 13      | 0D  | 3.76  | 45      | 2D  | 4.40  |
| 14      | 0E  | 3.78  | 46      | 2E  | 4.42  |
| 15      | 0F  | 3.80  | 47      | 2F  | 4.44  |
| 16      | 10  | 3.82  | 48      | 30  | 4.44  |
| 17      | 11  | 3.84  | 49      | 31  | 4.44  |
| 18      | 12  | 3.86  | 50      | 32  | 4.44  |
| 19      | 13  | 3.88  | 51      | 33  | 4.44  |
| 20      | 14  | 3.90  | 52      | 34  | 4.44  |
| 21      | 15  | 3.92  | 53      | 35  | 4.44  |
| 22      | 16  | 3.94  | 54      | 36  | 4.44  |
| 23      | 17  | 3.96  | 55      | 37  | 4.44  |
| 24      | 18  | 3.98  | 56      | 38  | 4.44  |
| 25      | 19  | 4.00  | 57      | 39  | 4.44  |
| 26      | 1A  | 4.02  | 58      | 3A  | 4.44  |
| 27      | 1B  | 4.04  | 59      | 3B  | 4.44  |
| 28      | 1C  | 4.06  | 60      | 3C  | 4.44  |
| 29      | 1D  | 4.08  | 61      | 3D  | 4.44  |
| 30      | 1E  | 4.10  | 62      | 3E  | 4.44  |

The following charging parameters can be programmed by the host through I<sup>2</sup>C:

**Table 4. Programmable Charging Parameters**

| Parameter                      | Name        | Register  |
|--------------------------------|-------------|-----------|
| Output Voltage Regulation      | $V_{OREG}$  | REG2[7:2] |
| Battery Charging Current Limit | $I_{OCHRG}$ | REG4[6:4] |
| Input Current Limit            | $I_{INLIM}$ | REG1[7:6] |
| Charge Termination Limit       | $I_{TERM}$  | REG4[2:0] |
| Weak Battery Voltage           | $V_{LOWV}$  | REG1[5:4] |

A new charge cycle begins when one of the following occurs:

- The battery voltage falls below  $V_{OREG} - V_{RCH}$
- VBUS Power On Reset (POR) clears and the battery voltage is below the weak battery threshold ( $V_{LOWV}$ ). **This occurs for all versions except the FAN5401.**
- $\overline{CE}$  or HZ\_MODE is reset through I<sup>2</sup>C write to CONTROL1 (R1) register.

### Charge Current Limit ( $I_{OCHARGE}$ )

**Table 5.  $I_{OCHARGE}$  (REG4 [6:4]) Current as Function of  $I_{OCHARGE}$  Bits and  $R_{SENSE}$  Resistor Values**

| DEC | BIN | HEX | $V_{RSENSE}$ (mV) | $I_{OCHARGE}$ (mA) |                |
|-----|-----|-----|-------------------|--------------------|----------------|
|     |     |     |                   | 68 m $\Omega$      | 100 m $\Omega$ |
| 0   | 000 | 00  | 37.4              | 550                | 374            |
| 1   | 001 | 01  | 44.2              | 650                | 442            |
| 2   | 010 | 02  | 51.0              | 750                | 510            |
| 3   | 011 | 03  | 57.8              | 850                | 578            |
| 4   | 100 | 04  | 64.6              | 950                | 646            |
| 5   | 101 | 05  | 71.4              | 1050               | 714            |
| 6   | 110 | 06  | 78.2              | 1150               | 782            |
| 7   | 111 | 07  | 85.0              | 1250               | 850            |

### Termination Current Limit

Current charge termination is enabled when TE (REG1[3])=1. Typical termination current values are given in Table 6.

**Table 6.  $I_{TERM}$  Current as Function of  $I_{TERM}$  Bits (REG4[2:0]) and  $R_{SENSE}$  Resistor Values**

| $I_{TERM}$ | FAN5400 - FAN5402 |                 |                |                   | FAN5403 - FAN5405 |                |
|------------|-------------------|-----------------|----------------|-------------------|-------------------|----------------|
|            | $V_{RSENSE}$ (mV) | $I_{TERM}$ (mA) |                | $V_{RSENSE}$ (mV) | $I_{TERM}$ (mA)   |                |
|            |                   | 68 m $\Omega$   | 100 m $\Omega$ |                   | 68 m $\Omega$     | 100 m $\Omega$ |
| 0          | 3.4               | 50              | 34             | 3.3               | 49                | 33             |
| 1          | 6.8               | 100             | 68             | 6.6               | 97                | 66             |
| 2          | 10.2              | 150             | 102            | 9.9               | 146               | 99             |
| 3          | 13.6              | 200             | 136            | 13.2              | 194               | 132            |
| 4          | 17.0              | 250             | 170            | 16.5              | 243               | 165            |
| 5          | 20.4              | 300             | 204            | 19.8              | 291               | 198            |
| 6          | 23.8              | 350             | 238            | 23.1              | 340               | 231            |
| 7          | 27.2              | 400             | 272            | 26.4              | 388               | 264            |

When the charge current falls below  $I_{TERM}$  for a period of 32 ms; PWM charging stops and the STAT bits change to READY (00) for about 500 ms while the IC determines whether the battery and charging source are still connected. The STAT bits then change to CHARGE DONE (10), provided the battery and charger are still connected.

## PWM Controller in Charge Mode

The IC uses a current-mode PWM controller to regulate the output voltage and battery charge currents. The synchronous rectifier (Q2) has a negative current limit that turns off Q2 at 140mA to prevent current flow from the battery.

## Safety Timer

This section references Figure 41 and Figure 42.

At the beginning of charging, the IC starts a 15-minute timer ( $t_{15MIN}$ ). When this timer times out, charging is terminated. Writing to any register through I<sup>2</sup>C stops and resets the  $t_{15MIN}$  timer, which in turn starts a 32-second timer ( $t_{32S}$ ). Setting the TMR\_RST bit (REG0[7]) resets the  $t_{32S}$  timer. If the  $t_{32S}$  timer times out, charging is terminated, the registers are set to their default values, and charging resumes using the default values with the  $t_{15MIN}$  timer running.

Normal charging is controlled by the host with the  $t_{32S}$  timer running to ensure that the host is alive. Charging with the  $t_{15MIN}$  timer running is used for charging that is unattended by the host. If the  $t_{15MIN}$  timer expires, the IC turns off the charger, sets the  $\overline{CE}$  bit, and indicates a timer fault (110) on the FAULT bits (REG0[2:0]). This sequence prevents overcharge if the host fails to reset the  $t_{32S}$  timer.

## V<sub>BUS</sub> POR / Non-Compliant Charger Rejection

When the IC detects that V<sub>BUS</sub> has risen above V<sub>IN(MIN)1</sub> (4.4 V), the IC applies a 110Ω load from V<sub>BUS</sub> to GND. To clear the V<sub>BUS</sub> POR (Power-On-Reset) and begin charging, V<sub>BUS</sub> must remain above V<sub>IN(MIN)1</sub> and below V<sub>BUS\_OVP</sub> for  $t_{VBUS\_VALID}$  (30 ms) before the IC initiates charging. The V<sub>BUS</sub> validation sequence always occurs before charging is initiated or re-initiated (for example, after a V<sub>BUS</sub> OVP fault or a V<sub>RCH</sub> recharge initiation).

$t_{VBUS\_VALID}$  ensures that unfiltered 50 / 60 Hz chargers and other non-compliant chargers are rejected.

## USB-Friendly Boot Sequence

For all versions except FAN5401, FAN5404

At V<sub>BUS</sub> POR, when the battery voltage is above the weak battery threshold (V<sub>LOWV</sub>), the IC operates in accordance with its I<sup>2</sup>C register settings. If V<sub>BAT</sub> < V<sub>LOWV</sub>, the IC sets all registers to their default values and enables the charger using an input current limit controlled by the OTG pin (100 mA if OTG is LOW and 500 mA if OTG is HIGH). This feature can revive a battery whose voltage is too low to ensure reliable host operation. Charging continues in the absence of host communication even after the battery has reached V<sub>OREG</sub>, whose default value is 3.54 V, and the charger remains active until  $t_{15MIN}$  times out. Once the host processor begins writing to the IC, charging parameters are set by the host, which must continually reset the  $t_{32S}$  timer to continue charging using the programmed charging parameters. If  $t_{32S}$  times out, the register defaults are loaded, the FAULT bits are set to 110, STAT is pulsed HIGH, and charging continues with default charge parameters.

The FAN5401 and FAN5404 do not automatically initiate charging at V<sub>BUS</sub> POR. Instead, they wait for the host to initiate charging through I<sup>2</sup>C commands.

## Input Current Limiting

To minimize charging time without overloading V<sub>BUS</sub> current limitations, the IC's input current limit can be programmed by the I<sub>INLIM</sub> bits (REG1[7:6]).

Table 7. Input Current Limit

| I <sub>INLIM</sub> REG1[7:6] | Input Current Limit |
|------------------------------|---------------------|
| 00                           | 100 mA              |
| 01                           | 500 mA              |
| 10                           | 800 mA              |
| 11                           | No limit            |

For all versions except the FAN5401 and FAN5404, the OTG pin establishes the input current limit when  $t_{15MIN}$  is running. For the FAN5401 and FAN5404, no charging occurs automatically at V<sub>BUS</sub> POR, so the input current limit is established by the I<sub>INLIM</sub> bits.

## Flow Charts




Figure 37. Charger VBUS POR




Figure 38. Charge Mode




Figure 39. Charge Configuration




Figure 40. HZ-State




Figure 41. Timer Flow Chart for FAN5400, FAN5402, FAN5403, FAN5405




Figure 42. Timer Flow Chart for FAN5401, FAN5404

## Special Charger

### FAN5403-05 Only

The FAN5403, FAN5404, and FAN5405 have additional functionality to limit input current in case a current-limited “special charger” is supplying V<sub>BUS</sub>. The FAN5403-05 slowly increases the charging current until either:

- I<sub>INLIM</sub> or I<sub>oCHARGE</sub> is reached

or

- V<sub>BUS</sub>=V<sub>SP</sub>.

If V<sub>BUS</sub> collapses to V<sub>SP</sub> when the current is ramping up, the FAN5403-05 charge with an input current that keeps V<sub>BUS</sub>=V<sub>SP</sub>. When the V<sub>SP</sub> control loop is limiting the charge current, the SP bit (REG5[4]) is set.

**Table 8. V<sub>SP</sub> as Function of SP Bits (REG5[2:0])**

| SP (REG5[2:0]) |     |     |                 |
|----------------|-----|-----|-----------------|
| DEC            | BIN | HEX | V <sub>SP</sub> |
| 0              | 000 | 00  | 4.213           |
| 1              | 001 | 01  | 4.293           |
| 2              | 010 | 02  | 4.373           |
| 3              | 011 | 03  | 4.453           |
| 4              | 100 | 04  | 4.533           |
| 5              | 101 | 05  | 4.613           |
| 6              | 110 | 06  | 4.693           |
| 7              | 111 | 07  | 4.773           |

## Safety Settings

### FAN5403-FAN5405 Only

The FAN5403-05 contain a SAFETY register (REG6) that prevents the values in OREG (REG2[7:2]) and IOCHARGE (REG4[6:4]) from exceeding the values of the VSAFE and ISAFE values.

After V<sub>BAT</sub> exceeds V<sub>SHORT</sub>, the SAFETY register is loaded with its default value and may be written only before any other register is written. After writing to any other register, the SAFETY register is locked until V<sub>BAT</sub> falls below V<sub>SHORT</sub>.

The ISAFE (REG6[6:4]) and VSAFE (REG6[3:0]) registers establish values that limit the maximum values of I<sub>oCHARGE</sub> and V<sub>OREG</sub> used by the control logic. If the host attempts to write a value higher than VSAFE or ISAFE to OREG or IOCHARGE, respectively; the VSAFE, ISAFE value appears as the OREG, IOCHARGE register value, respectively.

**Table 9. I<sub>SAFE</sub> (I<sub>oCHARGE</sub> Limit) as Function of ISAFE Bits (REG6[6:4])**

| ISAFE (REG6[6:4]) |     |     | V <sub>RSENSE</sub> (mV) | I <sub>SAFE</sub> (mA) |        |
|-------------------|-----|-----|--------------------------|------------------------|--------|
| DEC               | BIN | HEX |                          | 68 mΩ                  | 100 mΩ |
| 0                 | 000 | 00  | 37.4                     | 550                    | 374    |
| 1                 | 001 | 01  | 44.2                     | 650                    | 442    |
| 2                 | 010 | 02  | 51.0                     | 750                    | 510    |
| 3                 | 011 | 03  | 57.8                     | 850                    | 578    |
| 4                 | 100 | 04  | 64.6                     | 950                    | 646    |
| 5                 | 101 | 05  | 71.4                     | 1050                   | 714    |
| 6                 | 110 | 06  | 78.2                     | 1150                   | 782    |
| 7                 | 111 | 07  | 85.0                     | 1250                   | 850    |

**Table 10. V<sub>SAFE</sub> (V<sub>OREG</sub> Limit) as Function of VSAFE Bits (REG6[3:0])**

| VSAFE (REG6[3:0]) |      |     | Max. OREG (REG2[7:2]) | VOREG Max. |
|-------------------|------|-----|-----------------------|------------|
| DEC               | BIN  | HEX |                       |            |
| 0                 | 0000 | 00  | 100011                | 4.20       |
| 1                 | 0001 | 01  | 100100                | 4.22       |
| 2                 | 0010 | 02  | 100101                | 4.24       |
| 3                 | 0011 | 03  | 100110                | 4.26       |
| 4                 | 0100 | 04  | 100111                | 4.28       |
| 5                 | 0101 | 05  | 101000                | 4.30       |
| 6                 | 0110 | 06  | 101001                | 4.32       |
| 7                 | 0111 | 07  | 101010                | 4.34       |
| 8                 | 1000 | 08  | 101011                | 4.36       |
| 9                 | 1001 | 09  | 101100                | 4.38       |
| 10                | 1010 | 0A  | 101101                | 4.40       |
| 11                | 1011 | 0B  | 101110                | 4.42       |
| 12                | 1100 | 0C  | 101111                | 4.44       |
| 13                | 1101 | 0D  | 110000                | 4.44       |
| 14                | 1110 | 0E  | 110001                | 4.44       |
| 15                | 1111 | 0F  | 110010                | 4.44       |

## Thermal Regulation and Protection

When the IC's junction temperature reaches T<sub>CF</sub> (about 120°C), the charger reduces its output current to 550mA to prevent overheating. If the temperature increases beyond T<sub>SHUTDOWN</sub>, charging is suspended, the FAULT bits are set to 101, and STAT is pulsed HIGH. In Suspend Mode, all timers stop and the state of the IC's logic is preserved. Charging resumes at programmed current after the die cools to about 120°C.

Additional  $\theta_{JA}$  data points, measured using the FAN540X evaluation board, are given in Table 11 (measured with  $T_A=25^\circ\text{C}$ ). Note that as power dissipation increases, the effective  $\theta_{JA}$  decreases due to the larger difference between the die temperature and its ambient.

**Table 11. FAN5400 Evaluation Board Measured  $\theta_{JA}$**

| Power (W) | $\theta_{JA}$                 |
|-----------|-------------------------------|
| 0.504     | $54^\circ\text{C} / \text{W}$ |
| 0.844     | $50^\circ\text{C} / \text{W}$ |
| 1.506     | $46^\circ\text{C} / \text{W}$ |

## Charge Mode Input Supply Protection

### Sleep Mode

When  $V_{BUS}$  falls below  $V_{BAT} + V_{SLP}$ , and  $V_{BUS}$  is above  $V_{IN(MIN)}$ , the IC enters Sleep Mode to prevent the battery from draining into  $V_{BUS}$ . During Sleep Mode, reverse current is disabled by body switching Q1.

### Input Supply Low-Voltage Detection

The IC continuously monitors  $V_{BUS}$  during charging. If  $V_{BUS}$  falls below  $V_{IN(MIN)}$ , the IC:

1. Terminates charging
2. Pulses the STAT pin, sets the STAT bits to 11, and sets the FAULT bits to 011.

If  $V_{BUS}$  recovers above the  $V_{IN(MIN)}$  rising threshold after time  $t_{INT}$  (about two seconds), the charging process is repeated. This function prevents the USB power bus from collapsing or oscillating when the IC is connected to a suspended USB port or a low-current-capable OTG device.

### Input Over-Voltage Detection

When the  $V_{BUS}$  exceeds  $V_{BUS_{OVP}}$ , the IC:

1. Turns off Q3
2. Suspends charging
3. Sets the FAULT bits to 001, sets the STAT bits to 11, and pulses the STAT pin.

When  $V_{BUS}$  falls about 150 mV below  $V_{BUS_{OVP}}$ , the fault is cleared and charging resumes after  $V_{BUS}$  is revalidated (see *VBUS POR / Non-Compliant Charger Rejection*).

### VBUS Short While Charging

If  $V_{BUS}$  is shorted with a very low impedance while the IC is charging with  $I_{INLIMIT}=100\text{ mA}$ , the IC may not meet datasheet specifications until power is removed. To trigger this condition,  $V_{BUS}$  must be driven from 5 V to GND with a high slew rate. Achieving this slew rate requires a  $0\ \Omega$  short to the USB cable less than 10cm from the connector.

## Charge Mode Battery Detection & Protection

### VBAT Over-Voltage Protection

The OREG voltage regulation loop prevents  $V_{BAT}$  from overshooting the OREG voltage by more than 50 mV when the battery is removed. When the PWM charger runs with no battery, the TE bit is not set and a battery is inserted that is charged to a voltage higher than  $V_{OREG}$ ; PWM pulses stop. If no further pulses occur for 30 ms, the IC sets the FAULT bits to 100, sets the STAT bits to 11, and pulses the STAT pin.

### Battery Detection During Charging

The IC can detect the presence, absence, or removal of a battery if the termination bit (TE) is set. During normal charging, once  $V_{BAT}$  is close to  $V_{OREG}$  and the termination charge current is detected, the IC terminates charging and sets the STAT bits to 10. It then turns on a discharge current,  $I_{DETECT}$ , for  $t_{DETECT}$ . If  $V_{BAT}$  is still above  $V_{OREG} - V_{RCH}$ , the battery is present and the IC sets the FAULT bits to 000. If  $V_{BAT}$  is below  $V_{OREG} - V_{RCH}$ , the battery is absent and the IC:

1. Sets the registers to their default values.
2. Sets the FAULT bits to 111.
3. Resumes charging with default values after  $t_{INT}$ .

### Battery Short-Circuit Protection

If the battery voltage is below the short-circuit threshold ( $V_{SHORT}$ ); a linear current source,  $I_{SHORT}$ , supplies  $V_{BAT}$  until  $V_{BAT} > V_{SHORT}$ .

### Battery Detection During Power-up

For FAN5400 and FAN5403

At  $V_{BUS}$  POR, a 5 k $\Omega$  load is applied to  $V_{BAT}$  for 500 ms to discharge any residual system capacitance in case the battery is absent. If  $V_{BAT} < V_{SHORT}$ , linear charging commences. When  $V_{BAT}$  rises above  $V_{SHORT}$ , PWM charging proceeds with the float voltage (OREG) temporarily set to 4 V. If the battery voltage exceeds 3.7 V within 32 ms of the beginning of PWM charging, the battery is absent. If battery absent is detected:

1. High-Impedance Mode is entered.
2. FAULT bits are set to 111.
3. The  $t_{15MIN}$  timer is disabled until  $V_{BUS}$  is removed.

If  $V_{BAT}$  remains below 3.7 V during the initial 32 ms period, the float voltage returns to the OREG register setting and PWM charging continues.

## System Operation with No Battery

The FAN5402 and FAN5405 continue charging after  $V_{BUS}$  POR with the default parameters, regulating the  $V_{BAT}$  line to 3.54 V until the host processor issues commands or the 15-minute timer expires. In this way, the FAN5402 and FAN5405 can start the system without a battery.

The FAN540X soft-start function can interfere with the system supply with battery absent. The soft-start activates whenever  $V_{OREG}$ ,  $I_{INLIMIT}$ , or  $I_{OCHARGE}$  are set from a lower to higher value. During soft-start, the  $I_{IN}$  limit drops to 100 mA for about 1 ms unless  $I_{INLIMIT}$  is set to 11 (no limit). This could cause the system processor to fail to start. To avoid this behavior, use the following sequence.

1. Set the OTG pin HIGH. When  $V_{BUS}$  is plugged in,  $I_{INLIMIT}$  is set to 500 mA until the system processor powers up and can set parameters through I<sup>2</sup>C.
2. Program the Safety Register.
3. Set  $I_{INLIMIT}$  to 11 (no limit).
4. Set OREG to the desired value (typically 4.18).
5. Reset the IOLEVEL bit, then set IOCHARGE.
6. Set  $I_{INLIMIT}$  to 500mA if a USB source is connected.

During the initial system startup, while the charger IC is being programmed, the system current is limited to 325 mA for 1ms during steps 4 and 5. This is the value of the soft-start  $I_{CHARGE}$  current used when  $I_{NLIM}$  is set to No Limit.

If the system is powered up without a battery present, the CV bit should be set. When a battery is inserted, the CV bit is cleared.

#### Charger Status / Fault Status

The STAT pin indicates the operating condition of the IC and provides a fault indicator for interrupt driven systems.

**Table 12. STAT Pin Function**

| EN_STAT | Charge State                 | STAT Pin                        |
|---------|------------------------------|---------------------------------|
| 0       | X                            | OPEN                            |
| X       | Normal Conditions            | OPEN                            |
| 1       | Charging                     | LOW                             |
| X       | Fault<br>(Charging or Boost) | 128 $\mu$ s Pulse,<br>then OPEN |

The FAULT bits (R0[2:0]) indicate the type of fault in Charge Mode (see Table 13).

**Table 13. Fault Status Bits During Charge Mode**

| Fault Bit |    |    | Fault Description |
|-----------|----|----|-------------------|
| B2        | B1 | B0 |                   |
| 0         | 0  | 0  | Normal (No Fault) |
| 0         | 0  | 1  | VBUS OVP          |
| 0         | 1  | 0  | Sleep Mode        |
| 0         | 1  | 1  | Poor Input Source |
| 1         | 0  | 0  | Battery OVP       |
| 1         | 0  | 1  | Thermal Shutdown  |
| 1         | 1  | 0  | Timer Fault       |
| 1         | 1  | 1  | No Battery        |

#### Charge Mode Control Bits

Setting either HZ\_MODE or  $\overline{CE}$  through I<sup>2</sup>C disables the charger and puts the IC into High-Impedance Mode and resets  $t_{32S}$ . If  $V_{BAT} < V_{LOWV}$  while in High-Impedance Mode,  $t_{32S}$  begins running and, when it overflows, all registers (except SAFETY) reset, which enables  $t_{15MIN}$  charging on versions with the 15-minute timer.

When  $t_{15MIN}$  overflows, the IC sets the  $\overline{CE}$  bit and the IC enters High-Impedance Mode. If  $\overline{CE}$  was set by  $t_{15MIN}$  overflow, a new charge cycle can only be initiated through I<sup>2</sup>C or VBUS POR.

Setting the RESET bit clears all registers. If HZ\_MODE or  $\overline{CE}$  bits were set when the RESET bit is set, these bits are also cleared, but the  $t_{32S}$  timer is not started, and the IC remains in High-Impedance Mode.

**Table 14. FAN5403–FAN5405 DISABLE Pin and  $\overline{CE}$  Bit Functionality**

| Charging | DISABLE Pin | $\overline{CE}$ | HZ_MODE |
|----------|-------------|-----------------|---------|
| ENABLE   | 0           | 0               | 0       |
| DISABLE  | X           | 1               | X       |
| DISABLE  | X           | X               | 1       |
| DISABLE  | 1           | X               | X       |

Raising the DISABLE pin stops  $t_{32S}$  from advancing, but does not reset it. If the DISABLE pin is raised during  $t_{15MIN}$  charging, the  $t_{15MIN}$  timer is reset.

#### Operational Mode Control

OPA\_MODE (REG1[0]) and the HZ\_MODE (REG1[1]) bits in conjunction with the FAULT state define the operational mode of the charger.

**Table 15. Operation Mode Control**

| HZ_MODE | OPA_MODE | FAULT | Operation Mode   |
|---------|----------|-------|------------------|
| 0       | 0        | 0     | Charge           |
| 0       | X        | 1     | Charge Configure |
| 0       | 1        | 0     | Boost            |
| 1       | X        | X     | High Impedance   |

The IC resets the OPA\_MODE bit whenever the boost is deactivated, whether due to a fault or being disabled by setting the HZ\_MODE bit.

## Boost Mode

Boost Mode can be enabled if the IC is in 32-Second Mode with the OTG pin and OPA\_MODE bits as indicated in Table 16. The OTG pin ACTIVE state is 1 if OTG\_PL=1 and 0 when OTG\_PL=0.

If boost is active using the OTG pin, Boost Mode is initiated even if the HZ\_MODE=1. The HZ\_MODE bit overrides the OPA\_MODE bit.

**Table 16. Enabling Boost**


| OTG_EN | OTG Pin | HZ_MODE | OPA_MODE | BOOST    |
|--------|---------|---------|----------|----------|
| 1      | ACTIVE  | X       | X        | Enabled  |
| X      | X       | 0       | 1        | Enabled  |
| X      | ACTIVE  | X       | 0        | Disabled |
| 0      | X       | 1       | X        | Disabled |
| 1      | ACTIVE  | 1       | 1        | Disabled |
| 0      | ACTIVE  | 0       | 0        | Disabled |

To remain in Boost Mode, the TMR\_RST must be set by the host before the  $t_{32S}$  timer times out. If  $t_{32S}$  times out in Boost Mode; the IC resets all registers, pulses the STAT pin, sets the FAULT bits to 110, and resets the BOOST bit. VBUS POR or reading R0 clears the fault condition.

## Boost PWM Control

The IC uses a minimum on-time and computed minimum off-time to regulate VBUS. The regulator achieves excellent transient response by employing current-mode modulation. This technique causes the regulator to exhibit a load line. During PWM Mode, the output voltage drops slightly as the input current rises. With a constant  $V_{BAT}$ , this appears as a constant output resistance.

The “droop” caused by the output resistance when a load is applied allows the regulator to respond smoothly to load transients with no undershoot from the load line. This can be seen in Figure 33 and Figure 43.



**Figure 43. Output Resistance ( $R_{OUT}$ )**

$V_{BUS}$  as a function of  $I_{LOAD}$  can be computed when the regulator is in PWM Mode (continuous conduction) as:

$$V_{OUT} = 5.07 - R_{OUT} \cdot I_{LOAD} \quad \text{EQ. 1}$$

At  $V_{BAT}=3.3V$ , and  $I_{LOAD}=200mA$ ,  $V_{BUS}$  would drop to:

$$V_{OUT} = 5.07 - 0.26 \cdot 0.2 = 5.018V \quad \text{EQ. 1A}$$

At  $V_{BAT}=2.7V$ , and  $I_{LOAD}=200mA$ ,  $V_{BUS}$  would drop to:

$$V_{OUT} = 5.07 - 0.327 \cdot 0.2 = 5.005V \quad \text{EQ. 1B}$$

## PFM Mode

If  $V_{BUS} > V_{REF_{BOOST}}$  (nominally 5.07 V) when the minimum off-time has ended, the regulator enters PFM Mode. Boost pulses are inhibited until  $V_{BUS} < V_{REF_{BOOST}}$ . The minimum on-time is increased to enable the output to pump up sufficiently with each PFM boost pulse. Therefore the regulator behaves like a constant on-time regulator, with the bottom of its output voltage ripple at 5.07 V in PFM Mode.

**Table 17. Boost PWM Operating States**

| Mode | Description          | Invoked When                            |
|------|----------------------|-----------------------------------------|
| LIN  | Linear Startup       | $V_{BAT} > V_{BUS}$                     |
| SS   | Boost Soft-Start     | $V_{BUS} < V_{BST}$                     |
| BST  | Boost Operating Mode | $V_{BAT} > UVLO_{BST}$ and SS Completed |

## Startup

When the boost regulator is shut down, current flow is prevented from  $V_{BAT}$  to  $V_{BUS}$ , as well as reverse flow from  $V_{BUS}$  to  $V_{BAT}$ .

## LIN State

When EN rises, if  $V_{BAT} > UVLO_{BST}$ , the regulator first attempts to bring PMID within 400 mV of  $V_{BAT}$  using an internal 450 mA current source from VBAT (LIN State). If PMID has not achieved  $V_{BAT} - 400 \text{ mV}$  after 560  $\mu s$ , a FAULT state is initiated.

## SS State

When  $PMID > V_{BAT} - 400 \text{ mV}$ , the boost regulator begins switching with a reduced peak current limit of about 50% of its normal current limit. The output slews up until  $V_{BUS}$  is within 5% of its set point; at which time, the regulation loop is closed and the current limit is set to 100%.

If the output fails to achieve 95% of its set point ( $V_{BST}$ ) within 128  $\mu s$ , the current limit is increased to 100%. If the output fails to achieve 95% of its set point after this second 384  $\mu s$  period, a fault state is initiated.

## BST State

This is the normal operating mode of the regulator. The regulator uses a minimum  $t_{OFF}$ -minimum  $t_{ON}$  modulation scheme. The minimum  $t_{OFF}$  is proportional to  $\frac{V_{IN}}{V_{OUT}}$ , which

keeps the regulator's switching frequency reasonably constant in CCM.  $t_{ON(MIN)}$  is proportional to  $V_{BAT}$  and is a higher value if the inductor current reached 0 before  $t_{OFF(MIN)}$  in the prior cycle.

To ensure the VBUS does not pump significantly above the regulation point, the boost switch remains off as long as  $FB > V_{REF}$ .

## Boost Faults

If a BOOST fault occurs:


1. The STAT pin pulses.
2. OPA\_MODE bit is reset.
3. The power stage is in High-Impedance Mode.
4. The FAULT bits (REG0[2:0]) are set per Table 18.

## Restart After Boost Faults

If boost was enabled with the OPA\_MODE bit and OTG\_EN=0, Boost Mode can only be enabled through subsequent I<sup>2</sup>C commands since OPA\_MODE is reset on boost faults. If OTG\_EN=1 and the OTG pin is still ACTIVE (see Table 16), the boost restarts after a 5.2ms delay, as shown in Figure 44. If the fault condition persists, restart is attempted every 5ms until the fault clears or an I<sup>2</sup>C command disables the boost.

**Table 18. Fault Bits During Boost Mode**

| Fault Bit |    |    | Fault Description                                                                                                                                              |
|-----------|----|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B2        | B1 | B0 |                                                                                                                                                                |
| 0         | 0  | 0  | Normal (no fault)                                                                                                                                              |
| 0         | 0  | 1  | $V_{BUS} > V_{BUS_{OVP}}$                                                                                                                                      |
| 0         | 1  | 0  | $V_{BUS}$ fails to achieve the voltage required to advance to the next state during soft-start or sustained ( $>50\mu s$ ) current limit during the BST state. |
| 0         | 1  | 1  | $V_{BAT} < UVLO_{BST}$                                                                                                                                         |
| 1         | 0  | 0  | N/A: This code does not appear.                                                                                                                                |
| 1         | 0  | 1  | Thermal shutdown                                                                                                                                               |
| 1         | 1  | 0  | Timer fault; all registers reset.                                                                                                                              |
| 1         | 1  | 1  | N/A: This code does not appear.                                                                                                                                |



**Figure 44. Boost Response Attempting to Start into  $V_{BUS}$  Short Circuit (Times in  $\mu s$ )**

## VREG Pin

The VREG pin on FAN5400 - FAN5402 provides a voltage protected from over-voltage surges on VBUS, which can be used to run auxiliary circuits. This voltage is essentially a current-limited replica of PMID. The maximum voltage on this node is 5.9 V.

FAN5403-FAN5405 provide a 1.8 V regulated output on this pin, which can be disabled through I<sup>2</sup>C by setting the DIS\_VREG bit (REG5[6]). VREG can supply up to 2 mA. This circuit, which is powered from PMID, is enabled only when  $PMID > V_{BAT}$  and does not drain current from the battery. During boost,  $V_{REG}$  is off. It is also off when the HZ\_MODE bit (REG1[1])=1.

## Monitor Register (Reg10h)

Additional status monitoring bits enable the host processor to have more visibility into the status of the IC. The monitor bits are real-time status indicators and are not internally debounced or otherwise time qualified.

The state of the MONITOR register bits listed in High-Impedance Mode are only valid when  $V_{BUS}$  is valid.

Table 19. MONITOR Register Bit Definitions

| BIT#                | NAME       | STATE                                                    |                                                              | Active When         |
|---------------------|------------|----------------------------------------------------------|--------------------------------------------------------------|---------------------|
|                     |            | 0                                                        | 1                                                            |                     |
| MONITOR Address 10h |            |                                                          |                                                              |                     |
| 7                   | ITERM_CMP  | $V_{CSIN} - V_{BAT} < V_{ITERM}$                         | $V_{CSIN} - V_{BAT} > V_{ITERM}$                             | Charging with TE=1  |
|                     |            | $V_{CSIN} - V_{BAT} < 1mV$                               | $V_{CSIN} - V_{BAT} > 1mV$                                   | Charging with TE=0  |
| 6                   | VBAT_CMP   | $V_{BAT} < V_{SHORT}$                                    | $V_{BAT} > V_{SHORT}$                                        | Charging            |
|                     |            | $V_{BAT} < V_{LOWV}$                                     | $V_{BAT} > V_{LOWV}$                                         | High-Impedance Mode |
|                     |            | $V_{BAT} < UVLO_{BST}$                                   | $V_{BAT} > UVLO_{BST}$                                       | Boosting            |
| 5                   | LINCHG     | Linear Charging Not Enabled                              | Linear Charging Enabled                                      | Charging            |
| 4                   | T_120      | $T_J < 120^{\circ}C$                                     | $T_J > 120^{\circ}C$                                         |                     |
| 3                   | ICHG       | Charging Current Controlled by $I_{CHARGE}$ Control Loop | Charging Current Not Controlled by $I_{CHARGE}$ Control Loop | Charging            |
| 2                   | IBUS       | $I_{BUS}$ Limiting Charging Current                      | Charge Current Not Limited by $I_{BUS}$                      | Charging            |
| 1                   | VBUS_VALID | $V_{BUS}$ Not Valid                                      | $V_{BUS}$ is Valid                                           | $V_{BUS} > V_{BAT}$ |
| 0                   | CV         | Constant Current Charging                                | Constant Voltage Charging                                    | Charging            |

## I<sup>2</sup>C Interface

The FAN540X's serial interface is compatible with Standard, Fast, Fast Plus, and High-Speed Mode I<sup>2</sup>C-Bus® specifications. The FAN540X's SCL line is an input and its SDA line is a bi-directional open-drain output; it can only pull down the bus when active. The SDA line only pulls LOW during data reads and when signaling ACK. All data is shifted in MSB (bit 7) first.

### Slave Address

Table 20. I<sup>2</sup>C Slave Address Byte

| Part Types      | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0   |
|-----------------|---|---|---|---|---|---|---|-----|
| FAN5400–FAN5404 | 1 | 1 | 0 | 1 | 0 | 1 | 1 | R/W |
| FAN5405         | 1 | 1 | 0 | 1 | 0 | 1 | 0 | R/W |

In hex notation, the slave address assumes a 0 LSB. The hex slave address for the FAN5405 is D4h and is D6h for all other parts in the family.

### Bus Timing

As shown in Figure 45, data is normally transferred when SCL is LOW. Data is clocked in on the rising edge of SCL. Typically, data transitions shortly at or after the falling edge of SCL to allow ample time for the data to set up before the next SCL rising edge.




Figure 45. Data Transfer Timing

Each bus transaction begins and ends with SDA and SCL HIGH. A transaction begins with a START condition, which is defined as SDA transitioning from 1 to 0 with SCL HIGH, as shown in Figure 46.




Figure 46. Start Bit

A transaction ends with a STOP condition, which is defined as SDA transitioning from 0 to 1 with SCL HIGH, as shown in Figure 47.




Figure 47. Stop Bit

During a read from the FAN540X (Figure 50), the master issues a Repeated Start after sending the register address and before resending the slave address. The Repeated Start is a 1-to-0 transition on SDA while SCL is HIGH, as shown in Figure 48.

### High-Speed (HS) Mode

The protocols for High-Speed (HS), Low-Speed (LS), and Fast-Speed (FS) Modes are identical except the bus speed for HS Mode is 3.4 MHz. HS Mode is entered when the bus master sends the HS master code 00001XXX after a start condition. The master code is sent in Fast or Fast Plus Mode (less than 1MHz clock); slaves do not ACK this transmission.

The master then generates a repeated start condition (Figure 48) that causes all slaves on the bus to switch to HS Mode. The master then sends I<sup>2</sup>C packets, as described above, using the HS Mode clock rate and timing.

The bus remains in HS Mode until a stop bit (Figure 47) is sent by the master. While in HS Mode, packets are separated by repeated start conditions (Figure 48).





Figure 48. Repeated Start Timing

# Read and Write Transactions


The figures below outline the sequences for data read and write. Bus control is signified by the shading of the packet, defined as Master Drives Bus and Slave Drives Bus. All addresses and data are MSB first.

**Table 21. Bit Definitions for Figure 49, Figure 50**

| Symbol         | Definition                                                          |
|----------------|---------------------------------------------------------------------|
| S              | START, see Figure 46.                                               |
| A              | ACK. The slave drives SDA to 0 to acknowledge the preceding packet. |
| $\overline{A}$ | NACK. The slave sends a 1 to NACK the preceding packet.             |
| R              | Repeated START, see Figure 48                                       |
| P              | STOP, see Figure 47                                                 |



**Figure 49. Write Transaction**



**Figure 50. Read Transaction**

## Register Descriptions

The FAN5400-FAN5402 have seven user-accessible registers; the FAN5403-05 have an additional two registers, as defined in Table 22.

**Table 22. I<sup>2</sup>C Register Address**

| IC              | Register   |                 | Address Bits |   |   |   |   |   |   |   |
|-----------------|------------|-----------------|--------------|---|---|---|---|---|---|---|
|                 | Name       | REG#            | 7            | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
| ALL             | CONTROL0   | 0               | 0            | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
|                 | CONTROL1   | 1               | 0            | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
|                 | OREG       | 2               | 0            | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
|                 | IC_INFO    | 03<br>or<br>3Bh | 0            | 0 | 0 | 0 | 0 | 0 | 1 | 1 |
|                 | IBAT       | 4               | 0            | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| FAN5403-FAN5405 | SP_CHARGER | 5               | 0            | 0 | 0 | 0 | 0 | 1 | 0 | 1 |
|                 | SAFETY     | 6               | 0            | 0 | 0 | 0 | 0 | 1 | 1 | 0 |
| ALL             | MONITOR    | 10h             | 0            | 0 | 0 | 0 | 1 | 0 | 1 | 0 |

**Table 23. Register Bit Definitions**

This table defines the operation of each register bit for all IC versions. Default values are in **bold** text.

| Bit             | Name           | Value    | Type     | Description                                                                                 |
|-----------------|----------------|----------|----------|---------------------------------------------------------------------------------------------|
| <b>CONTROL0</b> |                |          |          | <b>Register Address: 00</b> <b>Default Value=X1XX 0XXX</b>                                  |
| 7               | TMR_RST<br>OTG | 1        | W        | Writing a 1 resets the $t_{32S}$ timer; writing a 0 has no effect                           |
|                 |                |          | R        | Returns the OTG pin level (1=HIGH)                                                          |
| 6               | EN_STAT        | 0        | R/W      | Prevents STAT pin from going LOW during charging; STAT pin still pulses to enunciate faults |
|                 |                | <b>1</b> |          | <b>Enables STAT pin LOW when IC is charging</b>                                             |
| 5:4             | STAT           | 00       | R        | Ready                                                                                       |
|                 |                | 01       |          | Charge in progress                                                                          |
|                 |                | 10       |          | Charge done                                                                                 |
|                 |                | 11       |          | Fault                                                                                       |
| 3               | BOOST          | <b>0</b> | <b>R</b> | <b>IC is not in Boost Mode</b>                                                              |
|                 |                | 1        |          | IC is in Boost Mode                                                                         |
| 2:0             | FAULT          |          | R        | Fault status bits: <i>for Charge Mode, see Table 13; for Boost Mode: see Table 18</i>       |

**Table 23. Register Bit Definitions** (Continued)

| Bit      | Name                   | Value   | Type | Description                                                                                                                                  |                                |
|----------|------------------------|---------|------|----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| CONTROL1 |                        |         |      | Register Address: 01                                                                                                                         | Default Value=0011 0000 (30h)  |
| 7:6      | I <sub>INLIM</sub>     |         | R/W  | Input current limit, see <i>Table 7</i>                                                                                                      |                                |
| 5:4      | V <sub>LOWV</sub>      | 00      | R/W  | 3.4 V                                                                                                                                        | Weak battery voltage threshold |
|          |                        | 01      |      | 3.5 V                                                                                                                                        |                                |
|          |                        | 10      |      | 3.6 V                                                                                                                                        |                                |
|          |                        | 11      |      | 3.7 V                                                                                                                                        |                                |
| 3        | TE                     | 0       | R/W  | Disable charge current termination                                                                                                           |                                |
|          |                        | 1       |      | Enable charge current termination                                                                                                            |                                |
| 2        | $\overline{\text{CE}}$ | 0       | R/W  | Charger enabled                                                                                                                              |                                |
|          |                        | 1       |      | Charger disabled                                                                                                                             |                                |
| 1        | HZ_MODE                | 0       | R/W  | Not High-Impedance Mode                                                                                                                      | See <i>Table 16</i>            |
|          |                        | 1       |      | High-Impedance Mode                                                                                                                          |                                |
| 0        | OPA_MODE               | 0       | R/W  | Charge Mode                                                                                                                                  |                                |
|          |                        | 1       |      | Boost Mode                                                                                                                                   |                                |
| OREG     |                        |         |      | Register Address: 02                                                                                                                         | Default Value=0000 1010 (0Ah)  |
| 7:2      | OREG                   |         | R/W  | Charger output “float” voltage; programmable from 3.5 to 4.44 V in 20 mV increments; <b>defaults to 000010 (3.54 V)</b> , see <i>Table 3</i> |                                |
| 1        | OTG_PL                 | 0       | R/W  | OTG pin active LOW                                                                                                                           |                                |
|          |                        | 1       |      | OTG pin active HIGH                                                                                                                          |                                |
| 0        | OTG_EN                 | 0       | R/W  | Disables OTG pin                                                                                                                             |                                |
|          |                        | 1       |      | Enables OTG pin                                                                                                                              |                                |
| IC_INFO  |                        |         |      | Register Address: 03 or 3B                                                                                                                   | Default Value=100X XXXX        |
| 7:5      | Vendor Code            | 100     | R    | Identifies Fairchild Semiconductor as the IC supplier                                                                                        |                                |
| 4:3      | PN                     |         | R    | Part number bits, see the <i>Ordering Info on page 1</i>                                                                                     |                                |
| 2:0      | REV                    |         | R    | IC Revision, revision 1.X, where X is the decimal of these three bits                                                                        |                                |
| IBAT     |                        |         |      | Register Address: 04                                                                                                                         | Default Value=1000 1001 (89h)  |
| 7        | RESET                  | 1       | W    | Writing a 1 resets charge parameters, except the Safety register (Reg6), to their defaults: writing a 0 has no effect; read returns 1        |                                |
| 6:4      | IOCHARGE               | Table 5 | R/W  | Programs the maximum charge current, see <i>Table 5</i>                                                                                      |                                |
| 3        | Reserved               | 1       | R    | Unused                                                                                                                                       |                                |
| 2:0      | ITERM                  | Table 6 | R/W  | Sets the current used for charging termination, see <i>Table 6</i>                                                                           |                                |

**Table 23. Register Bit Definitions** (Continued)

| <b>SP_CHARGER (FAN5403 – FAN5405)</b> |            |                 | <b>Register Address: 05</b>       |                                                                                                                                                       | <b>Default Value=001X X100</b>       |
|---------------------------------------|------------|-----------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| 7                                     | Reserved   | 0               | R                                 | Unused                                                                                                                                                |                                      |
| 6                                     | DIS_VREG   | 0               | R/W                               | 1.8 V regulator is ON                                                                                                                                 |                                      |
|                                       |            | 1               |                                   | 1.8 V regulator is OFF                                                                                                                                |                                      |
| 5                                     | IO_LEVEL   | 0               | R/W                               | Output current is controlled by IOCHARGE bits                                                                                                         |                                      |
|                                       |            | 1               |                                   | Voltage across $R_{SENSE}$ for output current control is set to 22.1 mV (325 mA for $R_{SENSE}=68\text{ m}\Omega$ , 221 mA for $100\text{ m}\Omega$ ) |                                      |
| 4                                     | SP         | 0               | R                                 | Special charger is not active ( $V_{BUS}$ is able to stay above $V_{SP}$ )                                                                            |                                      |
|                                       |            | 1               |                                   | Special charger has been detected and $V_{BUS}$ is being regulated to $V_{SP}$                                                                        |                                      |
| 3                                     | EN_LEVEL   | 0               | R                                 | DISABLE pin is LOW                                                                                                                                    |                                      |
|                                       |            | 1               |                                   | DISABLE pin is HIGH                                                                                                                                   |                                      |
| 2:0                                   | VSP        | Table 8         | R/W                               | Special charger input regulation voltage, see Table 8                                                                                                 |                                      |
| <b>SAFETY (FAN5403 – FAN5405)</b>     |            |                 | <b>Register Address: 06</b>       |                                                                                                                                                       | <b>Default Value=0100 0000 (40h)</b> |
| 7                                     | Reserved   | 0               | R                                 | Bit disabled and always returns 0 when read back                                                                                                      |                                      |
| 6:4                                   | ISAFE      | Table 9         | R/W                               | Sets the maximum $I_{OCHARGE}$ value used by the control circuit, see Table 9                                                                         |                                      |
| 3:0                                   | VSAFE      | Table 10        | R/W                               | Sets the maximum $V_{OREG}$ used by the control circuit, see Table 10                                                                                 |                                      |
| <b>MONITOR</b>                        |            |                 | <b>Register Address: 10h (16)</b> |                                                                                                                                                       | <i>See Table 19</i>                  |
| 7                                     | ITERM_CMP  | See<br>Table 19 | R                                 | Real-time ITERM comparator output: 1 when $VRSENSE > ITERM$ reference. Dynamic system loads can cause this bit to toggle between 0 and 1.             |                                      |
| 6                                     | VBAT_CMP   |                 | R                                 | Output of VBAT comparator                                                                                                                             |                                      |
| 5                                     | LINCHG     |                 | R                                 | 30 mA linear charger ON                                                                                                                               |                                      |
| 4                                     | T_120      |                 | R                                 | Thermal regulation comparator; when=1 and $T_{145}=0$ , the charge current is limited to 22.1 mV across $R_{SENSE}$                                   |                                      |
| 3                                     | ICHG       |                 | R                                 | 0 indicates the $I_{CHARGE}$ loop is controlling the battery charge current                                                                           |                                      |
| 2                                     | IBUS       |                 | R                                 | 0 indicates the $I_{BUS}$ (input current) loop is controlling the battery charge current                                                              |                                      |
| 1                                     | VBUS_VALID |                 | R                                 | 1 indicates $V_{BUS}$ has passed validation and is capable of charging                                                                                |                                      |
| 0                                     | CV         |                 | R                                 | 1 indicates the constant-voltage loop (OREG) is controlling the charger and all current limiting loops have released                                  |                                      |

## PCB Layout Recommendations

Bypass capacitors should be placed as close to the IC as possible. In particular, the total loop length for CMID should be minimized to reduce overshoot and ringing on the SW, PMID, and VBUS pins. All power and ground pins must be

routed to their bypass capacitors using top copper if possible. Copper area connecting to the IC should be maximized to improve thermal performance.






Figure 51. PCB Layout Recommendations


## Physical Dimensions





TOP VIEW



option 1  
option 2  
RECOMMENDED LAND PATTERN  
(NSMD TYPE)



SIDE VIEWS



BOTTOM VIEW

### NOTES:

- A. NO JEDEC REGISTRATION APPLIES.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCE PER ASMEY14.5M, 1994.
- D. DATUM C IS DEFINED BY THE SPHERICAL CROWNS OF THE BALLS.
- E. PACKAGE NOMINAL HEIGHT IS 586 MICRONS ±39 MICRONS (547-625 MICRONS).
- F. FOR DIMENSIONS D, E, X, AND Y SEE PRODUCT DATASHEET.
- G. DRAWING FILNAME: MKT-UC020AArev3.

Figure 52. 20-Ball WLCSP, 4x5 Array, 0.4 mm Pitch, 250  $\mu$ m Ball

## Product-Specific Dimensions

| Product    | D                 | E                 | X     | Y     |
|------------|-------------------|-------------------|-------|-------|
| FAN540XUCX | 1.960 $\pm$ 0.030 | 1.870 $\pm$ 0.030 | 0.335 | 0.180 |

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:  
<http://www.fairchildsemi.com/packaging/>



## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

|                          |                                                |                                       |                  |
|--------------------------|------------------------------------------------|---------------------------------------|------------------|
| 2Cool™                   | FPS™                                           |                                       | Sync-Lock™       |
| AccuPower™               | F-PFS™                                         |                                       |                  |
| AX-CAP®*                 | FRFET™                                         | PowerTrench®                          | TinyBoost™       |
| BitSiC™                  | Global Power Resource™                         | PowerXS™                              | TinyBuck™        |
| Build it Now™            | GreenBridge™                                   | Programmable Active Droop™            | TinyCalc™        |
| CorePLUS™                | Green FPS™                                     | QFET®                                 | TinyLogic®       |
| CorePOWER™               | Green FPS™ e-Series™                           | QS™                                   | TINYOPTO™        |
| CROSSVOLT™               | Gmax™                                          | Quiet Series™                         | TinyPower™       |
| CTL™                     | GTO™                                           | RapidConfigure™                       | TinyPVM™         |
| Current Transfer Logic™  | IntelliMAX™                                    |                                       | TinyWire™        |
| DEUXPEED®                | ISOPLANAR™                                     | Saving our world, 1mW/W/kW at a time™ | TranSiC™         |
| Dual Cool™               | Making Small Speakers Sound Louder and Better™ | SignalWise™                           | TriFault Detect™ |
| EcoSPARK®                | MegaBuck™                                      | SmartMax™                             | TRUECURRENT®*    |
| EfficientMax™            | MICROCOUPLER™                                  | SMART START™                          | μSerDes™         |
| ESBC™                    | MicroFET™                                      | Solutions for Your Success™           |                  |
|                          | MicroPak™                                      | SPM®                                  | UHC®             |
| Fairchild                | MicroPak2™                                     | STEALTH™                              | Ultra FRFET™     |
| Fairchild Semiconductor® | MillerDrive™                                   | SuperFET®                             | UniFET™          |
| FACT Quiet Series™       | MotionMax™                                     | SuperSOT™_3                           | VCX™             |
| FACT®                    | mWSaver™                                       | SuperSOT™_6                           | VisualMax™       |
| FAST®                    | OptoHiT™                                       | SuperSOT™_8                           | VoltagePlus™     |
| FastvCore™               | OPTOLOGIC®                                     | SupreMOS®                             | XS™              |
| FETBench™                | OPTOPLANAR®                                    | SyncFET™                              |                  |

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition                                                                                                                                                                                          |
|--------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.                                               |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.                                                    |

Rev. I64

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ          800077892  
  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel          +86 (21) 64016692-8333  
  
Email       mkt@ameya360.com