



The BTM430 and BTM431 Bluetooth® modules from Laird Technologies have been designed to meet the needs of developers who wish to add robust, short range Bluetooth data connectivity to their products. They are based on the market leading Cambridge Silicon Radio BC04 chipset, providing exceptionally low power consumption with outstanding range.

With a footprint as small as 12.5 x 18.0 mm for the BTM430 and best of class, low-power operation, these modules are the ideal choice for applications where designers need both performance and minimum size. For maximum flexibility in systems integration, the modules are designed to support a separate power supply for I/O.

To aid product development and integration, Laird Technologies has integrated a complete Bluetooth protocol stack within the modules, including support for the Bluetooth Serial Port Profile. The modules are fully qualified as Bluetooth End Products, allowing designers to integrate them within their own products with no further Bluetooth Qualification. They can then list and promote their products on the Bluetooth website free of charge.

A comprehensive AT command or Multipoint Packet Protocol is included, which simplifies firmware integration. This ensures that the choice of Laird Technologies Bluetooth modules guarantees the fastest route to market.

#### FEATURES AND BENEFITS

- Bluetooth v2.0+EDR
- Adaptive frequency hopping to cope with interference from other wireless devices
- External or internal antenna options
- Comprehensive AT interface for simple programming
- Multipoint Packet Protocol supporting up to 3 connections
- Bluetooth End Product Qualified
- Compact size
- Class 2 output – 4 dBm
- Low power operation
- UART interface
- PCM and SCO for external codec
- GPIO lines under AT control
- Wi-Fi co-existence

#### APPLICATION AREAS

- Embedded devices
- Phone accessories
- Security devices
- Medical and telehealth devices
- Aftermarket automotive applications
- Bluetooth advertising
- ePOS

**global solutions: local support™**

USA: +1.800.492.2320

Europe: +44.1628.858.940

Asia: +852.2268.6567

wirelessinfo@lairdtech.com

[www.lairdtech.com/wireless](http://www.lairdtech.com/wireless)

CATEGORIES	FEATURE	IMPLEMENTATION
<b>Wireless Specification</b>	Bluetooth®	Version 2.0+EDR
	Frequency	2.402 – 2.480 GHz
		Class 2
	Max Transmit Power	+4 dBm (at antenna pad – BTM430) +4 dBm (from integrated antenna – BTM431)
	Receive Sensitivity	Better than -84 dBm
	Range	Up to 30 meters
	Data Rates	Up to 2.1Mbps (over the air)
	UART Data Transfer Rate	Greater than 300 Kbps
<b>Host Interface</b>	UART	Supports CTS, RTS, DTR, DSR, DCD and RI
<b>User Interface</b>	GPIO	8 lines (shared)
<b>Profiles</b>		SPP – Serial Port Profile FTP Client OBEX Client HSP (partial) HFP (partial) DUN
<b>Supply Voltage</b>	Supply	3.0 v to + 3.3 v
	I/O	1.7 v to + 3.6 v (independent of Vcc)
<b>Power Consumption</b>	Current Consumption	Less than 40 mA during SCO transmission Idle (sleep) < 1 mA
<b>Coexistence / Compatibility</b>	802.11 (Wi-Fi)	2 wire and 3 wire schemes supported
<b>Connections</b>	External Antenna	50 Ohm matched SMT pad – BTM430
	Internal Antenna	Multilayer ceramic – BTM431
<b>Protocols</b>		AT Command Set
		Multipoint Packet Protocol – up to 3 connections (throughput is limited in multipoint mode)
<b>Physical</b>	Dimensions	12.5 mm x 18.0 mm x 3.4 mm (external antenna – BTM430) 12.5 mm x 22.0 mm x 3.4 mm (internal antenna – BTM431)
<b>Environmental</b>	Operating Temperature	-40°C to +85°C
	Storage Temperature	-40°C to +85°C
<b>Miscellaneous</b>	Lead free	Lead-free and RoHS compliant
	Warranty	1 Year
<b>Development Tools</b>	Development Kit	Development board and software tools
<b>Approvals</b>	Bluetooth	End Product Approved
	FCC/IC & CE	BTM430 - Limited Modular Approval
		BTM431 - Full Modular Approval

### ORDERING INFORMATION

BTM430	Bluetooth AT Data Module (external antenna)
BTM431	Bluetooth AT Data Module (with integrated antenna)
DVK-BTM430	Development Kit (external antenna)
DVK-BTM431	Development Kit (with integrated antenna)

The details contained within the document are subject to change.  
Download the product specification from [www.lairdtech.com/wireless](http://www.lairdtech.com/wireless) for the most current specification.

LWS-DS-BTM430-431 0412

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email        amall@ameya360.com  
  
QQ            800077892  
  
Skype        ameyasales1 ameyasales2

➤ Customer Service :

Email        service@ameya360.com

➤ Partnership :

Tel            +86 (21) 64016692-8333  
  
Email        mkt@ameya360.com