

HEYCO



Heyco® Liquid Tight Hole Plugs

Standard 85 Durometer Plugs

Maximum Panel Thickness .125" (3,2 mm)

- Oil tight, rain tight, submersible.
- UL certified for outdoor applications.
- V0 Flammability rating.
- Install with fingertip pressure (no tool required).
- Multiple nominal sizes fit .500" (12,7 mm) to 1.00" (25,4 mm) true size mounting holes.
- Three trade sizes fit 1/2" to 1" knock-out holes.
- Lock firmly in boxes from .030" (0,8 mm) to .125" (3,2 mm) thick.
- True sizes are UL recognized under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 008919C.
- Trade sizes are UL listed under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 081067C.

MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	UL or CSA	PART DIMENSIONS					
in.	mm.				A Head Diameter		B Overall Height		C Head Thickness	
					in.	mm.	in.	mm.	in.	mm.
.500	12,7	3830	KOS-LT 500	UL	.91	23,1	.45	11,4	.29	7,4
.625	15,9	3834	KOS-LT 625	UL	1.03	26,2	.47	11,9	.31	7,9
.750	19,1	3831	KOS-LT 750	UL	1.15	29,2	.51	13,0	.35	8,9
.875	22,2	3833	KOS-LT 1/2	UL	1.23	32,5	.50	13,5	.36	9,1
1.000	25,4	3832	KOS-LT 1000	UL	1.41	35,8	.56	14,2	.40	10,2
1.093	27,8	3835	KOS-LT 3/4	UL	1.53	38,6	.55	14,0		
1.375	34,9	3837	KOS-LT 1	UL	1.80	45,2	.56	14,3	.42	10,7

Available in black color only.



Low 75 Durometer Plugs

Maximum Panel Thickness .125" (3,2 mm)

MOUNTING HOLE DIAMETER*		PART NO.		DESCRIPTION	UL or CSA	PART DIMENSIONS					
		Black	Gray			B Head Diameter		C Overall Height		Head Thickness	
in.	mm.					in.	mm.	in.	mm.	in.	mm.
.875	22,2	3833FN	3833FP	KOS-LT 1/2 LD	UL	1.23	32,5	.50	13,5	.36	9,1
1.093	27,8	3835FN	3835FP	KOS-LT 3/4 LD	UL	1.53	38,6	.55	14,0	.40	10,2
1.375	34,9	3837FN	3837FP	KOS-LT 1 LD	UL	1.80	45,2	.56	14,3	.42	10,7

Standard colors black and gray.

*Consult Heyco for other Liquid Tight Hole Plug sizes in Low Durometer material.



Quick Specs

Material	85 75	Santoprene-Hardness 85 Shore A Santoprene-Hardness 75 Shore A
Certifications	Trade Sizes (1/2, 3/4, 1)	UL Listed under Underwriters' Laboratories File E28430 CSA Certified by Canadian Standard Association File 081067C
	True Sizes (all other)	UL Recognized under Underwriters' Laboratories File E51579 CSA Certified by Canadian Standard Association File 0089118C
Flammability Rating	94V-0	
Temperature Rating	-81°F (-60°C) to 275°F (135°C)	

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com