

# Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

74489440012



Bezeichnung :


SPEICHERDROSSEL WE-TDC 8038

description :


COUPLED INDUCTOR WE-TDC 8038

DATUM / DATE : 2010-08-31

## A Mechanische Abmessungen / dimensions:



|   | 8038      |    |
|---|-----------|----|
| A | 8,0 ± 0,3 | mm |
| B | 8,0 ± 0,3 | mm |
| C | 3,8 ± 0,3 | mm |
| D | 3,2 typ.  | mm |
| E | 2,4 typ.  | mm |
| F | 1,0 typ.  | mm |




● start of winding

## B Elektrische Eigenschaften / electrical properties:

## C Lötpad / soldering spec.:

| Eigenschaften / properties                                                       | Testbedingungen / test conditions |                                   | Wert / value | Einheit / unit | tol.   |
|----------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|--------------|----------------|--------|
| Induktivität (je Wicklg.) / inductance (each wdg.)                               | 100 kHz / 5mA                     | L <sub>1</sub> , L <sub>2</sub>   | 1,2          | μH             | +/-30% |
| DC-Widerstand (je Wicklg.) / DC-resistance (each wdg.)                           | @ 20°C                            | R <sub>DC1,2 typ</sub>            | 20,2         | mΩ             | typ.   |
| DC-Widerstand (je Wicklg.) / DC-resistance (each wdg.)                           | @ 20°C                            | R <sub>DC1,2 max</sub>            | 26           | mΩ             | max.   |
| Nennstrom (je Wicklg.) <sup>(1)</sup> / rated Current (each wdg.) <sup>(1)</sup> | ΔT = 40 K                         | I <sub>N1</sub> , I <sub>N2</sub> | 3,05         | A              | typ.   |
| Sättigungsstrom (je Wicklg.) / saturation current (each wdg.)                    | ΔL/L < 10%                        | I <sub>sat</sub>                  | 7,5          | A              | typ.   |
| Eigenres.-Frequenz / self-res.-frequency                                         |                                   | SRF                               | 90           | MHz            | typ.   |
| Nennspannung / rated Voltage                                                     |                                   | U <sub>DC</sub>                   | 80           | V              | max.   |

<sup>(1)</sup> Stromfluss durch beide Wicklungen verursacht ΔT / both windings driven by rated current will occur ΔT



## D Prüfgeräte / test equipment:

## E Testbedingungen / test conditions:

WAYNE KERR 3260B für/for L<sub>0</sub>; I<sub>SAT</sub>

Agilent N5776A für/for I<sub>DC</sub>;

GMC Metrahit 271 für/for R<sub>DC</sub>

Agilent E4991A für/for SRF

Luftfeuchtigkeit / humidity: 33%  
Umgebungstemperatur / temperature: +20°C

## F Werkstoffe & Zulassungen / material & approvals:

## G Eigenschaften / general specifications:

Basismaterial / base material: Ferrit/ ferrite  
Draht / wire: Class H  
Endoberfläche / finishing electrode: Ag/Ni/Sn

Betriebstemp. / operating temperature: -40°C - +125°C  
Umgebungstemp. / ambient temperature: -40°C - +85°C  
It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

ALa

Version 1

10-08-31

Name

Änderung / modification

Datum / date

**Würth Elektronik eiSos GmbH & Co. KG**

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
http://www.we-online.de

# Spezifikation für Freigabe / specification for release


Kunde / customer :  
 Artikelnummer / part number : 74489440012  
 Bezeichnung : SPEICHERDROSSEL WE-TDC 8038  
 description : COUPLED INDUCTOR WE-TDC 8038



DATUM / DATE : 2010-08-31

## H Induktivitätskurve / Inductance curve:

Induktivität vs Strom (typ.)/  
 Inductance vs Current (typ.)



|                                     |                          |      |                         |              |
|-------------------------------------|--------------------------|------|-------------------------|--------------|
| Freigabe erteilt / general release: | Kunde / customer         |      |                         |              |
|                                     |                          |      |                         |              |
|                                     |                          |      |                         |              |
| Datum / date                        | Unterschrift / signature |      |                         |              |
|                                     | Würth Elektronik         |      |                         |              |
|                                     |                          |      |                         |              |
| Geprüft / checked                   | Kontrolliert / approved  | ALa  | Version 1               | 10-08-31     |
|                                     |                          | Name | Änderung / modification | Datum / date |

### Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.de>

# Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

74489440012

Bezeichnung :

SPEICHERDROSSEL WE-TDC 8038

description :


COUPLED INDUCTOR WE-TDC 8038





DATUM / DATE : 2010-08-31

## I Rollenspezifikation / tape and reel specification:

## Gurtspezifikation / Tape specification:



|   |            |    |
|---|------------|----|
| A | 8,4 ± 0,1  | mm |
| B | 16,0 ± 0,3 | mm |
| C | 1,5 ± 0,1  | mm |
| D | 4,0 ± 0,1  | mm |
| E | 2,0 ± 0,1  | mm |
| F | 7,5 ± 0,1  | mm |
| G | 12,0 ± 0,1 | mm |
| H | 4,1 ± 0,1  | mm |
| I | 0,4 ± 0,05 | mm |



| Rollenspezifikation / Reel specification: |             |    |
|-------------------------------------------|-------------|----|
| a                                         | 178,0 ± 2,0 | mm |
| b                                         | 21,00 ± 0,8 | mm |
| c                                         | 13,00 ± 0,5 | mm |
| d                                         | 50,00 ± 1,0 | mm |

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

ALa

Version 1

10-08-31

Name

Änderung / modification

Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

**Würth Elektronik eiSos GmbH & Co. KG**

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
http://www.we-online.de

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)