


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:


PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	6.20 ohms max.
D.C. RESISTANCE	6-9 @20°C	0.10 ohms max.
D.C. RESISTANCE	4-5 @20°C	1.00 ohms max.
INDUCTANCE	1-3 10kHz, 100mVAC, Ls	1.60mH $\pm 10\%$
LEAKAGE INDUCTANCE	1-3 tie(4+5, 6+9), 100kHz, 100mVAC, Ls	35uH typ., 50uH max.
DIELECTRIC	1-9 tie(3+5), 4000VAC, 1 second	4000VAC, 1 minute
URNS RATIO	(1-3):(9-6)	8:1, $\pm 1\%$
URNS RATIO	(1-3):(5-4)	6:1, $\pm 1\%$

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C.

- Complies with the following requirements as defined by IEC61558-2-17:
- Basic insulation for a working voltage of 600VDC.
 - Reinforced insulation for a working voltage of 239VAC.

REV.	DATE	Packaging Specifications
6E	3/11	Method: Tray
6D	5/10	PKG-0730
6C	9/09	www.we-online.com/midcom
6B	1/09	SEE REVISION SHEET FOR



Tolerances unless otherwise specified:
 Angles: $\pm 1^\circ$
 Decimals: $\pm .005$ [.13]
 Fractions: $\pm 1/64$
 Footprint: $\pm .001$ [.03]
 This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE

TRANSFORMER
 EE13/7/4

eiSos p/n: 750370024

PART NO.

750370024



SPECIFICATION SHEET 1 OF 1

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com