

BYV25D-600

Rectifier diode, ultrafast

Rev. 01 — 29 July 2008

Product data sheet

1. Product profile

1.1 General description

Ultrafast, epitaxial rectifier diode in a SOT428 (DPAK) surface-mountable plastic package.

1.2 Features

- Fast switching
- Soft recovery characteristic
- Low forward voltage drop
- Low thermal resistance
- High thermal cycling performance

1.3 Applications

- High frequency switched-mode power supplies
- Discontinuous Current Mode (DCM) Power Factor Correction (PFC)

1.4 Quick reference data

- $V_{RRM} \leq 600 \text{ V}$
- $V_F \leq 1.11 \text{ V}$
- $I_{F(AV)} \leq 5 \text{ A}$
- $t_{rr} \leq 60 \text{ ns}$

2. Pinning information

Table 1. Pinning

| Pin | Description | Simplified outline | Graphic symbol |
|-----|----------------------------|----------------------|------------------|
| 1 | no connection | <p>SOT428 (DPAK)</p> | <p>001aaa020</p> |
| 2 | cathode (k) ^[1] | | |
| 3 | anode (a) | | |
| mb | mounting base; cathode (k) | | |

[1] It is not possible to connect to pin 2 of the SOT428 package.

3. Ordering information

Table 2. Ordering information

| Type number | Package | | Version |
|-------------|---------|---|---------|
| | Name | Description | |
| BYV25D-600 | DPAK | plastic single-ended surface-mounted package (DPAK); 3-leads (one lead cropped) | SOT428 |

4. Limiting values

Table 3. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-------------|-------------------------------------|---|-----|------|--------------------|
| V_{RRM} | repetitive peak reverse voltage | | - | 600 | V |
| V_{RWM} | crest working reverse voltage | | - | 600 | V |
| V_R | reverse voltage | square waveform; $\delta = 1.0$; $T_{mb} \leq 100\text{ }^{\circ}\text{C}$ | - | 600 | V |
| $I_{F(AV)}$ | average forward current | square waveform; $\delta = 0.5$; $T_{mb} \leq 131\text{ }^{\circ}\text{C}$ | - | 5 | A |
| I_{FRM} | repetitive peak forward current | square waveform; $\delta = 0.5$; $T_{mb} \leq 131\text{ }^{\circ}\text{C}$ | - | 10 | A |
| I_{FSM} | non-repetitive peak forward current | $t = 10\text{ ms}$; sinusoidal waveform | - | 60 | A |
| | | $t = 8.3\text{ ms}$; sinusoidal waveform | - | 66 | A |
| T_{stg} | storage temperature | | -40 | +150 | $^{\circ}\text{C}$ |
| T_j | junction temperature | | - | 150 | $^{\circ}\text{C}$ |

5. Thermal characteristics

Table 4. Thermal characteristics

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|----------------|---|--|-----------------------|-----|-----|------|
| $R_{th(j-mb)}$ | thermal resistance from junction to mounting base | with heatsink compound; see Figure 1 | - | - | 3.0 | K/W |
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | in free air | [1] - | 50 | - | K/W |

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.





Fig 1. Transient thermal impedance from junction to mounting base as a function of pulse width

6. Characteristics

Table 5. Characteristics
T_j = 25 °C unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|-------------------------|-------------------------------|--|-----|------|------|------|
| Static characteristics | | | | | | |
| V _F | forward voltage | I _F = 5 A; T _j = 150 °C; see Figure 2 | - | 0.97 | 1.11 | V |
| | | I _F = 5 A | - | 1.12 | 1.30 | V |
| I _R | reverse current | V _R = 600 V | - | 2 | 50 | μA |
| | | V _R = 600 V; T _j = 100 °C | - | 0.1 | 0.35 | mA |
| Dynamic characteristics | | | | | | |
| Q _r | recovered charge | I _F = 2 A to V _R ≥ 30 V; dI _F /dt = 20 A/μs; see Figure 3 | - | 40 | 70 | nC |
| t _{rr} | reverse recovery time | I _F = 1 A to V _R ≥ 30 V; dI _F /dt = 100 A/μs; see Figure 3 | - | 50 | 60 | ns |
| I _{RM} | peak reverse recovery current | I _F = 10 A to V _R ≥ 30 V; dI _F /dt = 50 A/μs; T _j = 100 °C; see Figure 3 | - | 3 | 5.5 | A |
| V _{FR} | forward recovery voltage | I _F = 10 A; dI _F /dt = 10 A/μs; see Figure 4 | - | 3.2 | - | V |



- (1) T_j = 150 °C; typical values
- (2) T_j = 150 °C; maximum values
- (3) T_j = 25 °C; maximum values

Fig 2. Forward current as a function of forward voltage




Fig 3. Reverse recovery definitions




Fig 4. Forward recovery definitions




Fig 5. Forward power dissipation as a function of average forward current; square waveform; maximum values

$$I_{F(AV)} = I_{F(RMS)} \times \sqrt{\delta}$$




Fig 6. Forward power dissipation as a function of average forward current; sinusoidal waveform; maximum values

$$a = \text{form factor} = I_{F(RMS)} / I_{F(AV)}$$

7. Package outline

Plastic single-ended surface-mounted package (DPAK); 3 leads (one lead cropped)

SOT428




Fig 7. Package outline SOT428 (TO-252)

8. Revision history

Table 6. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|--------------|--------------|--------------------|---------------|------------|
| BYV25D-600_1 | 20080729 | Product data sheet | - | - |

9. Legal information

9.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

9.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

9.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental

damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

10. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

11. Contents

1 Product profile 1

1.1 General description..... 1

1.2 Features 1

1.3 Applications 1

1.4 Quick reference data..... 1

2 Pinning information..... 1

3 Ordering information..... 2

4 Limiting values..... 2

5 Thermal characteristics..... 3

6 Characteristics..... 4

7 Package outline 6

8 Revision history..... 7

9 Legal information..... 8

9.1 Data sheet status 8

9.2 Definitions..... 8

9.3 Disclaimers..... 8

9.4 Trademarks..... 8

10 Contact information..... 8

11 Contents 9



Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com