

# IRF3315PbF


HEXFET® Power MOSFET

- Advanced Process Technology
- Dynamic dv/dt Rating
- 175°C Operating Temperature
- Fast Switching
- Fully Avalanche Rated
- Lead-Free


## Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The TO-220 package is universally preferred for all commercial-industrial applications at power dissipation levels to approximately 50 watts. The low thermal resistance and low package cost of the TO-220 contribute to its wide acceptance throughout the industry.



|                            |
|----------------------------|
| $V_{DS} = 150V$            |
| $R_{DS(on)} = 0.070\Omega$ |
| $I_D = 23A$                |



## Absolute Maximum Ratings

|                           | Parameter                                | Max.                   | Units |
|---------------------------|------------------------------------------|------------------------|-------|
| $I_D @ T_C = 25^\circ C$  | Continuous Drain Current, $V_{GS} @ 10V$ | 23                     | A     |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V$ | 16                     |       |
| $I_{DM}$                  | Pulsed Drain Current ①                   | 84                     |       |
| $P_D @ T_C = 25^\circ C$  | Power Dissipation                        | 94                     | W     |
|                           | Linear Derating Factor                   | 0.63                   | W/°C  |
| $V_{GS}$                  | Gate-to-Source Voltage                   | $\pm 20$               | V     |
| $E_{AS}$                  | Single Pulse Avalanche Energy②           | 350                    | mJ    |
| $I_{AR}$                  | Avalanche Current③                       | 12                     | A     |
| $E_{AR}$                  | Repetitive Avalanche Energy③             | 9.4                    | mJ    |
| dv/dt                     | Peak Diode Recovery dv/dt ③              | 2.5                    | V/ns  |
| $T_J$                     | Operating Junction and                   | -55 to + 175           | °C    |
| $T_{STG}$                 | Storage Temperature Range                |                        |       |
|                           | Soldering Temperature, for 10 seconds    | 300 (1.6mm from case ) |       |
|                           | Mounting torque, 6-32 or M3 screw        | 10 lbf•in (1.1N•m)     |       |

## Thermal Resistance


|                 | Parameter                           | Typ. | Max. | Units |
|-----------------|-------------------------------------|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case                    | —    | 1.6  | °C/W  |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface | 0.50 | —    |       |
| $R_{\theta JA}$ | Junction-to-Ambient                 | —    | 62   |       |

# IRF3315PbF

International  
IR Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

|                                 | Parameter                            | Min. | Typ.  | Max.  | Units               | Conditions                                                                  |
|---------------------------------|--------------------------------------|------|-------|-------|---------------------|-----------------------------------------------------------------------------|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | 150  | —     | —     | V                   | $V_{GS} = 0V, I_D = 250\mu A$                                               |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.187 | —     | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}, I_D = 1\text{mA}$                           |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | —     | 0.070 | $\Omega$            | $V_{GS} = 10V, I_D = 12A$ ④                                                 |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | 2.0  | —     | 4.0   | V                   | $V_{DS} = V_{GS}, I_D = 250\mu A$                                           |
| $g_{fs}$                        | Forward Transconductance             | 17   | —     | —     | S                   | $V_{DS} = 50V, I_D = 12A$                                                   |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —     | 25    | $\mu A$             | $V_{DS} = 150V, V_{GS} = 0V$                                                |
|                                 |                                      | —    | —     | 250   |                     | $V_{DS} = 120V, V_{GS} = 0V, T_J = 125^\circ\text{C}$                       |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —     | 100   | nA                  | $V_{GS} = 20V$                                                              |
|                                 | Gate-to-Source Reverse Leakage       | —    | —     | -100  |                     | $V_{GS} = -20V$                                                             |
| $Q_g$                           | Total Gate Charge                    | —    | —     | 95    | nC                  | $I_D = 12A$                                                                 |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | —     | 11    |                     | $V_{DS} = 120V$                                                             |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | —     | 47    |                     | $V_{GS} = 10V$ , See Fig. 6 and 13 ④                                        |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 9.6   | —     | ns                  | $V_{DD} = 75V$                                                              |
| $t_r$                           | Rise Time                            | —    | 32    | —     |                     | $I_D = 12A$                                                                 |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 49    | —     |                     | $R_G = 5.1\Omega$                                                           |
| $t_f$                           | Fall Time                            | —    | 38    | —     |                     | $R_D = 5.9\Omega$ , See Fig. 10 ④                                           |
| $L_D$                           | Internal Drain Inductance            | —    | 4.5   | —     | nH                  | Between lead,<br>6mm (0.25in.)<br>from package<br>and center of die contact |
| $L_S$                           | Internal Source Inductance           | —    | 7.5   | —     |                     |                                                                             |
| $C_{iss}$                       | Input Capacitance                    | —    | 1300  | —     | pF                  | $V_{GS} = 0V$                                                               |
| $C_{oss}$                       | Output Capacitance                   | —    | 300   | —     |                     | $V_{DS} = 25V$                                                              |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 160   | —     |                     | $f = 1.0\text{MHz}$ , See Fig. 5                                            |



## Source-Drain Ratings and Characteristics

|          | Parameter                              | Min.                                                                        | Typ. | Max. | Units   | Conditions                                                     |
|----------|----------------------------------------|-----------------------------------------------------------------------------|------|------|---------|----------------------------------------------------------------|
| $I_S$    | Continuous Source Current (Body Diode) | —                                                                           | —    | 23   | A       | MOSFET symbol showing the integral reverse p-n junction diode. |
| $I_{SM}$ | Pulsed Source Current (Body Diode) ①   | —                                                                           | —    | 84   |         |                                                                |
| $V_{SD}$ | Diode Forward Voltage                  | —                                                                           | —    | 1.3  | V       | $T_J = 25^\circ\text{C}, I_S = 12A, V_{GS} = 0V$ ④             |
| $t_{rr}$ | Reverse Recovery Time                  | —                                                                           | 174  | 260  | ns      | $T_J = 25^\circ\text{C}, I_F = 12A$                            |
| $Q_{rr}$ | Reverse Recovery Charge                | —                                                                           | 1.2  | 1.7  | $\mu C$ | $di/dt = 100A/\mu s$ ④                                         |
| $t_{on}$ | Forward Turn-On Time                   | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S + L_D$ ) |      |      |         |                                                                |


### Notes:

① Repetitive rating; pulse width limited by max. junction temperature. ( See fig. 11 )


② Starting  $T_J = 25^\circ\text{C}$ ,  $L = 4.9\text{mH}$   
 $R_G = 25\Omega$ ,  $I_{AS} = 12A$ . (See Figure 12)

③  $I_{SD} \leq 12A$ ,  $di/dt \leq 140A/\mu s$ ,  $V_{DD} \leq V_{(BR)DSS}$ ,  
 $T_J \leq 175^\circ\text{C}$


④ Pulse width  $\leq 300\mu s$ ; duty cycle  $\leq 2\%$ .




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance Vs. Temperature

# IRF3315PbF


International  
**IR** Rectifier




**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs. Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Case

# IRF3315PbF


International  
**IOR** Rectifier




**Fig 12a.** Unclamped Inductive Test Circuit




**Fig 12c.** Maximum Avalanche Energy Vs. Drain Current



**Fig 12b.** Unclamped Inductive Waveforms





**Fig 13a.** Basic Gate Charge Waveform



**Fig 13b.** Gate Charge Test Circuit

## Peak Diode Recovery dv/dt Test Circuit



\*  $V_{GS} = 5V$  for Logic Level Devices


**Fig 14. For N-Channel HEXFETS**

# IRF3315PbF

## TO-220AB Package Outline

Dimensions are shown in millimeters (inches)

International  
**IR** Rectifier



NOTES:  
1- DIMENSIONING AND TOLERANCING AS PER ASME Y14.5 M-1994.  
2- DIMENSIONS ARE SHOWN IN INCHES (MILLIMETERS).  
3- LEAD DIMENSION AND FLASH UNCONTROLLED IN U.S.  
4- DIMENSION D, D1 & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.  
5- CONTROLLING DIMENSION: INCHES.  
6- THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS E1, D2 & E2.  
7- DIMENSION E2 IS NOT BEYOND A ZONE WHERE STAMPING AND SOLDERING IRREGULARITIES ARE ALLOWED.  
8- OUTLINE CONFORMS TO JEDEC TO-220 EXCEPT A2 (max.) AND D2 (min.)  
9- DIMENSIONS ARE DERIVED FROM THE ACTUAL PACKAGE OUTLINE.

| SYMBOL | DIMENSIONS  |        | NOTES |
|--------|-------------|--------|-------|
|        | MILLIMETERS | INCHES |       |
| A      | 5.56        | 4.83   | 140   |
| A1     | 0.51        | 1.40   | .020  |
| A2     | 2.03        | 2.32   | .080  |
| b      | 0.38        | 1.01   | .015  |
| b1     | 0.38        | 0.97   | .015  |
| b2     | 1.54        | 1.78   | .045  |
| b3     | 1.54        | 1.73   | .045  |
| c      | 0.38        | 0.61   | .014  |
| c1     | 0.38        | 0.56   | .014  |
| D      | 14.22       | 16.51  | .560  |
| D1     | 8.38        | 9.02   | .350  |
| D2     | 11.68       | 12.88  | .460  |
| E      | 9.65        | 10.67  | .380  |
| E1     | 6.35        | 6.88   | .270  |
| E2     | -           | 0.76   | .030  |
| e      | 2.54        | .100   | .100  |
| e1     | 5.08        | .200   | .100  |
| H1     | 5.84        | 6.86   | .230  |
| L      | 12.70       | 14.73  | .500  |
| L1     | 5.56        | 4.06   | .140  |
| MP     | 3.54        | 4.08   | .139  |
| Q      | 2.54        | 3.42   | .100  |

LEAD ASSIGNMENTS

1- GATE  
2- DRAIN  
3- SOURCE


OPTIONAL DIMENSIONS

1- GATE  
2- DRAIN  
3- SOURCE

## TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010  
LOT CODE 1789  
ASSEMBLED ON WW 19, 2000  
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead - Free"



TO-220AB package is not recommended for Surface Mount Application.

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

Data and specifications subject to change without notice.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.10/09

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email       mkt@ameya360.com