Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



8058 Hook-up/Lead - Magnet Wire

Picture Not Available For more Information please call

1-800-Belden1



General Description:

Beldsol is a dual insulated Magnet Wire, combining excellent dielectric characteristics of polyurethane and toughness and solvent resistance of a nylon overcoat. Rated by IEEE tests for 270°F usage and will solder without insulation removal at 750°F.

Physical Characteristics (Overall)	
Conductor	
AWG:	
# Conductors AWG Stranding Conductor Material 1 36 Solid BC - Bare Copper	
Total Number of Conductors:	1
Insulation	<u> </u>
Insulation Material:	
Insulation Material PUR/Nylon - Polyurethane/Nylon	
Min. Increase in OD:	0 in.
Overall Cable	
Overall Maximum Diameter:	.0058
Mechanical Characteristics (Overall)	
Non-UL Temperature Rating:	130°C
Bulk Cable Weight:	0.079 lbs/1000 ft.
Approximate Length:	6400
Turns Per Linear Inch:	180.0
Turns Per Square Inch:	32400
Applicable Specifications and Agency Compli	iance (Overall)
Applicable Standards & Environmental Programs	
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	J-W-1177/9
MIL Spec Rating:	Class 130, Type SUN, Single
NEMA Specification:	NEMA-MW28-C (Single)
Plenum/Non-Plenum	

Electrical Characteristics (Overall)
Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft) 414.800

Max. Recommended Current:

Current

Page 1 of 2 01-09-2015

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



8058 Hook-up/Lead - Magnet Wire

.036 A

Breakdown Voltage:

1075 volts minimum at room temperature

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8058	1 EA	0.531 LB			#36 BELDSOL MAG WIRE

Revision Number: 2 Revision Date: 03-23-2010

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com