



## No hassle warranty

*No waiting.*

*No shipping charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

# TMD-55W

## Multilogger Thermometer with Wireless Download

Amprobe TMD-55W thermometer with wireless download capability is a professional choice for HVAC/R technicians, electricians, research, industrial process, and quality control. This model with dual inputs allows easy super-heat and sub-cool temperature measurement as well as cut-out and in temperature measurements.

Choose between models with 0.1% and 0.05% basic accuracy, single and triple displays or memory. Wireless communication is invaluable for applications requiring remote access to the instruments data.

- Backlit triple-display
- Built in memory
  - 16 sets, Maximum 1024 data points
- Data-logging:
  - 128 samples with real-time data per channel
- Easy Data Recall with up and down key: T1, T2, T1-T2, Time and Memory Location
- Thermocouple Offset Adjustment
- REC, MAX, MIN, MAX-MIN, Average, Relative Zero and HOLD functions
- Resolution 0.1°C/1°C, 0.1°F/1°F
- Warning beeper with Hi/Lo setting
- User selectable recording interval
- Real time clock with calendar



## TMD-55W Multilogger Thermometer with Wireless Download

## Data Sheet

### General Specifications

|                        |                                                                                |
|------------------------|--------------------------------------------------------------------------------|
| Display                | 4½ digit liquid crystal display (LCD) with a maximum reading of 19999.         |
| Polarity               | Automatic, positive implied, negative polarity indication.                     |
| Low Battery Indication | The "⚡" is displayed when the battery voltage drops below the operating level. |
| Auto Power Off         | 30 minutes                                                                     |
| Measurement Rate       | 2.5 times / second.                                                            |
| Operating Environment  | 0°C to 50°C (32°F to 122°F) <80% R.H.                                          |
| Storage Environment    | -20°C to 60°C (-4°F to 140°F) <70% R.H. with battery removed from meter.       |
| Accuracy               | Stated accuracy at 23°C ±5°C, <75% R.H.                                        |
| Battery                | 1.5V x 4pcs AAA size                                                           |
| Battery Life           | 120 hours                                                                      |
| Dimensions             | L241.3 X W157.98 X H76.2mm (9.5 X 6.22 X3 in)                                  |
| Weight                 | Approx. 304g (0.67lb) including batteries and packaging box.                   |

### WIRELESS Features

|                 |                                                                                                                                 |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range | 910~920MHz.<br>Low current consumption less than 1mA.<br>The transmitting distance can reach 25M without magnetic interference. |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------|



## TMD-55W Multilogger Thermometer with Wireless Download

## Data Sheet

### Electrical Specifications

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| <b>Temperature Scale</b> | User selectable Celcius or Fahrenheit               |
| <b>Measurement Range</b> | <b>Thermocouple Type Range</b>                      |
|                          | K-TYPE (0.1°) : -200°C to 1372°C (-328°F to 2501°F) |
|                          | J-TYPE (0.1°): -210°C to 1200°C (-346°F to 2192°F)  |
|                          | T-TYPE (0.1°): -200°C to 400°C (-328°F to 752°F)    |
|                          | E-TYPE (0.1°): -210°C to 1000°C (-346°F to 1832°F)  |
|                          | R-TYPE (1°): 0°C to 1767°C (32°F to 3212°F)         |
|                          | S-TYPE (1°): 0°C to 1767°C ( 32°F to 3212°F)        |
|                          | N-TYPE (0.1°): -50°C to 1300°C ( -58°F to 2372°F)   |
| <b>Accuracy</b>          | <b>K/J/T/E-TYPE</b>                                 |
|                          | ±(0.05% rdg + 0.3°C) -50°C to 1372°C                |
|                          | ±(0.05% rdg + 0.7°C) -50°C to -210°C                |
|                          | ±(0.05% rdg + 0.6°F) -58°F to 2501°F                |
|                          | ±(0.05% rdg + 1.4°F) -58°F to -346°F                |
|                          | <b>N-TYPE</b>                                       |
|                          | ±(0.05% rdg + 0.8°C) -50°C to 0°C                   |
|                          | ±(0.05% rdg + 0.4°C) 0°C to 1300°C                  |
|                          | ±(0.05% rdg + 1.6°F) -58°F to 32°F                  |
|                          | ±(0.05% rdg + 0.8°F) 32°F to 2372°F                 |
|                          | <b>R/S-TYPE</b>                                     |
|                          | ±(0.05% rdg + 2°C) 0°C to 1767°C                    |
|                          | ±(0.05% rdg + 4°F) 32°F to 3212°F                   |



## TMD-55W Multilogger Thermometer with Wireless Download

## Data Sheet



**Amprobe® Test Tools**  
website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
Everett, WA 98203  
Tel: 877-AMPROBE

**Amprobe® Test Tools**  
website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
Everett, WA 98203  
Tel: 877-AMPROBE

©2010 Amprobe Test Tools. All rights reserved.  
6/2010 TMD-55\_DS Rev A

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email      mkt@ameya360.com