




PRODUCT SPECIFICATION

HDM128GS24-1

240 x 128 GRAPHICS
LCD DISPLAY MODULE



HANTRONIX, INC. 10080 BUBB RD. CUPERTINO, CA 95014	Q.A.: JB	REV.: 1.0	HDM128GS24-1	SHEET 1 OF 10
				DATE: 12/12/97

1.MECHANICAL DATA

(1) Part Name	
(2) Module Size	170.0 (W)mm x 102.0 (H)mm x MAX 14.0 (D)mm
(3) Dot Size	0.47 (W)mm x 0.47 (H)mm
(4) Dot Pitch	0.5 (W)mm x 0.5 (H)mm
(5) Number of Dot's	240 (W) x 128 (H)Dots
(6) Duty	1/128
(7) LCD	Normally Black, Negative Type
(8) Viewing Direction	6 O'clock
(9) LCD Controller	BUILT-IN T6963C (TOSHIBA)
(10) Recommended FL Inverter	TDK CORP. CXA-L10L OR CXA-L10L-F
(11) Backlight	CCFT
(12) Weight	226.5 g

2.ABSOLUTE MAXIMUM RATINGS

(1) ELECTRICAL ABSOLUTE RATINGS

V_{SS}=0 V: Standard

ITEM	SYMBOL	MIN	MAX	UNIT	COMMENT
Power Supply for Logic	VDD-VSS	0	7.0	V	
Power Supply for LC Drive	VDD-VEE	0	24.0	V	
Input Voltage	V _I	VSS	VDD	V	
FL Driving Voltage	VFL	0	1500	V _{rms}	
FL Input Current	IFL	-	10.0	mA _{rms}	
Static Electricity	-	-	-	-	Note 1

Note 1 LCM should be grounded during handling LCM.

(2) ENVIRONMENTAL ABSOLUTE MAXIMUM RATINGS

ITEM	OPERATING		STORAGE		COMMENT
	MIN.	MAX.	MIN.	MAX.	
Ambient Temperature	0	50	-20	70	Note 2 , 3
Humidity	Note 1		Note 1		Without condensation

Note 1 Ta ≤ 50°C : 85%RH max

Ta > 50°C : Absolute humidity must be lower
than the humidity of 85%RH at 50°C

Note 2 Ta at -20°C will be < 48hrs, at 70°C will be < 120 hrs

Note 3 Background color changes slightly depending on ambient temperature.
This phenomenon is reversible.

HANTRONIX, INC. 10080 BUBB RD. CUPERTINO, CA 95014	Q.A.: JB	REV.: 1.0	HDM128GS24-1	SHEET 3 OF 10
				DATE: 12/11/97

3. ELECTRICAL CHARACTERISTICS

Ta=25°C

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Logic Circuit Power Supply	VDD-VSS	—	4.75	5.0	5.25	V
LCD Driver Power Supply	VDD-VEE	—	17.05	17.8	18.55	V
Input Voltage	VIH	H level	0.7VDD	—	VDD	V
	VIL	L level	VSS	—	0.3VDD	V
Power Consumption Power Supply	Pd	VDD = 5.0V VEE = -15V	—	—	180	mW
Supply Current (LCD)	IDD	VDD = 5.0V VEE = -15V	—	—	18.0	mA
	IEE		—	—	6.0	
FL Staring Voltage	VFLS	0°C	900	—	—	Vrms
FL Driving Frequency	fFL	—	15	30	50	KHZ

4. OPTICAL CHARACTERISTICS

Ta=25°C

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	NOTE
Viewing Angle	θ	$Cr \geq 2.0$	50	—	—	deg	NOTE 5
	ϕ		—	—	± 40		
Contrast Ratio	Cr	$\phi=0^\circ, \theta=0^\circ$	10	—	—		NOTE 6
Response Time (rise)	Tr	$\phi=0^\circ, \theta=0^\circ$	—	200	500	ms	NOTE 2
Response Time (fall)	Tf	$\phi=0^\circ, \theta=0^\circ$	—	150	300	ms	

HANTRONIX, INC.
10080 BUBB RD.
CUPERTINO, CA 95014

Q.A.:
JB

REV.:
1.0


HDM128GS24-1

SHEET 4 OF 10

DATE:
12/11/97

(NOTE 1)

Definition of Operation Voltage(Vop)



*Conditions

Viewing Angle(a1):90


Frame Frequency:70Hz

Appling Waveform: 1/N duty 1/a bias
SELECTED WAVEFORM

$V_{op} = V_{DD} - V_{EE}$

(NOTE 2)

Definition of Response Time(Tr,Tf)



*Conditions

Operating Voltage: Vth


Viewing Angle(a1):90

Frame Frequency:70Hz

Appling Waveform: 1/N duty 1/a bias
SELECTED WAVEFORM

(NOTE 3)

Description of Measuring Equipment and Driving Waveforms



HANTRONIX, INC.
10080 BUBB RD.
CUPERTINO, CA 95014

Q.A.:

JB

REV.:

1.0

HDM128GS24-1


SHEET 5 OF 10

DATE:

12/11/97


(NOTE 4)

Definition of Viewing Direction



(NOTE 5)

Definition of Viewing Angle(a1,b1)



*Conditions


Operating Voltage: Vth

Frame Frequency: 70Hz

Applying Waveform: 1/N duty 1/a bias
SELECTED WAVEFORM

(NOTE 6)

Definition of Contrast Ratio (Cr)



*Conditions

Operating Voltage: Vth

Temperature : 25

Viewing Angle(a1) : 90

Frame Frequency: 70Hz

Applying Waveform: 1/N duty 1/a bias
SELECTED WAVEFORM

Contrast Ratio: $Cr = a/b$

HANTRONIX, INC.
10080 BUBB RD.
CUPERTINO, CA 95014

Q.A.:
JB

REV.:
1.0

HDM128GS24-1

SHEET 6 OF 10

DATE:
12/11/97

6.INTERNAL PIN CONNECTION

PIN NO.	SYMBOL	FUNCTION
1	FGND	FRAME GROUND (0V)
2	GND	GROUND
3	VDD	POWER SUPPLY FOR LOGIC (+5V)
4	VEE	POWER SUPPLY FOR LC DRIVING
5	$\overline{WR}$	DATA WRITE
6	$\overline{RD}$	DATA READ
7	$\overline{CE}$	CHIP ENABLE
8	C/D	$\overline{WR}$ ="L",C/D="H" : COMMAND WRITE $\overline{WR}$ ="L",C/D="L" : DATA WRITE $\overline{RD}$ ="L",C/D="H" : STATUS READ $\overline{RD}$ ="L",C/D="L" : DATA READ
9	NC	NO CONNECTION
10	$\overline{RESET}$	CONTROLLER RESET
11	D0	DATA INPUT/OUTPUT
12	D1	DATA INPUT/OUTPUT
13	D2	DATA INPUT/OUTPUT
14	D3	DATA INPUT/OUTPUT
15	D4	DATA INPUT/OUTPUT
16	D5	DATA INPUT/OUTPUT
17	D6	DATA INPUT/OUTPUT
18	D7	DATA INPUT/OUTPUT
19	FS	FONT SELECT CONNECT TO VDD : 6X8 PIXELS/CHARACTER CONNECT TO GND : 8X8 PIXELS/CHARACTER
20	RV	DISPLAY DATA REVERSE RV=H : REVERSE DISPLAY RV=L : NORMAL DISPLAY

FL CONNECTOR : J.A.E./IL-G-5S-S3C2

PIN NO.	SYMBOL	FUNCTION
1	VFL	POWER SUPPLY FOR FL DRIVE
2	NC	NO CONNECTION
3	NC	NO CONNECTION
4	NC	NO CONNECTION
5	VFL	POWER SUPPLY FOR FL DRIVE

HANTRONIX, INC.
10080 BUBB RD.
CUPERTINO, CA 95014

Q.A.:
JB


REV.:
1.0

HDM128GS24-1

SHEET 7 OF 10


DATE: 12/11/97

7. POWER SUPPLY




$$R1 + VR + R2 = 10K \sim 20K$$

8-2 POWER ON/OFF TIMING



The missing pixels may occur when the LCM is driven beyond above power interface timing sequence.

HANTRONIX, INC. 10080 BUBB RD. CUPERTINO, CA 95014	Q.A.: JB	REV.: 1.0	HDM128GS24-1	SHEET 9 OF 10
				DATE: 12/11/97



HANTRONIX, INC.
10080 BUBB RD.
CUPERTINO, CA 95014

Q.A.:
JB

REV.:
1.0

HDM128GS24-1

SHEET 10 OF 10

DATE:
12/11/97

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com