



SCHEMATIC

MATERIALS:

Center Contact – Gold Plated Beryllium Copper with Teflon insulation.

Resistor Terminator

Dielectric: PTFE

RATING:

Operating Voltage: 335 VRMS Max.

Operating Temperature: -65°C to +125°C

Nominal Impedance: 50 Ohms

VSWR:

DC – 4 GHz :1.05:1 Max.

4 – 8 GHz :1.10:1 Max.

8 – 12 GHz :1.15:1 Max.

12 – 18 GHz :1.25:1 Max.

Frequency Range: DC to 18.0 GHz

Power: 1 Watt

ORDERING INFORMATION: Model 4286

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com