

BLUE (WHITE DIFFUSED) LED OPERATING CHARACTERISTICS AT TA=25°C					
CHARACTERISTICS	MIN	TYP	MAX	UNITS	TEST COND.
FORWARD VOLTAGE		3.5	4.1	V	I _F =10 mA
PEAK WAVELENGTH		428		nm	
DOMINANT WAVELENGTH	462	465	468	nm	
LUMINOUS INTENSITY	7.1	12.5	18	mcd	I _F =10 mA
VIEWING ANGLE		70		DEG	

BLUE (WHITE DIFFUSED) LED		
ABSOLUTE MAXIMUM RATING AT 25 °C AMBIENT		UNITS
POWER DISSIPATION	90	mW
CONTINUOUS FORWARD CURRENT	20	mA
DERATE LINEARLY FROM 55°C	0.44	mA/°C
PEAK PULSE CURRENT, 10μs PULSE	120	mA
REVERSE VOLTAGE	5	V
LEAD SOLDERING TEMPERATURE, 5 SEC., 1/16" FROM BASE	260	°C
OPERATING TEMPERATURE	-55 TO +100	°C
STORAGE TEMPERATURE	-55 TO +100	°C

REV	ECN NO	REVISIONS	DRN	CKD	APP	DATE
A	—	NEW RELEASE	KLJ			




YELLOW/GREEN BI-COLOR LED OPERATING CHARACTERISTICS AT TA=25°C						
CHARACTERISTICS	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
FORWARD VOLTAGE	YELLOW GREEN		2.1	2.8	V	I _F =20 mA
PEAK WAVELENGTH	YELLOW GREEN		585 565		nm	
DOMINANT WAVELENGTH	YELLOW (Y2) YELLOW (Y3) GREEN	583 585	569	587 589	nm	MEASURED ON EXELTRON 2001
LUMINOUS INTENSITY	YELLOW GREEN	2.5	6.3 4.3		mcd	I _F =10 mA
VIEWING ANGLE	YELLOW GREEN		80		DEG	I _F =20 mA

YELLOW/GREEN BI-COLOR LED			
ABSOLUTE MAXIMUM RATING AT 25 °C AMBIENT		GREEN	YELLOW
POWER DISSIPATION	100	60	mW
CONTINUOUS FORWARD CURRENT	30	20	mA
DERATE LINEARLY FROM 50°C	0.40	0.25	mA/°C
PEAK PULSE CURRENT, 10μs PULSE	120	80	mA
LEAD SOLDERING TEMPERATURE, 5 SEC., 1/16" FROM BASE	260		°C
OPERATING TEMPERATURE	-55 TO +100		°C
STORAGE TEMPERATURE	-55 TO +100		°C


NOTES:

1. LEADS TO FIT INTO HOLES SPACED AS PER HOLE PATTERN.
2. PIN NUMBERS FOR REFERENCE ONLY. DESIGNATION NON-EXISTENT ON PART.
3. LED LEAD DIMENSIONS SHOWN ARE MEASURED AT HOUSING EXIT.
4. DIALIGHT PART NUMBER: 553-0748-857F.
5. THIS ASSEMBLY CONTAINS ELECTROSTATIC DISCHARGE SENSITIVE DEVICES (ESDS). MAINTAIN ALL PRECAUTIONARY MEASURES DURING ASSEMBLY, HANDLING, AND STORAGE IN ACCORDANCE WITH IPC-A-610.

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE: DRAWING SCALE ALL DIM'S IN: INCHES (MM)	DRAWING NUMBER C-17566	REV A
TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: ±1/64 DECIMALS (.XX): ±.01 DECIMALS (.XXX): ±.005 DECIMALS (.XXXX): ±.0005 ANGLES: ±1°	TITLE 3mm LED BI-LEVEL CBI RoHS COMPLIANT	
FINISH:	MATERIAL	
FSCM 83330	Dialight 1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727	
	SHEET 11 OF 11	FAMILY TABLE:



RECOMMENDED PC BOARD HOLE PATTERN



RoHS Compliant 553-0748-857F

Part Numbers with the "F" suffix ending are RoHS Compliant. Reel and bag packaging are marked with "RoHS Compliant" label or equivalent markings. These parts can be used with RoHS reflow profile. Parts can be wave soldered, dip soldered or hand soldered using typical lead-free soldering process with max 260°C temp. for 5 sec.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com