

MICRO SWITCH™
General Purpose Limit Switches
SZL-WL Series



MICRO SWITCH™ SZL-WL Series

General Purpose Limit Switches

MICRO SWITCH™ SZL-WL Series general purpose limit switches are cost effective switches that may be used in a wide range of applications from general purpose conveyors to heavy-duty machinery. Rugged and reliable, the SZL-WL Series switches are specially designed for world-wide use and supported by Honeywell's vast experience in serving industries around the globe.

High quality product offerings combined with Honeywell's global sales and service resources makes the SZL-WL Series the smart choice for industries whose goal is to minimize plant downtime and reduce overall maintenance costs.

What makes our switches better?

- Small size and universal mounting footprint typically allows for use in constricted spaces and reduces replacement costs by providing interchangeability with similar style switches
- Wide variety of actuator heads and an assortment of actuators typically allows the SZL-WL Series to be applied in many types of applications
- IP67 construction often allows for use in dusty and dirty indoor and outdoor applications
- Mechanical service life of up to 10,000,000 operations promotes the durability required for use in many types of industries from factory floor to agriculture and/or machinery



COST OPTIMIZATION • EASE OF USE
RELIABILITY • GLOBAL ACCEPTANCE

Features and Benefits

INDUSTRIAL GLOBAL DESIGN

The SZL-WL Series is designed to the EN50041 mounting standard which promotes interchangeability between other brands of limit switches.

Robust and reliable.

TWO CIRCUIT DOUBLE BREAK CONTACTS

The SZL-WL Series promotes reliable switching under industrial 10 amp current loads and typically allows end users the ability to control two circuits within one switch.

WIDE CHOICE OF ACTUATORS

Honeywell's SZL-WL Series offers side rotary, top and side plunger, and wobble stick style actuators that makes the switch reasonably adaptable to numerous types of applications.

OIL TIGHT, WATER TIGHT, DUST TIGHT

IP67 sealing protects against dust and moisture, and allows the SZL-WL Series to be used in dirty and rugged environments found in both indoor and outdoor applications.

Potential Applications



INDUSTRIAL

- Counting and position sensing on conveyors and assembly lines
- Fixture and tooling position sensing on automated metal removing machines
- Position indication on electric valves on pipelines
- Position indication on dampers, fume hoods, and HVAC/R equipment
- Truck ramp position and elevator car position/leveling control



SZL-WL Series

PRODUCT NOMENCLATURE

Figure 1. SZL-WL for Asia-Pacific Use Only





Figure 2. SZL-WL for North American Use Only



MICRO SWITCH™ General Purpose Limit Switches

Table 1. Chart A • Standard Type

	WL-A	WL-B ¹	WL-C ²	WL-D, P	WL-E	WL-F	WL-G
Pretravel	15° ±5°	15° ±5°	15° ±5°	50° ±5°	1,7 mm [0.07 in] max.	1,7 mm [0.07 in] max.	1,7 mm [0.07 in] max.
Differential Travel	12°	12°	12°	–	1 mm [0.04 in]	1 mm [0.04 in]	1 mm [0.04 in]
Overtravel	30°	30°	30°	35°	5,6 mm [0.22]	6,4 mm [0.25]	5,6 mm [0.22]
Total travel	40°	40°	40°	90°	–	–	–
Operating torque	0,51 Nm [4.5 in-lb]	0,51 Nm [4.5 in-lb]	0,195 Nm [1.72 in-lb]	0,447 Nm [4.0 in-lb]	26,67 N [6 lb] (force)	26,67 N [6 lb] (force)	16,67 N [3.75 lb] (force)

	WL-H	WL-I	WL-J	WL-K ³	WL-L ³	WL-M ³	WL-N ³
Pretravel	2,8 mm [0.11 in]	1,7 mm [0.07 in] max.	2,8 mm [0.11 in] max.	20 mm ±10 mm [0.79 in ±0.039 in]	20 mm ±10 mm [0.79 in ±0.039 in]	40 mm ±20 mm [1.57 in ±0.79 in]	40 mm ±20 mm [1.57 in ±0.79 in]
Differential travel	1 mm [0.04 in]	1 mm [0.04 in]	1 mm [0.04 in]	–	–	–	–
Overtravel	5,6 mm [0.22 in]	6,4 mm [0.25 in]	4,0 mm [0.16 in]	–	–	–	–
Total travel	8,4 mm [0.33 in]	9,2 mm [0.36 in]	5,7 mm [0.22 in]	–	–	–	–
Operating force max.	40,03 N [9 lb]	26,67 N [6 lb]	40,03 N [9 lb]	1,47 N [0.33 lb]	1,47 N [0.33 lb]	1,47 N [0.33 lb]	0,28 N [0.06 lb]

¹ Operating characteristics of the WL-B are measured at the arm length of 38 mm [1.5 in]

² Operating characteristics of the WL-C are measured at the lever length of 140 mm [5.5 in]

³ Operating characteristics of these types are measured at the tip of the actuator

Table 2. Chart B • Overtravel/High Precision Type

	WLA-A	WLB-A	WLA-B ¹	WLB-B ¹	WLA-C ²	WLB-C ²	WLC-A
Pretravel	18° ±4°	10° (-1°/+2°)	18° ±4°	10° (-1°/+2°)	18° ±4°	10° (-1°/+2°)	25° ±5°
Differential travel	10°	7°	10°	–	10°	7°	16°
Overtravel	55°	65°	55°	65°	55°	65°	60°
Total travel	80°	80°	80°	80°	80°	80°	90°
Operating torque max.	0,37 Nm [3.3 in-lb]	0,37 Nm [3.3 in-lb]	0,37 Nm [3.3 in-lb]	0,37 Nm [3.3 in-lb]	0,398 Nm [3.52 in-lb]	0,398 Nm [3.52 in-lb]	0,34 Nm [3.0 in-lb]

	WLC-B ¹	WLC-C ²	WLD-A	WLD-B ¹	WLD-C ²	WLE-A	WLE-B	WLE-C
Pretravel	25° ± 5°	25° ± 5°	20° max.	20° max.	20° max.	6° ±1°	5° (+2°/-0°)	5° (+2°/-0°)
Differential travel	16°	16°	10°	10°	10°	3°	3°	3°
Overtravel	60°	60°	70°	70°	70°	40°	40°	40°
Total travel	90°	90°	90°	90°	90°	40°	40°	40°
Operating torque max.	0,34 Nm [3.0 in-lb]	0,36 Nm [3.16 in-lb]	0,365 Nm [3.23 in-lb]	0,365 Nm [3.23 in-lb]	0,398 Nm [3.52 in-lb]	0,51 Nm [4.5 in-lb]	0,51 Nm [4.5 in-lb]	0,195 Nm [1.72 in-lb]


¹ Operating characteristics are measured at the arm length of 38 mm [1.5 in]

² Operating characteristics are measured at the lever length of 140 mm [5.5 in]

SZL-WL Series

Table 3. Specifications

Characteristic	Parameter
Product type	Honeywell General Purpose Limit Switch
Actuators	side rotary, top roller plunger, top plunger, sealed top roller plunger, side roller plunger, side pin plunger, top ball plunger, wobble/cat whisker, wobble/plastic rod, wobble/coil spring
Circuitry	single pole double throw double break
Electrical	10 A
Housing material	aluminum die-cast
Housing type	industrial
Conduit	PF 1/2, 1/2 in-14 NPT
Sealing	IP67
Operating temperature	-10 °C to 80 °C [14 °F to 176 °F]
Mechanical life	10,000,000 operations
Agency approvals and standards	UL, CE, CSA
Sealed	Industrial




MICRO SWITCH™ General Purpose Limit Switches

ORDER GUIDE/RECOMMENDED LISTINGS

Table 4. Product listings

O.T. • Operating torque
O.F. • Operating force
P.T. • Pretravel
O.T. • Overtravel
D.T. • Differential travel

	Part Number	Actuation	Note	O.T. Nm [in-lb]	Bar chart	P.T. (max.)	O.T.	D.T. (max.)	Conduit
	SZL-WL-A	side rotary standard lever, standard	—	0,51 [4.5]	0° 20° 50° 1-2 3-4	20°	30°	12°	PF 1/2
	SZL-WL-A-N				0° 8° 50° 3-4 1-2				1/2 in NPT
	SZL-WLA-A	side rotary standard lever, high overtravel	—	0,37 [3.3]	0° 22° 77° 1-2 3-4 0° 12° 77° 3-4 1-2	22°	55°	10°	PF 1/2
	SZL-WLB-A	side rotary standard lever, high overtravel	—	0,37 [3.3]	0° 12° 77° 1-2 3-4 0° 5° 77° 3-4 1-2	12°	65°	7°	PF 1/2
	SZL-WLC-A	side rotary standard lever, high overtravel	—	0,34 [3.0]	0° 30° 90° 1-2 3-4	30°	60°	16°	PF 1/2
	SZL-WLC-A-N				0° 14° 90° 3-4 1-2				1/2 in NPT
	SZL-WLD-A	side rotary standard lever, high overtravel	—	0,37 [3.23]	0° 20° 90° 1-2 3-4 0° 10° 90° 3-4 1-2	20°	70°	10°	PF 1/2
	SZL-WLE-A	side rotary standard lever, high precision	1	0,51 [4.5]	0° 7° 47° 1-2 3-4 0° 4° 47° 3-4 1-2	7°	40°	3°	PF 1/2


Note:

1. Operating characteristics are measured at the actuator arm length of 38 mm [1.5 in]

SZL-WL Series

O.T. • Operating torque
O.F. • Operating force
P.T. • Pretravel
O.T. • Overtravel
D.T. • Differential travel

Table 4. Product listings, continued

	Part Number	Actuation	Note	O.T. Nm [in-lb]	Bar chart	P.T. (max.)	O.T.	D.T. (max.)	Conduit
	SZL-WL-B	side rotary adjustable lever, standard	1	0,51 [4.5]	0° 20° 50° 1-2 3-4	20°	30°	12°	PF 1/2
	SZL-WL-B-N				0° 8° 50° 3-4 1-2				1/2 in NPT
	SZL-WLA-B	side rotary adjustable lever, high overtravel	1	0,37 [3.3]	0° 22° 77° 1-2 3-4 0° 12° 77° 3-4 1-2	22°	55°	10°	PF 1/2
	SZL-WLB-B	side rotary adjustable lever, high overtravel	1	0,37 [3.3]	0° 12° 77° 1-2 3-4 0° 5° 77° 3-4 1-2	12°	65°	7°	PF 1/2
	SZL-WLC-B	side rotary adjustable lever, high overtravel	1	0,34 [3.0]	0° 30° 90° 1-2 3-4	30°	60°	16°	PF 1/2
	SZL-WLC-B-N				0° 14° 90° 3-4 1-2				1/2 in NPT
	SZL-WLD-B	side rotary adjustable lever, high overtravel	1	0,37 [3.23]	0° 20° 90° 1-2 3-4 0° 10° 90° 3-4 1-2	20°	70°	10°	PF 1/2
	SZL-WLE-B	side rotary adjustable lever, high precision	2	0,51 [4.5]	0° 5° 45° 1-2 3-4 0° 2° 45° 3-4 1-2	5°	40°	3°	PF 1/2





Notes:

1. Operating characteristics are measured at the actuator arm length of 38 mm [1.5 in]
2. Operating characteristics are measured at the actuator arm length of 140 mm [5.5 in]

MICRO SWITCH™ General Purpose Limit Switches

O.T. • Operating torque
O.F. • Operating force
P.T. • Pretravel
O.T. • Overtravel
D.T. • Differential travel

Table 4. Product listings, continued

	Part Number	Actuation	Note	O.T. Nm [in-lb]	Bar chart	P.T. (max.)	O.T.	D.T. (max.)	Conduit
	SZL-WL-C	side rotary rod adjustable, standard	2	0,195 [1.72]	0° 20° 50° 1-2 3-4	20°	30°	12°	PF 1/2
	SZL-WL-C-N				0° 8° 50° 3-4 1-2				1/2 in NPT
	SZL-WLA-C	side rotary rod adjustable, high overtravel	2	0,398 [3.52]	0° 22° 77° 1-2 3-4 0° 12° 77° 3-4 1-2	22°	55°	10°	PF 1/2
	SZL-WLB-C	side rotary rod adjustable, high overtravel	2	0,398 [3.52]	0° 12° 77° 1-2 3-4 0° 5° 77° 3-4 1-2	12°	65°	7°	PF 1/2
	SZL-WLC-C	side rotary rod adjustable, high overtravel	2	0,38 [3.16]	0° 30° 70° 1-2 3-4	30°	40	16°	PF 1/2
	SZL-WLC-C-N				0° 14° 70° 3-4 1-2				1/2 in NPT
	SZL-WLD-C	side rotary rod adjustable, high overtravel	2	0,398 [3.52]	0° 20° 90° 1-2 3-4 0° 10° 90° 3-4 1-2	20°	70°	10°	PF 1/2
	SZL-WLE-C	Side rotary rod adjustable, high precision	1	0,195 [1.72]	0° 5° 45° 1-2 3-4 0° 2° 45° 3-4 1-2	5°	40°	3°	PF 1/2
	SZL-WL-D SZL-WL-P	fork lock lever, opposite direction rollers (-D); same direction rollers (-P)  		0,447 [4.0]	0° 55° 90° 1-2 3-4 0° 55° 90° 3-4 1-2	55°	35°	–	PF 1/2















Notes:

- Operating characteristics are measured at the actuator arm length of 38 mm [1.5 in]
- Operating characteristics are measured at the actuator arm length of 140 mm [5.5 in]

SZL-WL Series

O.T. • Operating torque
O.F. • Operating force
P.T. • Pretravel
O.T. • Overtravel
D.T. • Differential travel


Table 4. Product listings, continued

	Part Number	Actuation	Note	O.F. N [lb]	Bar chart	P.T. (max.)	O.T.	D.T. (max.)	Conduit
	SZL-WL-E	top roller plunger	–	26,67 [6.0]		1,7 mm [0.07 in]	5,6 mm [0.22 in]	1 mm [0.04 in]	PF 1/2
	SZL-WL-E-N								1/2 in NPT
	SZL-WL-F	top plunger	–	26,67 [6.0]		1,7 mm [0.07 in]	6,4mm [0.25 in]	1 mm [0.04 in]	PF 1/2
	SZL-WL-F-N								1/2 in NPT
	SZL-WL-G	top roller plunger, sealed	–	16,67 [3.75]		1,7 mm [0.07 in]	5,6 mm [0.22 in]	1 mm [0.04 in]	PF 1/2
	SZL-WL-H	side roller plunger	–	40,03 [9.0]		2,8 mm [0.11 in]	5,6 mm [0.22 in]	1 mm [0.04 in]	PF 1/2
	SZL-WL-I	top ball plunger	–	26,67 [6.0]		1,7 mm [0.07 in]	4 mm [0.157 in]	1 mm [0.04 in]	PF 1/2
	SZL-WL-J	side plunger	–	40,03 [9.0]		2,8 mm [0.11 in]	6,4 mm [0.25 in]	1 mm [0.04 in]	PF 1/2

MICRO SWITCH™ General Purpose Limit Switches

O.T. • Operating torque
O.F. • Operating force
P.T. • Pretravel
O.T. • Overtravel
D.T. • Differential travel

Table 4. Product listings, continued

	Part Number	Actuation	Note	O.F. N [lb]	Bar chart	P.T. (max.)	O.T.	D.T. (max.)	Conduit
	SZL-WL-K	wobble-coil spring Ø 6,5 mm [Ø 0.256 in]	3, 4	1,47 [0.33]	–	20 mm ±10 mm [0.79 in ±0.39 in]	–	–	PF 1/2
	SZL-WL-K-N								1/2 in NPT
	SZL-WL-L	wobble-coil spring Ø 4,8 mm [Ø 0.189 in]	3, 4	1,47 [0.33]	–	20 mm ±10 mm [0.79 in ±0.39 in]	–	–	PF 1/2
	SZL-WL-M	wobble-plastic rod Ø 8,0 mm [Ø 0.315 in]	3, 4	1,47 [0.33]	–	40 mm ±20 mm [1.57 in ±0.79 in]	–	–	PF 1/2
	SZL-WL-N	wobble-steel wire Ø 1,0 mm [Ø 0.04 in]	3, 4	0,28 [0.06]	–	40 mm ±20 mm [1.57 in ±0.79 in]	–	–	PF 1/2

Notes:

1. Operating characteristics are measured at the actuator arm length of 38 mm [1.5 in]
2. Operating characteristics are measured at the actuator arm length of 140 mm [5.5 in]
3. Operating characteristics are measured at the tip of the actuator
4. Operating force is measured from the tip of the wobble

DIMENSIONS mm [in]

[illegible]

Technical drawing of the KS B 0221 (PF 1/2) cover mounting screw assembly. The drawing shows three views: a front view, a side view, and a top view.

Front View Dimensions:

- Top width: 67,0 mm [2.64 in] max.
- Adjustable range: 25 mm to 89 mm [1.0 in to 3.5 in]
- 4 - M3.5 x 27.5 head mounting screw and spring washer
- M5 x 16 hexagon socket head bolts
- 4 - Ø 5,20 mm [0.21 in] mounting holes
- 3 - M4 x 13 cover mounting screw
- Adjustable plate
- Cover
- LABEL POSITION
- KS B 0221 (PF 1/2) 4 threads min.
- 4 - M6 x 1,0 15 depth min.

Side View Dimensions:

- 13,1 mm [0.52 in]
- 25,4 mm [1.00 in]
- 12,7 mm [0.50 in]
- 25,4 mm [1.00 in]
- 13,0 mm [0.51 in]
- 68,7 mm [2.70 in]
- 94,1 mm [3.70 in]
- 5,0 mm [0.20 in]
- 21,6 mm [0.85 in]
- 29,2 mm [1.15 in]
- 35,0 mm [1.38 in]
- 41,5 mm [1.63 in] max.

Top View Dimensions:

- 14,7 mm [0.58 in]
- 58,7 mm [2.31 in]
- 5,0 mm [0.20 in]
- 15,1 mm [0.59 in]
- 30,2 mm [1.19 in]
- 40,0 mm [1.57 in]
- Ø 18,0 mm [Ø 0.71 in]
- 45°
- 25°
- 25°
- 45°

[illegible]

Technical drawing of the SZL-WL-D and SZL-WL-P limit switches, showing dimensions in millimeters (mm) and inches (in).

Left View (SZL-WL-D):

- Ø 17.5 mm x 7 mm [Ø 0.69 in x 0.28 in] stainless steel roller
- 90°
- 4 - M3.5 x 27.5 head mounting screw and spring washer
- M5 x 16 hexagon socket head bolts
- 4 - Ø 5.20 mm [Ø.21 in] mounting holes
- 3 - M4 x 13 cover mounting screw
- Labels: **Handyroll**, **LIMIT SWITCH**, **SZL-WL-D**, **10A 125-250V AC**, **0.4A 120VAC**, **0.4A 200VAC**, **VAMP 125VAC**, **WP 200VAC**
- Dimensions: 14.7 mm [0.58 in], 58.7 mm [2.31 in], 5.0 mm [0.20 in], 4.9 mm [0.19 in], 30.2 mm [1.19 in], 40.0 mm [1.57 in], 15.1 mm [0.59 in]

Right View (SZL-WL-P):

- 62.5 mm [2.46 in] max.
- 56.4 mm [2.22 in]
- 42.8 mm [1.69 in]
- 13.1 mm [0.52 in]
- 25.4 mm [1.00 in]
- 12.7 mm [0.50 in]
- 31.4 mm [1.24 in]
- 68.7 mm [2.70 in]
- 5.0 mm [0.20 in]
- 21.6 mm [0.85 in]
- 29.2 mm [1.15 in]
- 35.0 mm [1.38 in]
- 41.5 mm [1.63 in] max.
- 4 - M6 x 1.0 15 depth min.
- Label: **LABEL POSITION**
- Cover
- KS B 0221 (PF 1/2) 4 threads min.

Bottom Views:

- SZL-WL-D** (Left)
- SZL-WL-P** (Right)

MICRO SWITCH™ General Purpose Limit Switches

DIMENSIONS mm [in]

Figure 5. SZL-VL-E




Figure 6. SZL-WL-F




Figure 7. SZL-WL-G





Figure 8. SZL-WL-H



SZL-WL Series

DIMENSIONS mm [in]

Figure 9. SZL-WL-I




Figure 10. SZL-WL-J




Figure 11. SZL-WL-K





Figure 12. SZL-WL-L



MICRO SWITCH™ General Purpose Limit Switches

DIMENSIONS mm [in]

Figure 13. SZL-WL-M





Figure 14. SZL-WL-N




SET POSITION INDICATOR

Proper Operation Zone

- The two convex indicators on the shaft housing show the operating zones for proper operation, thereby, simplifying installation and maintenance.
- Too much over-travel may cause shortened mechanical life due to possible damage to the switch mechanism.

Figure 15. Side Rotary Proper Operation Zone



MOUNTING DIMENSIONS

Figure 16. Surface Mount




Figure 17. Through-Hole Mount





Figure 18. Rear Mount




ADJUSTABLE OPERATING CHARACTERISTICS

Standard/High Precision Series

- All side rotary switches of Standard and High Precision models can be set to actuate on one side only. Clockwise and counterclockwise mode is available by rotating the plunger inside the operating head as shown below.

Figure 19. Standard/High Precision Type Switches




MICRO SWITCH™ General Purpose Limit Switches

OVERTRAVEL “D” SERIES

- The Overtravel “D” Series switches can be set to one side actuation mode by rotating the cam located inside the operating head as shown below.

Figure 20. Overtravel “D” Series



OPERATING HEAD DIRECTION CHANGE

90° Incremental Rotation

- Most SZL-WL –D, P, E, G, H, and J Series switches allow for the operating head to be rotated to any of the four positions indicated below. Loosen the four head lock screws and rotate the head to the desired position.

Note* The head of the Overtravel “D” Series can be set **ONLY** to directions **1** and **3**.

Figure 21. SZL-WL Head Rotation




Figure 24. ZLC-4DSM-



SZL-WL Series

SEAL CONNECTOR

Product Nomenclature





Figure 25. LSC-09C-PFT



MICRO SWITCH™ General Purpose Limit Switches

ADDITIONAL INFORMATION

The following associated literature is available on the Web at sensing.honeywell.com:

- Product installation instructions
- Product range guide
- Product nomenclature tree
- Product application-specific information
 - Application Note: Application in Injection Molding Machine (IJM)

This Honeywell datasheet supports the following MICRO SWITCH™ SZL-WL Series listings:

SZL-WL-A	SZL-WLD-B	SZL-WL-G
SZL-WL-A-N	SZL-WLE-B	SZL-WL-H
SZL-WL-B-N	SZL-WL-C	SZL-WL-I
SZL-WL-C-N	SZL-WLA-C	SZL-WL-J
SZL-WL-E-N	SZL-WLB-C	SZL-WL-K
SZL-WL-F-N	SZL-WLC-A-N	SZL-WL-L
SZL-WLA-A	SZL-WLC-B-N	SZL-WL-M
SZL-WLB-A	SZL-WLC-C	SZL-WL-N
SZL-WLC-A	SZL-WLC-C-N	SZL-WL-P
SZL-WLD-A	SZL-WLD-C	SZL-WL-A-LEVER
SZL-WLE-A	SZL-WLE-C	SZL-WL-A-LEVER-P
SZL-WL-B	SZL-WL-D	SZL-WL-B-LEVER
SZL-WLA-B	SZL-WL-E	SZL-WL-B-LEVER-P
SZL-WLB-B	SZL-WL-F	SZL-WL-C-LEVER
SZL-WLC-B		

WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell website, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

Find out more

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office.

To learn more about Honeywell's sensing and control products, call **+1-815-235-6847** or **1-800-537-6945**, visit **sensing.honeywell.com**, or e-mail inquiries to **info.sc@honeywell.com**

Sensing and Control
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422
honeywell.com

The Honeywell logo, consisting of the word "Honeywell" in a bold, red, sans-serif font.

002392-1-EN IL50 GLO
January 2015
Copyright © 2015 Honeywell International Inc. All rights reserved.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com