

4-CH Bidirectional Low Capacitance ESD Protection Device with 15kV Contact and Ultra Low Clamping Voltage

Check for Samples: [TPD4E101](#)

FEATURES

- Provides System Level ESD Protection for Low-voltage IO Interface
- IEC 61000-4-2 Level 4
 - $\pm 15\text{kV}$ (Air discharge)
 - $\pm 15\text{kV}$ (Contact discharge)
- IEC 61000-4-5 (Surge): 3A (8/20 μs)
- IO Capacitance 4.8pF (Typ)
- R_{DYNAMIC} 0.45 Ω (Typ)
- DC Breakdown Voltage $\pm 6\text{V}$ (Min)
- Ultra low Leakage Current 100nA (Max)
- 10V Clamping Voltage (Max at $I_{\text{pp}} = 1\text{A}$)
- Industrial Temperature Range: -40°C to 125°C
- Space Saving DPW package (0.8mm x 0.8mm)

APPLICATIONS


- Cell Phones
- eBook
- Portable Media Players
- Digital Camera
- Tablet PC
- Set Top Box

DEVICE CONFIGURATION

DESCRIPTION

The TPD4E101 is a four channel ESD protection device in an ultra small DPW package. It is the industry's smallest 4-ch ESD protection device with 0.48mm pitch. This larger pitch helps save on PCB manufacturing costs. The device provides IEC61000-4-2 compliance up to 15kV contact discharge. It has an ESD clamp circuit with back-to-back diodes for bipolar/bidirectional signal support. The 7pF line capacitance is suitable for a wide range of applications supporting data rate up to 700Mbps. Typical application areas in portable applications are:

- Audio lines (Microphone, Earphone and Speakerphone)
- SD interface
- SIM interface
- Keypad or other buttons



0.8 mm x 0.8mm DPW Package
(Bottom View)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

ORDERING INFORMATION

For the most current packaging and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.

ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted)

	MIN	MAX	UNIT
Operating temperature range	–40	125	°C
Storage temperature	–65	155	°C
IEC 61000-4-2 Contact Discharge		±15	kV
IEC 61000-4-2 Air-gap Discharge		±15	kV
Peak Pulse Current (tp = 8/20 µs)		3	A
Peak Pulse Power (tp = 8/20 µs)		40	W

ELECTRICAL CHARACTERISTICS

T_A = –40°C to 125°C (unless otherwise specified)


PARAMETER	TEST CONDITION	MIN	TYP	MAX	UNIT
V _{RWM} Reverse stand-off voltage				±5.5	V
I _{LEAK} Leakage current	Pins = 5 V, GND = 0 V			100	nA
VClamp1,2 Clamp voltage from data pin to ground pin	I _{PP} = 1 A, 8/20 µs ⁽¹⁾		10		V
	I _{PP} = 3 A, 8/20 µs ⁽¹⁾		13		V
VClamp2,1 Clamp voltage from ground pin to data pin	I _{PP} = 1 A, 8/20 µs ⁽¹⁾		9		V
	I _{PP} = 3 A, 8/20 µs ⁽¹⁾		13		V
R _{DYN} Dynamic resistance	Pins to GND ⁽²⁾		0.45		Ω
	GND to Pins ⁽²⁾		0.42		Ω
C _{IO} IO Capacitance	V _{IO} = 2.5 V		4.8	7	pF
V _{BRF} Break-down voltage, pin 1, 2, 3, or 4 to GND	I _{IO} = 1 mA	6			V
V _{BRR} Break-down voltage, GND to pin 1, 2, 3, or 4	I _{IO} = 1 mA	6			V

(1) Non-repetitive current pulse 8/20 us exponentially decaying waveform according to IEC61000-4-5

(2) Extraction of RDYN using least squares fit of TLP characteristics between I=10A AND I=20A

BOARD LAYOUT RECOMMENDATION

3 mil trace
routing



4 mil trace
routing





Figure 1. IEC 61000-4-2 Clamping Voltage, +8kV Contact




Figure 2. IEC 61000-4-2 Clamping Voltage, -8kV Contact




Figure 3. TLP, $t_{PW} = 100\text{ns}$, $t_{RISE} = 10\text{ns}$, Data to GND




Figure 4. TLP, $t_{PW} = 100\text{ns}$, $t_{RISE} = 10\text{ns}$, GND to Data




Figure 5. IV Curve




Figure 6. Surge Curves, Data to GND




Figure 7. Surge Curves, GND to Data




Figure 8. Capacitance




Figure 9. Insertion Loss

REVISION HISTORY

Changes from Original (August 2012) to Revision A	Page
---	------

- | | |
|---|---|
| • Revised document to release full version of Datasheet. | 1 |
|---|---|
-

Changes from Revision A (January 2013) to Revision B	Page
--	------

- | | |
|---|---|
| • Updated PARAMETER wording for VClamp1,2 and VClamp2,1 | 2 |
|---|---|
-

Changes from Revision B (May 2013) to Revision C	Page
--	------

- | | |
|--|---|
| • Updated first page formatting. | 1 |
| • Removed Ordering Information table | 1 |
| • Changed VClamp1,2 Test Condition From: $I_{PP} = 5\text{ A}$, 8/20 μs To: $I_{PP} = 3\text{ A}$, 8/20 μs | 2 |
| • Changed VClamp2,1 Test Condition From: $I_{PP} = 5\text{ A}$, 8/20 μs To: $I_{PP} = 3\text{ A}$, 8/20 μs | 2 |
-

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TPD4E101DPWR	ACTIVE	X2SON	DPW	4	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	A1	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPD4E101DPWR	X2SON	DPW	4	3000	180.0	9.5	0.91	0.91	0.5	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPD4E101DPWR	X2SON	DPW	4	3000	180.0	180.0	30.0

DPW (S-PX2SON-N4)

PLASTIC SMALL OUTLINE NO-LEAD



4211218/C 05/11

- NOTES:
- All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - This drawing is subject to change without notice.
 - SON (Small Outline No-Lead) package configuration.
 - The package thermal pad must be soldered to the board for thermal and mechanical performance.
 - See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.

THERMAL PAD MECHANICAL DATA

DPW (S-PX2SON-N4)


PLASTIC SMALL OUTLINE NO-LEAD

THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.




Exposed Thermal Pad Dimensions

4211578/G 07/13

NOTES: All linear dimensions are in millimeters

DPW (S-PX2SON-N4)

PLASTIC SMALL OUTLINE NO-LEAD



- NOTES:
- All linear dimensions are in millimeters.
 - This drawing is subject to change without notice.
 - Publication IPC-7351 is recommended for alternate designs.
 - Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads.
 - Maximum stencil thickness 0,127 mm (5 mils). All linear dimensions are in millimeters.
 - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
 - Side aperture dimensions over-print land for acceptable area ratio > 0.66. Customer may reduce side aperture dimensions if stencil manufacturing process allows for sufficient release at smaller opening.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com