

Audio Coupling

Miniature Encapsulated Transformer

MET-31-T

Description:

Triad's high reliability audio transformers provide the durability and precision required in today's demanding designs. These transformers are available for a wide variety of applications.

MET-31-7 1-3 6000 CT 4-6 6000 CT

Electrical Specifications (@20C)

Power	Matching Impedance		Max. Ma DC	DC Resistance (Ω)		Overall
level	Primary	Secondary	Unbalance	Primary	Secondary	Turns
(mW)			in Primary			Ratio
50	600Ω CT	600Ω CT	3.0	70	95	1.0:1.0


Frequency Response: ± 2.0 dB, at 300 Hz to 100K Hz (1 KHz Ref.)

Longitudinal Balance: 60dB Min @ 1 KHz

Pri-Sec Hipot test (Pri-Sec): 1000 VRMS for 1 sec.


Construction:

Plug-in terminals are precision spaced to provide fixed mounting centers. Epoxy molded case includes a .020" recess for ease of solder inspection. Leads are Tin plated 0.020" in diameter.



RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

*Upon printing, this document is considered "uncontrolled". Specifications are subjected to change without notice. Please contact Triad Magnetics' website for the most current version.



Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com