

Wall Plug - Ins

WDU9-500

Electrical Specifications (@25C)

- 1. Primary Rating: 120V 60Hz 8.5W
- 2. Primary Excitation Current: 55mA Max
- 3. Secondary Rating: 9VDC ± 5%, 500mADC
- 4. Secondary No-Load Rating: 13.2VDC Ref.
- 5. Output Ripple Voltage: 800mV Max
- 6. Operating Temperature Range: -10 Deg C to +40 Deg C
- 7. Temperature Rise: 75 Deg C Max at rated load

50 Deg C Max on enclosure surface

Mechanical Parameters:

Case Type: Thermoplastic molded enclosure. Output Cord: 24 AWG, 6 Ft. Long Min.

Agency File:


UL/CUL: File E245587, UL 1310

A. Dimensions:

Ι	W	D
60	43	39

*Units: In Millimeter

B. Schematic:



Technical Note: 1. Inside (tip)-positive (+), outside-negative (-)

U.S. DOE Compliance per Sec. 301 of EISA 2007: As of July 1, 2008, this product is intended for use as follows:


- 1. Requires Federal Food and Drug Administration listing and approval as a medical device in accordance with section 513 of the Federal Food, Drug, and Cosmetic Act (21 U.S.C. 360c)
- **2.** Powers the charger of a detachable battery pack or charges the battery of a product that is fully or primarily motor operated.
- 3. As a service part or a spare part for an end-use product manufactured before July 1, 2008, that constitutes the primary load of this power supply.


RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

22520B Temescal Canyon Road Corona, California 92883





NAMEPLATE MARKING



Publish Date: July 20, 2010

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com