



8E9001RS
(ON 0NIMVH) 品名図

版数 REV.	年月日 DATE	DGN NO.	変更内容 DESCRIPTION	製図 DR.	担当 CHK.	査閲 APPD.	承認 APPD.
2	19.Apr.2004	054913	CORRECTION OF SPECIFICATION NO.	H.KOBAYASHI	H.KOBAYASHI	H. Shimazu	A. Onogawa



1. Optical Performance
(The performance when the item is mated with FO-FC-RS-A2)
Insertion Loss 0.5dB Max
note1. The value shows insertion loss in case that a master optical connector, to which PC connection is available, and a master optical connector, to which PC connection is available, are connected.
note2. Order in which the plugs are mated:
1st: FC plug, 2nd: LC plug.

2. Mechanical Performance
Unlock force of lever : 2.9N MIN

1. 光学性能 (FO-FC-RS-A2と嵌合した時の性能である)
挿入損失 0.5dB以下

注1. PC接続が可能なマスター光コネクタとPC接続が可能なマスター光コネクタを接続した場合である。
注2. フラグの結合は、FCプラグ、LCプラグの順とする。

2. 機械性能
レバー離脱力: 2.9N以上

9	PARALLEL PIN	2	STAINLESS STEEL		
8	LEVER B	1	STAINLESS STEEL		
7	LEVER A	1	STAINLESS STEEL		
6	SUS PIPE	1	STAINLESS STEEL		
5	LEVER PIN 2	1	STAINLESS STEEL		
4	LEVER PIN 1	1	STAINLESS STEEL		
3	CONVERSION SLEEVE	1	CERAMIC		
2	LC FLANGE	1	ZINC ALLOY	NICKEL PLATING	
1	LC HOUSING	1	SYNTHETIC RESIN		
符号 NO.	名称 DESCRIPTION	個数 QTY.	材料 MATERIAL	仕上 FINISH	備考 REMARKS

仕様書 (SPECIFICATION)		第1版 (ORIGINAL DATE)		尺貫 (SCALE)	
JACS-70011		31.Mar.2004		N.6	
公差 (GENERAL TOLERANCE)		製図 DR.		名称 (TITLE)	
寸法 (DIMENSION)		担当 CHK.		FO-FC-FS (LC-A2)	
. ±0.8		査閲 APPD.		-STD	
.X ±0.4		承認 APPD.		重量 (WEIGHT)	
.XX ±0.1					
.XXX ±					
角度 (ANGLES)					
.° ±					
.°X' ±					

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com