

| CONFIGURATION                                                                                                                                                                                                                                                                     |                                                                  | PART NUMBER |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|-------------|
| Male Jamnut Receptacle, 3 Pin, 16 Awg, Shell 12                                                                                                                                                                                                                                   |                                                                  | RT07123PNH  |
| DIMENSIONS                                                                                                                                                                                                                                                                        |                                                                  |             |
| <p>Technical drawing showing dimensions and components of the Male Jamnut Receptacle. Dimensions include 33.0, 21.10, 19.30, 10.00, 19.00, 22.50, and 31.8. Components labeled include 11/16-24 UNEF, O-Ring, O-Ring, Fixed In Position, Nut, Insert, Seal Gasket, and Shell.</p> |                                                                  |             |
| <p>Panel Cut out Reference</p>                                                                                                                                                                                                                                                    |                                                                  |             |
| TECHNICAL DATA                                                                                                                                                                                                                                                                    |                                                                  |             |
| TEMPERATURE RANGE:                                                                                                                                                                                                                                                                | -40°C to + 105°C                                                 |             |
| PROTECTION:                                                                                                                                                                                                                                                                       | IP67 in mated condition and in combination with sealed backshell |             |
| VOLTAGE RATING:                                                                                                                                                                                                                                                                   | 250V                                                             |             |
| HOUSING BODY:                                                                                                                                                                                                                                                                     | Zinc Alloy, Nickel Plated                                        |             |
| COUPLING NUT:                                                                                                                                                                                                                                                                     | -                                                                |             |
| INSERT:                                                                                                                                                                                                                                                                           | Glass-filled Thermoplastic UL94-V0                               |             |
| SEAL:                                                                                                                                                                                                                                                                             | NBR                                                              |             |
| CURRENT:                                                                                                                                                                                                                                                                          | 13A                                                              |             |
| CONTACT SIZE:                                                                                                                                                                                                                                                                     | 16Awg                                                            |             |
| APPROVALS:                                                                                                                                                                                                                                                                        | UL ECBT2                                                         |             |

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email      mkt@ameya360.com