



VRLA Rechargeable Battery

BP4.5-6



FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

APPLICATION

- UPS
- Electronic Toy-Cars
- Fans
- Emergency Lights
- Rechargeable Flashlights



SPECIFICATIONS

Nominal Voltage	6 V
Nominal Capacity	4.5Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	910g(2.0lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	$\leq 21m\ \Omega$ (Fully Charged)
Max. Discharge Current	67.5 A (5 sec.)
Max. Charge Current	1.35 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL 94-HB) BP4.5-6 Optional: Flame Retardant ABS(UL 94-V0) BP4.5-6FR



- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
Length 70±1.5 (2.76±0.06) Width 48±1.5 (1.89±0.06) Container Height 102±1.5 (4.02±0.06) Total Height 107±2.0 (4.21±0.08)		Terminal T1 Terminal T2

Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	81.35	59.89	47.99	28.55	16.38	6.558	4.522	2.527	1.330
1.75V	94.16	64.88	50.20	29.64	16.87	6.690	4.590	2.565	1.350
1.70V	100.04	67.21	51.75	30.32	17.17	6.750	4.615	2.578	1.356
1.65V	104.54	68.82	52.94	30.74	17.38	6.797	4.631	2.586	1.362
1.60V	108.00	70.20	54.00	31.05	17.55	6.838	4.645	2.586	1.362

Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	14.66	10.54	8.35	4.84	2.752	1.093	0.754	0.421	0.222
1.75V	17.28	11.42	8.73	5.02	2.835	1.115	0.765	0.427	0.225
1.70V	18.36	11.83	9.00	5.14	2.886	1.125	0.769	0.430	0.226
1.65V	19.18	12.12	9.21	5.21	2.920	1.133	0.772	0.431	0.227
1.60V	19.82	12.36	9.39	5.26	2.950	1.140	0.774	0.431	0.227

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com