

1	2	3	4	5																																																												
		RECOMMENDED PCB LAYOUT - COMPONENT VIEW																																																														
		<table><tr><th colspan="4">Pitch : 5.00mm</th></tr><tr><th>Poles</th><th>A(mm)</th><th>Poles</th><th>A(mm)</th></tr><tr><td>2</td><td>11.00</td><td>15</td><td>76.00</td></tr><tr><td>3</td><td>16.00</td><td>16</td><td>81.00</td></tr><tr><td>4</td><td>21.00</td><td>17</td><td>86.00</td></tr><tr><td>5</td><td>26.00</td><td>18</td><td>91.00</td></tr><tr><td>6</td><td>31.00</td><td>19</td><td>96.00</td></tr><tr><td>7</td><td>36.00</td><td>20</td><td>101.00</td></tr><tr><td>8</td><td>41.00</td><td>21</td><td>106.00</td></tr><tr><td>9</td><td>46.00</td><td>22</td><td>111.00</td></tr><tr><td>10</td><td>51.00</td><td>23</td><td>116.00</td></tr><tr><td>11</td><td>56.00</td><td>24</td><td>121.00</td></tr><tr><td>12</td><td>61.00</td><td>25</td><td>126.00</td></tr><tr><td>13</td><td>66.00</td><td></td><td></td></tr><tr><td>14</td><td>71.00</td><td></td><td></td></tr></table>			Pitch : 5.00mm				Poles	A(mm)	Poles	A(mm)	2	11.00	15	76.00	3	16.00	16	81.00	4	21.00	17	86.00	5	26.00	18	91.00	6	31.00	19	96.00	7	36.00	20	101.00	8	41.00	21	106.00	9	46.00	22	111.00	10	51.00	23	116.00	11	56.00	24	121.00	12	61.00	25	126.00	13	66.00			14	71.00		
Pitch : 5.00mm																																																																
Poles	A(mm)	Poles	A(mm)																																																													
2	11.00	15	76.00																																																													
3	16.00	16	81.00																																																													
4	21.00	17	86.00																																																													
5	26.00	18	91.00																																																													
6	31.00	19	96.00																																																													
7	36.00	20	101.00																																																													
8	41.00	21	106.00																																																													
9	46.00	22	111.00																																																													
10	51.00	23	116.00																																																													
11	56.00	24	121.00																																																													
12	61.00	25	126.00																																																													
13	66.00																																																															
14	71.00																																																															
TECHNICAL CHARACTERISTICS MATERIAL INSULATOR: PA 66 FLAMABILITY RATING: UL94-V0 COLOR: GREY/WHITE WIRE GUARD: STAINLESS STEEL CONTACT: BRASS SOLDER TAIL PLATING: TIN ENVIRONMENTAL OPERATING TEMPERATURE: -40 UP TO 105°C COMPLIANCE: LEAD FREE AND ROHS ELECTRICAL CURRENT RATING: 16A WORKING VOLTAGE: 300VAC WITHSTANDING VOLTAGE: 1.3KV CONTACT RESISTANCE: 20 mOhm max STANDARD CERTIFIED E315414 / MODEL NUMBER 4147 B MECHANICAL SOLID WIRE: 28-14 AWG / 0.08-3.3MM² STRANDED WIRE: 28-14 AWG / 0.08-3.3MM² WIRE STRIPE LENGTH: 6-7MM PITCH: 5.00MM SOLDERING: WAVE PROCESS ONLY PACKAGING: BOX SERIE 4147 B																																																																
<table><tr><td colspan="4">RoHS Compliant</td></tr><tr><td>G</td><td></td><td></td><td></td></tr><tr><td>F</td><td></td><td></td><td></td></tr><tr><td>E</td><td></td><td></td><td></td></tr><tr><td>D</td><td></td><td></td><td></td></tr><tr><td>C</td><td></td><td></td><td></td></tr><tr><td>B</td><td>29-JUL-13</td><td>DWG REVIEW</td><td>QL</td></tr><tr><td>A</td><td>02-JUL-12</td><td>PDF</td><td>GG</td></tr><tr><td>REV</td><td>DATE</td><td>FILE</td><td>BY</td></tr></table>					RoHS Compliant				G				F				E				D				C				B	29-JUL-13	DWG REVIEW	QL	A	02-JUL-12	PDF	GG	REV	DATE	FILE	BY																								
RoHS Compliant																																																																
G																																																																
F																																																																
E																																																																
D																																																																
C																																																																
B	29-JUL-13	DWG REVIEW	QL																																																													
A	02-JUL-12	PDF	GG																																																													
REV	DATE	FILE	BY																																																													
		PROJECTION: GENERAL TOLERANCE .X = $\pm$ 0.2 .XX = $\pm$ 0.15 WÜRTH ELEKTRONIK																																																														
		APPROVAL: RJ UNIT: MM SCALE: SHEET: 1/1 DRAW: MARVIN DESCRIPTION: SERIE 4147 - 5.00MM SCREWLESS 45° ENTRY 3.3MM² WIRES WR-TBL WERI PART NO: 691 414 720 0xx B SIZE A4																																																														

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com