



**Regular Nytyes**

- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.

**Screw Mountable Nytyes**

- Molded-in screw hole mount provides one-piece mounting and bundling.
- Mounting screws not included.

**Push Mountable Nytyes**


- Snap quickly into holes with only fingertip pressure.
- Provide one-piece mounting and bundling.
- Hold securely in panels up to 1/8" (3,2 mm) thick.





## Heyco® Nytye® Nylon Cable Ties

| PART SPECIFICATIONS           |     |                                |       | PART NO. |          | DESCRIPTION  | PART DIMENSIONS |     |         |     |             |     |                     |                    |         |    |
|-------------------------------|-----|--------------------------------|-------|----------|----------|--------------|-----------------|-----|---------|-----|-------------|-----|---------------------|--------------------|---------|----|
| Max. Tensile Strength         |     | Max. Bundle Diameter           |       | Natural  | UV Black |              | A Length        |     | B Width |     | C Thickness |     | Min Bundle Diameter |                    |         |    |
| lbs.                          | N   | in.                            | mm.   |          |          | in.          | mm.             | in. | mm.     | in. | mm.         | in. | mm.                 |                    |         |    |
| <b>Regular Nytyes®</b>        |     |                                |       |          |          |              |                 |     |         |     |             |     |                     |                    |         |    |
| 18                            | 80  | .75                            | 19,1  | 3500     | 3502     | NT 70        | 3.80            | 97  | .09     | 2,3 | .05         | 1,1 |                     |                    |         |    |
|                               |     | 1.50                           | 38,1  | 3503     | 3504     | NT 70L       | 6.25            | 159 |         |     |             |     |                     |                    |         |    |
|                               |     | 2.00                           | 50,8  | 3506     | 3507     | NT 70E       | 8.00            | 203 |         |     |             |     |                     |                    |         |    |
| 30                            | 133 | 1.00                           | 25,4  | 3510     | 3511     | NT 90        | 5.20            | 132 | .12     | 2,9 |             |     |                     |                    |         |    |
|                               |     | 1.25                           | 31,8  | 3515     | 3516     | NT 120       | 5.67            | 144 |         |     |             |     |                     |                    |         |    |
| 40                            | 178 | 2.00                           | 50,8  | 3850     | 3851     | NT 170       | 8.25            | 210 | .14     | 3,4 | .06         | 1,4 | .06                 | 1,6                |         |    |
|                               |     | 1.75                           | 44,4  | 3520     | 3521     | NT 150       | 7.50            | 191 |         |     |             |     |                     |                    |         |    |
| 50                            | 222 | 3.00                           | 76,2  | 3525     | 3526     | NT 250       | 11.25           | 286 | .19     | 4,8 | .06         | 1,4 |                     |                    |         |    |
|                               |     | 4.00                           | 101,6 | 3530     | 3531     | NT 330       | 14.50           | 368 |         |     |             |     |                     |                    |         |    |
|                               |     | <b>Screw Mountable Nytyes®</b> |       |          |          |              |                 |     |         |     |             |     |                     |                    |         |    |
| 30                            | 133 | 1.00                           | 25,4  | 3550     | -        | MNT 90       | 5.50            | 140 | .12     | 2,9 | .05         | 1,1 |                     |                    | Screw # | 4  |
| 40                            | 178 | 1.25                           | 31,8  | 3555     | -        | MNT 120      | 6.50            | 165 | .14     | 3,4 | .05         | 1,3 |                     |                    |         | 8  |
| 50                            | 222 | 1.75                           | 44,4  | 3560     | -        | MNT 150      | 8.00            | 203 | .19     | 4,8 | .06         | 1,4 |                     |                    |         | 10 |
| <b>Push Mountable Nytyes®</b> |     |                                |       |          |          |              |                 |     |         |     |             |     |                     | Mounting Hole Dia. |         |    |
| 40                            | 180 | 1.42                           | 36,0  | -        | 3907     | PWMS-155 HSB | 6.23            | 158 | .14     | 3,5 | .05         | 1,2 | .19                 | 4,6                |         |    |
| 50                            | 222 | 1.75                           | 44,4  | 3904     | -        | PMT 150      | 8.00            | 203 | .19     | 4,8 | .06         | 1,4 | .25                 | 6,4                |         |    |


Standard color natural. UV Black at extra charge. Consult Heyco for Nytyes in colors.




Regular Nytyes



Screw Mountable Nytyes



Push Mountable Nytyes



Quick Specs

|                     |  |
|---------------------|--|
| Material            | Nylon 6/6  |
| Certifications      | Recognized under the Component Program of Underwriters' Laboratories File E54523 |
| Flammability Rating | 94V-2  |
| Temperature Range   | 32°F (0°C) to 185°F (85°C)   |

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)