

PowerTool MAXPOWERTOOL002# Quick Start Guide



The MAXPOWERTOOL002# is a USB-to-PMBus™ interface dongle for exclusive use with Maxim Integrated's digital power products. The dongle can be used to communicate with PMBus devices using the installed PowerTool software.

1. Download and install the PowerTool software available at:
<http://content.maximintegrated.com/en/design/tools/applications/evkit-software/index.mvp/id/1183>
2. Remove the MAXPOWERTOOL002# from the package.
3. Connect the provided USB cable and ribbon cable as shown in Figure 1. The STATUS LED on the MAXPOWERTOOL002# illuminates. The color of the LED indicates the device's status as follows:
 - **Steady GREEN color:** No I²C communication is in progress.
 - **Blinking ORANGE color:** The device is communicating I²C data.
 - **Steady RED color:** I²C communication has been interrupted.



Figure 1. MAXPOWERTOOL002# Installation

Features:

- Supports 100kHz and 400kHz I²C communication speeds
- USB-to-SMBus conversion for Maxim digital power evaluation kits
- Uses USB only for power

For additional information, visit: www.maximintegrated.com.

PMBus is a trademark of SMIF, Inc.

Revised 10/14

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com