

**Micro Commercial Components** 

Pb

**MAKING:KGJ** 


Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

## **BAV99BRW**

## **Features**

- Lead Free Finish/Rohs Compliant ("P"Suffix designates RoHS Compliant. See ordering information)
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Low Current Leakage
- Low Cost
- Small Outline Surface Mount Package



# **Maximum Ratings**


- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C


#### Electrical Characteristics @ 25°C Unless Otherwise Specified


	1		1
Reverse Voltage	$V_R$	75V	
Average Rectified	Ιο	150mA	
Output Current			
Peak Forward	I <sub>FSM</sub>	1.0A	t=1s, Non-Repetitive
Surge Current		2.0A	t=1us, Non-Repetitive
Power Dissipation	P <sub>TOT</sub>	200mW	
Maximum Instantaneous Forward Voltage	V <sub>F</sub>	715mV 855mV 1000mV 1250mV	I <sub>FM</sub> = 1mA; I <sub>FM</sub> = 10mA; I <sub>FM</sub> = 50mA; I <sub>FM</sub> = 150mA;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	2.5uA 0.025uA	VR=75V VR=20V
Typical Junction Capacitance	CJ	2.0pF	Measured at 1.0MHz, V <sub>R</sub> =0V
Reverse Recovery Time	T <sub>rr</sub>	4nS	$I_F=I_R=10$ mA $I_{rr}=0.1$ * $I_R$ $R_c=100\Omega$

# 200mW 75Volt Plastic-Encapsulate Diode










DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.006	.014	0.15	0.35		
В	.045	.053	1.15	1.35		
С	.085	.096	2.15	2.45		
D	.026		0.65Nominal			
Ð	.047	.055	1.20	1.40		
Τ	.071	.087	1.80	2.20		
J		.004		0.10		
K	.035	.043	0.90	1.10		
Ĺ	.010	.018	0.26	0.46		
М	.003	.006	0.08	0.15		




# **Typical Characteristics**

## **BAV99BRW**




1.8 1.6 C<sub>T</sub>, TOTAL CAPACITANCE (pF) 1.4 1.2 1.0 8.0 0.6 0.4 0.2 0.0 0 10 30 40 20

 $\label{eq:VR} {\rm V_{R},\ REVERSE\ VOLTAGE\ (V)}$  Fig. 3 Typical Capacitance vs. Reverse Voltage



V<sub>R</sub>, INSTANTANEOUS REVERSE VOLTAGE (V) Fig. 2 Typical Reverse Characteristics



T<sub>A</sub>, AMBIENT TEMPERATURE (°C) Fig. 4 Power Derating Curve, Note 1



#### **Micro Commercial Components**

### Ordering Information:

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# AMEYA360 Components Supply Platform

## **Authorized Distribution Brand:**

























## Website:

Welcome to visit www.ameya360.com

## Contact Us:

## > Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

## > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

## Customer Service :

Email service@ameya360.com

# Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com