

**Control Transformer Class 2** 

# **ТСТ40-06Е07АВ**

#### **Description:**

Triad control transformers come with tamper resistant shrouds for safety and a steel bracket welded to the bottom of the transformer for ease of mounting. These transformers are design and have the safety agency recognition for application where a Class 2 transformer is necessary. Some of the applications would include, but not limited to HVAC, Control boards, Lighting, etc.

#### **Electrical Specifications (@25C):**

- 1. Maximum Power: 40VA
- 2. \*Input: 120V, 50/60 Hz
  - 240V, 50/60Hz
- 3. Output: 24V @ 1.67Amps
- 4. Voltage Regulation: 15% TYP @ full load to no load
- 5. Temperature Rise: <40°C TYP
- 6. Hipot: 1500VAC Input to Output, Input & Output to Core
- 7. Inherently Limited. No fusing required.
- \* Only one input voltage to be applied to primary at any time.

#### **Construction:**

Three flange bobbin construction with primaries and secondaries wound side by side for low capacitive coupling. Unit weight is 1.5lbs.

#### Agency File:


UL: File E65390, UL 5085-3 (1585), Class 2 Transformer cUL: File E65390, UL 5085-3 (1585) For Canadian Use (CSA 22.2, No.66.3-06)



#### **Connections:**

Input: Quick Disconnect tabs, 0.5 x 0.25 x 0.032 Output: Quick Disconnect tabs, 0.5 x 0.25 x 0.032

#### Schematic:




**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.


As of April 7, 2008, UL standards 506 and 1585 will be migrated to UL 5085-2 and 5085-3, respectively.


\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

460 Harley Knox Blvd. Perris, California 92571









Publish Date: December 4, 2013



# Authorized Distribution Brand :



### Website :

Welcome to visit www.ameya360.com

# Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

- > Sales :
  - Direct +86 (21) 6401-6692
  - Email amall@ameya360.com
  - QQ 800077892
  - Skype ameyasales1 ameyasales2

### > Customer Service :

Email service@ameya360.com

## > Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com